

TOWN OF GLASTONBURY

INVITATION TO BID

<u>BID #</u>	<u>ITEM</u>	<u>DATE & TIME REQUIRED</u>
GL-2017-26	Locker Room Renovation Glastonbury Police Department	May 11, 2017 @ 11:00 a.m.

The Town of Glastonbury is seeking bids for the Renovation of the Mens and Womens Locker Rooms at the Glastonbury Police Department, 2108 Main Street, Glastonbury, CT 06033

A mandatory pre-bid meeting and site walk through will be held starting at the Glastonbury Police Department 2108 Main Street, Glastonbury, CT 06033 on April 26, 2017 at 9:00 a.m. All bidders must attend in order for their bid to be considered.

Bid Forms may be downloaded from the Town’s website at www.glastonbury-ct.gov or the State of Connecticut Department of Administrative Services website at www.das.state.ct.us at no cost.

Prevailing Wages: The contractor must comply with Section 31-53 of the Connecticut General Statutes as amended, including annual adjustments in prevailing wages.

Bid Security shall be issued payable to the “Town of Glastonbury” in the form of a certified check or Bid Bond in an amount not less than 10% of the total amount of the base bid. The Bid Bond must be issued by a surety company licensed in the State of Connecticut. Cashier’s checks will not be accepted.

The Town reserves the right to waive informalities or reject any part of, or the entire bid, when said action is deemed to be in the best interest of the Town. All Sealed Bids must be submitted to the Office of the Purchasing Agent no later than the time and date indicated. All bids will be publicly opened and read.

The Town of Glastonbury is an Affirmative Action/Equal Opportunity Employer. Minority/Women/Disadvantaged Business Enterprises are encouraged to bid.

Mary F. Visone
Purchasing Agent

TABLE OF CONTENTS

SECTION

Invitation to Bid	
Table of Contents	TC - 1
Information for Bidders	IB 1-4
General Construction Specifications	GCS 1-6
Special Conditions	SC 1-3
Insurance Requirements	IR 1
List of Drawings	1
Bid Proposal	BP 1-2
Wage Rates	15 pages
Specifications/Project Manual	130 pages
Drawings	9 pages

TOWN OF GLASTONBURY
Locker Room Renovations Police Department
INFORMATION FOR BIDDERS

BID #GL-2017-26

1. Sealed bids (**one original and one copy**) on the attached Bid Forms will be received at the Office of the Purchasing Agent, Town Hall, 2155 Main Street, Glastonbury, Connecticut, 06033 (second level). At the designated time of opening, they will be publicly opened, read, recorded and placed on file.
2. Whenever it is deemed to be in the best interest of the Town, the Town Manager, Purchasing Agent or designated representative shall waive informalities in any and all bids. The right is reserved to reject any bid, or any part of any bid, when such action is deemed to be in the best interest of the Town of Glastonbury.
3. The basis of award will be based on the lump sum bid of the lowest qualified, responsible and responsive bidder.
4. Bids will be carefully evaluated as to conformance with stated specifications.
5. The envelope enclosing your bid should be clearly marked by your company name and address, bid number, time of bid opening, and date.
6. Specifications must be submitted complete in every detail and, when requested, samples shall be provided. If a bid involves any exception from stated specifications, they must be clearly noted as exceptions, underlined, and attached to the bid.
7. The Bid Documents contain the provisions required for the requested item. Information obtained from an officer, agent, or employee of the Town or any other person shall not affect the risks or obligations assumed by the Bidder or relieve him/her from fulfilling any of the conditions of the bid.
8. Each Bidder is held responsible for the examination and/or to have acquainted themselves with any conditions at the job site which would affect their work before submitting a bid. Failure to meet these criteria shall not relieve the Bidder of the responsibility of completing the bid without extra cost to the Town of Glastonbury.
9. Any bid may be withdrawn prior to the above-scheduled time for the opening of bids or authorized postponement thereof. Any bid received after the time and the date specified shall not be considered. No bidder may withdraw a bid within sixty (60) days after the actual date of the opening thereof. Should there be reasons why a bid cannot be awarded within the specified period, the time may be extended by mutual agreement between the Town and the Bidder.
10. Each bid must be accompanied by a bid bond payable to the Town for ten percent (10%) of the total amount of the bid. The bid bond of the successful bidder will be retained until the payment bond and performance bond have been executed and approved, after which it will be returned. A certified check may be used in lieu of a bid bond. The Town of Glastonbury will not be liable for the accrual of any interest on any certified check submitted. Cashier's checks will not be accepted.
11. A 100% Performance and Payment bond is required of the successful bidder. This bond shall cover all aspects of the specification and shall be delivered to the Purchasing Agent prior to the issuance of a purchase order. The Performance and Payment Bond will be returned upon the delivery and acceptance of the bid items.

12. The Bidder agrees and warrants that in the submission of this sealed Bid, they will not discriminate or permit discrimination against any person or group of persons on the grounds of race, color, religion, national origin, sex, or physical disability including, but not limited to blindness, unless it is shown by such Bidder that such disability prevents performance of that which must be done to successfully fulfill the terms of this sealed Bid or in any manner which is prohibited by the laws of the United States or the State of Connecticut: and further agrees to provide the Human Relations Commission with such information requested by the Commission concerning the employment practices and procedures of the Bidder. An Affirmative Action Statement will be required by the successful Bidder.
13. Bidder agrees to comply with all of the latest Federal and State Safety Standards and Regulations and certifies that all work required in this bid will conform to and comply with said standards and regulations. Bidder further agrees to indemnify and hold harmless the Town for all damages assessed against the Town as a result of Bidder's failure to comply with said standards and/or regulations.
14. All correspondence regarding any purchase made by the Town of Glastonbury shall reference the Town purchase order number. Each shipping container shall clearly indicate both purchase order number and item number.
15. Bidder is required to review the Town of Glastonbury Code of Ethics adopted July 8th, 2003 and effective August 1, 2003 and revised October 29, 2013 and effective November 28, 2013. Bidder shall acknowledge that they have reviewed the document in the area provided on the bid / proposal response page (BP). The selected Bidder will also be required to complete and sign an Acknowledgement Form prior to award. The Code of Ethics and the Consultant Acknowledgement Form can be accessed at the Town of Glastonbury website at www.glastonbury-ct.gov. Upon entering the website click on **Bids & Proposals Icon**, which will bring you to the links for the **Code of Ethics** and the **Consultant Acknowledgement Form**. If the Bidder does not have access to the internet a copy of these documents can be obtained through the Purchasing Department at the address listed within this bid / proposal.
16. Any bidder, in order to be considered, shall be engaged primarily in the business of construction with for minimum of five (5) years and have a valid contractor's license in the State of Connecticut.
17. **Non-Resident Contractors (IF APPLICABLE):Resident Contractors:**

Upon award the Town is required to report names of nonresident (out of state) Contractors to the State of Connecticut, Department of Revenue Services (DRS) to ensure that Employment Taxes and other applicable taxes are being paid by Contractors. **A single surety bond for 5% of the entire contract price is required to be filed with DRS by any unverified nonresident prime or general contractor (if awarded) where the contract price for the project is \$250,000 or more.** The contractor will be required to promptly furnish to the Town a copy of the **Form AU-968 - Certificate of Compliance** issued by the State of Connecticut, DRS. See State of Connecticut **Notice SN 2012 (2)**.
18. Bidder shall include on a sheet(s) attached to its proposal a complete disclosure of all past and pending mediation, arbitration and litigation cases that the bidder or its principals (regardless of their place of employment) have been involved in for the most recent five years. Please include a

statement of the issues in dispute and their resolution. Acceptability of Bidder based upon this disclosure shall lie solely with the Town.

19. Bidder or its principals, regardless of their place of employment, shall not have been convicted of, nor entered any plea of guilty, or nolo contendere, or otherwise have been found civilly liable or criminally responsible for any criminal offense or civil action. Bidder shall not be in violation of any State or local ethics standards or other offenses arising out of the submission of bids or proposals, or performance of work on public works projects or contracts.
20. After award of Contract, Owner will require the Contractor's Schedule of Values, which shall be submitted at the preconstruction meeting. The Schedule of Values must accurately reflect job costs and include a complete breakdown of material and labor costs.
21. Prevailing Wage Rates:

Bidders shall comply with State Statutes concerning Employment and Labor Practices, if applicable, and Section 31-53 of the Connecticut General Statutes, as amended (Prevailing Wages). Wage Rate Determination for this project from the State of Connecticut is included in the Bid Documents. Certified payrolls for site labor shall be submitted weekly to the Town's Representative or his designee on the correct State of Connecticut form. The Town reserves the right to, without prior notice, audit payroll checks given to workers on site in order to ascertain that wages and fringe benefits are being paid as required by the State of Connecticut. Please make special note of the State requirement to adjust wage and fringe benefit rates on each July 1st following the original published rates.

NOTE that bidder is to include in its bid proposal all costs required by such annual increases in the PREVAILING RATES. No Escalation Clauses are to be included in the bidder's proposal and no Escalation Clauses will be in the Contract Agreement. Bidder is to anticipate any future increases and include these costs in its quotation.

Contractor's invoices will not be paid if certified payrolls are incomplete, incorrect or not received in a timely manner.

All Apprentices must be registered with the State of Connecticut and their number shall not exceed the number allowed by law. Otherwise, all workers must be paid at least the Journeyman rate listed including benefits.

OSHA SAFETY AND HEALTH CERTIFICATION: Effective July 1, 2009: Any Mechanic, Laborer, or Worker, who performs work in a classification listed on the prevailing wage rate schedule on any public works project covered under C.G.S. Section 31-53, both on site and on or in the public building, must have completed a federal OSHA Safety and Health course within the last 5 years.

22. Each Bidder shall submit a list of similar projects completed within the last three years. In order to be eligible for consideration, the Bidder must have successfully completed a minimum of five (5) similar projects within the last three (3) years. Please provide project name and contact information for project coordinator (name, title, address, phone number). Please also provide contract value.

23. For technical questions regarding this Bid, please contact David Sacchitella, Building Superintendent, at (860) 652-7706, email dave.sacchitella@glastonbury-ct.gov. For administrative questions regarding this Bid, please contact Mary F. Visone, Purchasing Agent at (860) 652-7588, email purchasing@glastonbury-ct.gov. The request must be received at least five (5) business days prior to the advertised response deadline. All questions, answers, and/or addenda, as applicable, will be posted on the Town's website at www.glastonbury-ct.gov (Upon entering the website click on Bids & Proposals Icon; click the Bid Title to view all bid details and document links). It is the respondent's responsibility to check the website for addenda prior to submission of any proposal.

IMPORTANT:

- Failure to comply with general rules may result in disqualification of the Bidder.
- Municipal projects are exempt from Federal Excise Taxes, as well as, State of Connecticut Sales, Use and Service Taxes and should not be include in the Bidder's proposal.

01.00 WORKMANSHIP, MATERIALS AND EMPLOYEES

- 01.01 Wherever in this contract the word “Engineer” is used, it shall be understood as referring to the Building Superintendent of the Town of Glastonbury acting personally or through any assistants duly authorized.
- 01.02 The entire work described herein shall be completed in accordance with the plans and specifications to the full intent and meaning of the same. Unless otherwise specified, all materials incorporated in the permanent work shall be new, and both workmanship and material shall be of good quality. The Contractor shall, if required, furnish satisfactory evidence as to the kind and quality of materials.
- 01.03 The wording “furnish”, “install”, “construct”, “furnish and install”, or any similar terms, unless specifically noted to the contrary, shall include all labor, materials, water, tools, equipment, light, power, transportation, and any other services required for the completion of the work.
- 01.04 The Contractor shall at all times enforce strict discipline and good order among his employees, and shall seek to avoid employing on the work any unfit person or anyone not skilled in the work assigned to him.

02.00 SUPERINTENDENT

- 02.01 The Contractor shall keep on the work during its progress, in the absence of the Contractor, a competent Superintendent. The Superintendent shall be acceptable to the Engineer and shall fully represent the Contractor. All directions given to the Superintendent shall be binding as if given to the Contractor.

03.00 PRECONSTRUCTION MEETING

- 03.01 A Preconstruction Meeting will be held with the Engineer, Contractor, and any other interested parties prior to commencing any work. The Engineer shall arrange the meeting based on a mutually convenient time.

04.00 PERMITS

- 04.01 All permits, licenses, and fees required for the performance of the Contract work shall be secured and paid for by the Contractor. The local building permit fees will be waived.

05.00 PROPERTY ACCESS

- 05.01 The Contractor shall take all proper precautions to protect from injury or unnecessary interference, and provide proper means of access to abutting property where the existing access is cut off by the Contractor.
- 05.02 The Contractor shall take all proper precautions to protect persons from injury or unnecessary inconvenience and leave an unobstructed way along the public and private places for travelers, vehicles, and access to hydrants.

05.03 The Contractor shall make arrangements with the adjacent property owners for such trespass as he may reasonably anticipate in the performance of the work. All such arrangements shall be reported, in writing, to the Engineer.

06.00 PROTECTION OF THE PUBLIC AND OF WORK AND PROPERTY

06.01 The Contractor shall continuously maintain adequate protection of all work from damage, and shall take all reasonable precautions to protect the Town from injury or loss arising in connection with the Contract.

06.02 The Contractor shall adequately protect adjacent private and public property as provided by law and the Contract Documents.

06.03 The Contractor shall make good any damage, injury, or loss of work and to the property of the Town resulting from lack of reasonable protective precautions.

06.04 The police building involved will be occupied during the work and fully operational. The Contractor may be required to adjust his work schedule should the work have an adverse impact on operations. There will be no modification of the bid price should a schedule adjustment be required.

07.00 EXISTING IMPROVEMENTS

07.01 The Contractor shall conduct his work so as to minimize damage to existing improvements designated to remain. Except where specifically stated otherwise in the specifications, drawings, or as directed by the Engineer, it will be the responsibility of the Contractor to restore to their original condition, as near as practical, all improvements on public or private property. This shall include:

- a. Property within and adjacent to the work area such as shrubs, walks, driveways, fences, etc.
- b. Utility mains, ducts, poles, and services. The Contractor is hereby notified that utilities, if/where shown on the plans, are at approximate locations. These locations are subject to possible errors in the source of information and errors in transcription. The Contractor shall make certain of the exact location of all mains, ducts, poles, and services prior to excavation.

08.00 SEPARATE CONTRACTS

08.01 The Engineer reserves the right to let other contracts in connection with this work. The Contractor shall afford other contractors reasonable opportunity for the introduction and storage of their materials and the execution of their work, and shall properly connect and coordinate his work with theirs. Wherever work being done by the Town of Glastonbury forces or by other contractors is contiguous to work covered by this Contract, the respective rights of the various interests involved shall be established by the Engineer to secure the completion of the various portions of the work.

09.00 INSPECTION OF WORK

09.01 The Town shall provide sufficient personnel for the inspection of the work.

09.02 The Engineer shall at all times have access to the work whenever it is in preparation or progress, and the Contractor shall provide proper facilities for such access and for inspection.

09.03 If the specifications or the Engineer's instructions require any work to be specially tested or approved, the Contractor shall give the Engineer timely notice of its readiness for inspection and, if the inspection is by another authority other than the Engineer, of the date fixed for such inspection. Inspections by the Engineer shall be made promptly. If any work should be covered up without approval or consent of the Engineer, it must, if required by the Engineer, be uncovered for examination and properly restored at the Contractor's expense.

09.04 Re-inspection of any work may be ordered by the Engineer. If such work is found to be in accordance with the Contract Documents, the Town shall pay the cost of re-inspection and replacement. If such work is not in accordance with the Contract Documents, the Contractor shall pay such cost.

10.00 RIGHT TO INCREASE OR DECREASE WORK

10.01 The Town shall have the right to increase or decrease the amount of work herein specified as may be required.

11.00 RIGHT OF ENGINEER TO STOP WORK FOR WEATHER CONDITIONS

11.01 Should the work, in the opinion of the Engineer, be in danger by reason of inclemency of weather, or could not be finished in time to prevent such danger, the Contractor shall cease operations upon order of the Engineer, and shall not resume them until ordered to do so by the Engineer when the weather conditions are favorable. The Contractor shall, upon such orders, discontinue work, remove all materials or appliances for or in use upon the work, and place the premises in proper condition for use by the public during the time the work is suspended as herein provided, without cost to the Town.

12.00 CONTRACTOR TO BE RESPONSIBLE FOR IMPERFECT WORK OR MATERIALS

12.01 Any faithful work or imperfect material that may be discovered before the acceptance and the payment of the work shall be corrected upon the order of the Engineer. The acceptance and payment of the work does not in any manner relieve the Contractor of his obligation to construct work in the proper manner and the use of materials herein specified.

13.00 TOWN MAY NOTIFY CONTRACTOR IF WORK IS NOT CARRIED ON SATISFACTORILY

13.01 If, in the opinion of the Engineer, the Contractor is not proceeding with the work at a sufficient rate of progress so as to finish in the time specified, or has abandoned said work, or is not complying with the terms and stipulations or the Contract and specifications, the Engineer may serve notice on the Contractor to adopt such methods as will ensure the completion of the work in the time specified.

13.02 If, within five days after the Engineer has notified the Contractor that his work is not being carried on satisfactorily as before mentioned, the Engineer shall have the right to annul the

Contract and manage the work under the direction of the Engineer, or re-let, for the very best interest of the Town as a new contract, the work under said new Contract shall be considered the responsibility of the defaulting Contractor.

- 13.03 Additional costs incurred over and above the original Contract shall be borne by the Performance Bond.

14.00 DEDUCTIONS FOR UNCORRECTED WORK

- 14.01 If the Engineer deems it inexpedient to correct work that has been damaged or that was not done in accordance with the Contract, an equitable deduction from the Contract price shall be made there for.

- 14.02 The Contractor shall promptly remove from the premises all materials condemned by the Engineer as failing to meet Contract requirements, whether incorporated in the work or not, and the Contractor shall promptly replace and re-execute his own work in accordance with the Contract and without expense to the Town, and shall bear the expense of making good all work by other contractors destroyed or damaged by such removal or replacement.

- 14.03 If the Contractor does not remove such condemned work and materials as promptly as possible after written notice, the Engineer may remove them and store the materials at the expense of the Contractor.

15.00 CLEANING UP

- 15.01 The Contractor must remove all debris of every description as the work progresses and leave the surroundings in a neat and orderly condition to the satisfaction of the Engineer.

- 15.02 Upon completion, and before acceptance and final payment, the Contractor shall remove from the site all equipment, forms, surplus material, rubbish and miscellaneous debris and leave the site in a neat and presentable condition.

16.00 ROYALTIES AND PATENTS

- 16.01 The Contractor shall pay all royalties and license fees. He shall defend all suits or claims for infringement of any patent rights and shall save the Town of Glastonbury harmless from loss on account hereof, except that the Town of Glastonbury shall be responsible for all such loss when a particular manufacturer, product, or process is specified by the Town of Glastonbury.

17.00 ERRORS OR CONFLICT IN DRAWINGS AND SPECIFICATIONS

- 17.01 The Contractor shall immediately notify the Owner/Engineer should he find any errors or conflicts in the contract documents. The Owner/Engineer shall render his interpretation or instruction in writing on the items as soon as possible.

- 17.02 Any work undertaken by the Contractor containing possible errors or conflicts will be done at his own risk unless he has received prior written approval from the Owner/Engineer.

17.03 The Contractor shall be responsible for estimating and supplying all quantities, and where clarification or additional information is required, a request in writing to the Owner/Engineer shall be made. No extra charge or compensation will be allowed the Contractor unless there is a change in scope or dimension of the project resulting in need for extra material, equipment and/or labor. Said differences are to be handled under Article 18.

18.00 EXTRA WORK AND EXTRA COST

18.01 The Owner, without invalidating the contract documents, may order extra work or make changes by altering, adding to or deducting from the work, the contract price being adjusted accordingly. All such work shall be executed under the conditions of the original contract except that any claim of extension of time caused thereby shall be adjusted at the time of ordering the change.

18.02 No extra work or change shall be performed unless in pursuance of a written order from the Owner/Engineer, with the agreed price prior to the commencement of the work, and no claim for an addition to the contract price shall be valid unless so ordered.

18.03 The value of any such work or change shall be determined, in one or more of the following ways:

- a) By estimate and acceptance on a lump sum.
- b) By unit prices named in the contract or subsequently agreed upon.
- c) By cost and percentage or by cost and a final fee.

19.00 SUBSTITUTIONS

19.01 The Contractor shall use materials as specified unless material list is of an open nature. Material other than specified will be permitted only after written application, including four (4) copies of specifications, is made by the Contractor and written approval received from the Engineer or Owner.

The material installed in the job site shall be new and of the quality specified.

The manufacturer's recommendation shall be followed for the installation of all equipment.

20.00 PRODUCT SUBMITTALS

20.01 Prior to ordering materials, the Contractor shall submit submittals as specified in the detailed specification sections. Three (3) copies of the submittals shall be forwarded to the Engineer for review and approval.

20.02 Submittals shall indicate specification Section for each product. Submittals not containing all the required information shall be returned to the contractor for re-submittal.

21.00 OWNER'S ACCEPTANCE

21.01 Within seven (7) days of the Contractor's notification that the installation is substantially complete, the Owner's authorized representative shall inspect the installation. The Owner, with the Contractor, shall take necessary steps to inspect the installation. Upon completion of the inspection, the Owner or the Owner's authorized representative may either accept the work

outright or prepare a "Punch List" that upon completion by the Contractor and acceptance by the Owner will signify final acceptance provided that all other applicable terms and provisions of the Contract have been completed to the Owner's satisfaction.

22.00 RESPONSIBILITY FOR MAINTENANCE

22.01 It will be the Contractor's responsibility to maintain the work as specified in the detailed specifications during the warranty period.

23.00 SERVICE BY THE CONTRACTOR

23.01 The Contractor shall maintain the work as specified during the warranty period.

24.00 WARRANTY

24.01 The guarantee shall be as specified in the respective sections of the specification.

24.02 The Contractor shall be responsible for the repair and/or replacement of all defective work and materials. All repair work shall be completed in a timely fashion.

24.04 Should the Contractor not respond promptly, the Owner may take any action he deems necessary to repair the defect and prevent further damage to his property, including the hiring of another contractor, or the repairing of such a defect with material supplied by the Contractor. In this event, the Contractor shall be liable for expenses incurred and property damages suffered by the Owner.

01.00 NOTICE TO CONTRACTOR

- 01.01 Intent of Contract: The intent of the Contract is to prescribe a complete work or improvement which the Contractor undertakes to do, in full compliance with the specifications, plans, special provisions, proposal and Contract. The Contractor shall perform all work in close conformity with the plans or as modified by written orders, including the furnishing of all materials, supplies, transportation, labor, and all other things necessary to the satisfactory prosecution and completion of the project.

The scope of the work shall include all labor, materials and equipment needed to provide and install, Locker Room Renovations and associated equipment and materials, complete and ready for use, as described in the plans and specifications for Locker Room Renovations at Glastonbury Police Department in Glastonbury, CT.

02.00 COMMUNICATIONS

- 02.01 All notices, demands, requests, instructions, approvals, proposals, and claims must be in writing.
- 02.02 Any notice to, or demand upon, the Contractor shall be sufficiently given if delivered at the office of the Contractor stated on the signature page of the Agreement (or at such other office as the Contractor may, from time to time, designate) in a sealed, postage-prepaid envelope or delivered with charges prepaid to any telegraph company for transmission, in each case addressed to such office.
- 02.03 All papers required to be delivered to the Town shall, unless otherwise specified in writing to the Contractor, be delivered to the Building Superintendent, 2143 Main Street, Glastonbury, CT 06033, and any notice to, or demand upon, the Town shall be delivered at the above address in a sealed, postage-prepaid envelope or delivered with charges prepaid to any telegraph company for transmission, in each case addressed to such office or to such other representatives of the Town, or to such other address as the Town may subsequently specify in writing to the Contractor for such purpose.
- 02.04 Any such notice shall be deemed to have been given as of the time of actual delivery or, in case of mailing, when the same should have been received in due course of post or, in the case of telegrams, at the time of actual receipt, as the case may be.

03.00 WORK BY OTHERS

- 03.01 Private utilities, contractors, developers or other parties may be expected to be working within the Contract area during this Contract. It shall be the responsibility of the contractor to coordinate his work with the work being done by others in order that the construction shall proceed in an efficient and logical manner. The Contractor shall have no claim or claims whatever against the Town, the Engineer, or other parties due to delays or other reasons caused by the work by others or his failure to coordinate such work.

04.00 CONTRACTOR'S WORK AND STORAGE AREA

- 04.01 The Contractor shall contact the Town to determine if any specific locations will be designated, or gain its approval prior to using any area for storage of equipment, materials and trailers during

the period of this Contract. The Contractor shall confine his work/storage area to the limits as designated or approved and shall be responsible for the security of the work/storage area. Upon completion of the Contract, the Contractor shall remove all equipment and materials, except as otherwise specified, and restore the site to its original condition as approved by the Engineer and at no cost to the Town.

05.00 DISPOSAL AREA

05.01 The Tryon Street Bulky Waste Facility will be available to the Contractor, at no charge, for disposal of materials that are accepted at that facility. No materials containing lead-based paint of any level shall be dumped at the Tryon Street facility. The Contractor is required to obtain a disposal area for all other unsuitable or surplus materials at no cost to the Town.

06.00 DUST CONTROL

06.01 During the progress of the work, the Contractor shall conduct his operations and maintain the area of his activities so as to minimize the creation and dispersion of dust. If the Engineer decides that it is necessary to use water or calcium chloride for more effective dust control, the Contractor shall furnish and spread the material, as directed, without additional compensation.

07.00 PROTECTION OF EXISTING UTILITIES

07.01 Before starting any excavation, the Contractor shall submit to the Engineer plans or details showing the proposed method the Contractor will use to support and protect all existing utilities during construction. The furnishing of such plans and details shall not serve to relieve the Contractor of any responsibility for the proper conduct of the work.

07.02 There will be no extra payment for submitting plans or details for supporting and protecting all existing utilities during construction.

08.00 TIME FOR COMPLETION/NOTICE TO PROCEED

08.01 Within ten (10) calendar days after the date of the Notice of Award, the Contractor must provide the appropriate insurance certificates to the Town Purchasing Agent and shall be issued a Notice to Proceed and a Purchase Order prior to initiating any work on the project.

08.02 Work shall commence within thirty (30) days of the date of the Notice to Proceed/Purchase Order.

08.03 After the work has begun, it will continue in an orderly fashion and shall be fully completed within 120 consecutive calendar days from the date of commencement. The Engineer reserves the right to extend the contract an additional thirty (30) days by mutual written agreement.

08.04 It is the intention of the Town to have all work required under this Contract completed no later than November 15, 2016. In no case, however, shall the work be completed any later than December 1, 2016.

08.05 Because the facilities remain open during the installation period, the Contractor shall make every reasonable effort to complete the installation as expeditiously as possible.

09.00 MEASUREMENT AND PAYMENT

- 09.01 All direct, indirect, or incidental costs of work and/or services required by these specifications shall be included in the Lump Sum price.
- 09.02 Monthly progress payments will be made, based on the approved Schedule of Values, for work that has progressed in accordance with the contract documents, subject to a deduction of five percent (5%) of the amount of the application for payment to be retained by the Owner until completion of the entire contract in an acceptable manner and two and one half percent (2.5%) until the applicable one year warranty period has expired and all required inspections have been completed and results have been submitted and approved by the Engineer.

10.00 COMPLIANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REQUIREMENTS

- 10.01 This award of bid is subject to the conformance of the Contractor to all Federal, State, and Local laws, statutes, regulations, ordinances or other requirements that are applicable to the type of work contained in these specifications.

INSURANCE

The Bidder shall, at its own expense and cost, obtain and keep in force during the entire duration of the Project or Work the following insurance coverage covering the Bidder and all of its agents, employees and sub-contractors and other providers of services and shall name the **Town of Glastonbury and its employees and agents as an Additional Insured** on a primary and non-contributory basis to the Bidders Commercial General Liability and Automobile Liability policies. **These requirements shall be clearly stated in the remarks section on the Bidders Certificate of Insurance.** Insurance shall be written with insurance carriers approved in the State of Connecticut and with a minimum Best's Rating of A-VIII. In addition, all carriers are subject to approval by the Town. Minimum Limits and requirements are stated below:

1) Worker's Compensation Insurance:

- Statutory Coverage
- Employer's Liability
- \$500,000 each accident/\$500,000 disease-policy limit/\$500,000 disease each employee
- A Waiver of Subrogation shall be provided in favor of the Town of Glastonbury and its employees and agents.

2) Commercial General Liability:

- Including Premises & Operations, Products and Completed Operations, Personal and Advertising Injury, Contractual Liability and Independent Contractors.
- Limits of Liability for Bodily Injury and Property Damage
Each Occurrence \$1,000,000
Aggregate \$2,000,000 (The Aggregate Limit shall apply separately to each job.)
- A Waiver of Subrogation shall be provided in favor of the Town of Glastonbury and its employees and agents.

3) Automobile Insurance:

- Including all owned, hired, borrowed and non-owned vehicles
- Limit of Liability for Bodily Injury and Property Damage: Per Accident \$1,000,000
- A Waiver of Subrogation shall be provided in favor of the Town of Glastonbury and its employees and agents.

The Bidder shall direct its Insurer to provide a Certificate of Insurance to the Town before any work is performed. The Contractor shall be responsible to notify the Town 60 days in advance with written notice of cancellation or non-renewal. The Certificate shall evidence all required coverage. The Bidder shall provide the Town copies of any such insurance policies upon request.

INDEMNIFICATION

To the fullest extent permitted by law, the Bidder shall indemnify and hold harmless the Town of Glastonbury and its consultants, agents, and employees from and against all claims, damages, losses and expenses, direct, indirect or consequential (including but not limited to fees and charges of engineers, attorneys and other professionals and court and arbitration costs) to the extent arising out of or resulting from the performance of the Bidder's work, provided that such claim, damage, loss or expense is caused in whole or in part by any negligent act or omission by the Bidder, or breach of its obligations herein or by any person or organization directly or indirectly employed or engaged by the Bidder to perform or furnish either of the services, or anyone for whose acts the Bidder may be liable.

**TOWN OF GLASTONBURY
Locker Room Renovations Police Department
LIST OF DRAWINGS**

BID #GL-2017-26

List of Drawings:

Architectural:

- A-110 Men's Locker Room Plans
- A-120 Women's Locker Room Plans

Mechanical:

- M110 Locker Room Plans
- M120 Women's Locker Room Plans
- M210 Mechanical Details and Specifications

Electrical:

- E110 Locker Room Electrical Plans
- E120 Women's Locker Room Plans
- E210 Electrical Note, Panel board & Symbol List



TOWN OF GLASTONBURY * 2155 MAIN STREET * GLASTONBURY * CT

BID / PROPOSAL NO: GL-2017-26 DATE DUE: 05-11-17

DATE ADVERTISED: 04-18-17 TIME DUE: 11:00 AM

NAME OF PROJECT: Locker Room Renovations Glastonbury Police Department

In compliance with this Invitation to Bid, the Bidder hereby proposes to provide goods and/or services as per this solicitation in strict accordance with the Bid Documents, within the time set forth therein, and at the prices submitted with their bid response.

It is the responsibility of the Bidder to clearly mark the outside of the bid envelope with the Company name and Address, Bid Number, Date and Time of Bid Opening, and it also THE RESPONSIBILITY OF THE BIDDER TO CHECK THE TOWN'S WEBSITE BEFORE SUBMITTING BID FOR ADDENDA POSTED PRIOR TO BID OPENING.

THE BIDDER ACKNOWLEDGES RECEIPT OF THE FOLLOWING ADDENDA AS REQUIRED:

Addendum #1 _____ (Initial/Date) **Addendum #2** _____ (Initial/Date) **Addendum #3** _____ (Initial/Date)

Other Items Required with Submission of Bid Proposal

The following bid checklist describes items required for inclusion with the above-referenced bid proposal package. It is provided for the convenience of the bidders and, therefore, should not be assumed to be a complete list.

_____ Bid Bond (10% of total bid amount).

_____ List of five (5) similar projects completed within last three (3) years.

_____ Acknowledgement of Addendums (as applicable).

_____ Acknowledgement of Code of Ethics on Bid Proposal page.

_____ Sealed bids, one original and one copy.

_____ Disclosure of past and pending mediation, arbitration and litigation cases that the Bidder or its principals have been involved in for the most recent five years (if applicable).

_____ Copy of Bidder's Contractor's License (State of Connecticut).

Name of Bidder: _____

LUMP SUM BID:

Furnish and install Locker Room Renovations at Glastonbury Police Department as specified in the Plans and Specifications for Bid GL-2017-26.

TOTAL OF LUMP SUM BID AMOUNT

\$ _____
(Numeric Bid Amount)

(Written Bid Amount)

CODE OF ETHICS:

I / We have reviewed a copy of the Town of Glastonbury's Code of Ethics and agree to submit a Consultant Acknowledgement Form if I / We are selected. Yes _____ No _____ *

*Bidder is advised that effective August 1, 2003, the Town of Glastonbury cannot consider any bid or proposal where the bidder has not agreed to the above statement.

Print Name, Title of Individual

Doing Business as (Trade Name)

Signature of Individual

Street Address

Date

City, State, Zip Code

E:mail Address

Telephone Number / Fax Number

Project: Glastonbury Police Department Locker Replacement

**Minimum Rates and Classifications
for Building Construction**

ID# : B 23440

**Connecticut Department of Labor
Wage and Workplace Standards Division**

By virtue of the authority vested in the Labor Commissioner under provisions of Section 31-53 of the General Statutes of Connecticut, as amended, the following are declared to be the prevailing rates and welfare payments and will apply only where the contract is advertised for bid within 20 days of the date on which the rates are established. Any contractor or subcontractor not obligated by agreement to pay to the welfare and pension fund shall pay this amount to each employee as part of his/her hourly wages.

Project Number: GL-2017-26

Project Town: Glastonbury

State#:

FAP#:

Project: Glastonbury Police Department Locker Replacement

CLASSIFICATION	Hourly Rate	Benefits
1a) Asbestos Worker/Insulator (Includes application of insulating materials, protective coverings, coatings, & finishes to all types of mechanical systems; application of firestopping material for wall openings & penetrations in walls, floors, ceilings	38.25	27.96
<hr/>		
1b) Asbestos/Toxic Waste Removal Laborers: Asbestos removal and encapsulation (except its removal from mechanical systems which are not to be scrapped), toxic waste removers, blasters.**See Laborers Group 7**		
<hr/>		
1c) Asbestos Worker/Heat and Frost Insulator	37.15	27.56

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

2) Boilermaker	38.34	26.01
----------------	-------	-------

3a) Bricklayer, Cement Mason, Concrete Finisher (including caulking), Stone Masons	33.48	30.61 + a
---	-------	-----------

3b) Tile Setter	34.90	24.69
-----------------	-------	-------

3c) Terrazzo Mechanics and Marble Setters	31.69	22.35
---	-------	-------

3d) Tile, Marble & Terrazzo Finishers	26.70	21.02
---------------------------------------	-------	-------

3e) Plasterer	33.48	30.61
---------------	-------	-------

As of: **Tuesday, April 11, 2017**

Project: Glastonbury Police Department Locker Replacement

-----LABORERS-----

4) Group 1: Laborers (common or general), acetylene burners, carpenter tenders, concrete specialists, wrecking laborers, fire watchers.	28.55	18.90
---	-------	-------

4a) Group 2: Mortar mixers, plaster tender, power buggy operators, powdermen, fireproofers/mixer/nozzleman (Person running mixer and spraying fireproof only).	28.80	18.90
--	-------	-------

4b) Group 3: Jackhammer operators/pavement breaker, mason tender (brick), mason tender (cement/concrete), forklift operators and forklift operators (masonry).	29.05	18.90
--	-------	-------

4c) **Group 4: Pipelayers (Installation of water, storm drainage or sewage lines outside of the building line with P6, P7 license) (the pipelayer rate shall apply only to one or two employees of the total crew who primary task is to actually perform the mating of pipe sections) P6 and P7 rate is \$26.80.	28.80	18.90
---	-------	-------

4d) Group 5: Air track operator, sand blaster and hydraulic drills.	29.30	18.90
---	-------	-------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

4e) Group 6: Blasters, nuclear and toxic waste removal.	31.55	18.90
---	-------	-------

4f) Group 7: Asbestos/lead removal and encapsulation (except it's removal from mechanical systems which are not to be scrapped).	29.55	18.90
--	-------	-------

4g) Group 8: Bottom men on open air caisson, cylindrical work and boring crew.	28.38	18.90
--	-------	-------

4h) Group 9: Top men on open air caisson, cylindrical work and boring crew.	27.86	18.90
---	-------	-------

4i) Group 10: Traffic Control Signalman	16.00	18.90
---	-------	-------

5) Carpenter, Acoustical Ceiling Installation, Soft Floor/Carpet Laying, Metal Stud Installation, Form Work and Scaffold Building, Drywall Hanging, Modular-Furniture Systems Installers, Lathers, Piledrivers, Resilient Floor Layers.	32.00	24.42
---	-------	-------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

5a) Millwrights 32.47 24.84

6) Electrical Worker (including low voltage wiring) (Trade License required: E1,2 L-5,6 C-5,6 T-1,2 L-1,2 V-1,2,7,8,9) 38.65 24.42+3% of gross wage

7a) Elevator Mechanic (Trade License required: R-1,2,5,6) 50.14 31.585+a+b

-----LINE CONSTRUCTION-----

Groundman 25.93 6.5% + 8.53

Linemen/Cable Splicer 47.14 6.5% + 20.98

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

8) Glazier (Trade License required: FG-1,2)	35.58	20.15 + a
---	-------	-----------

9) Ironworker, Ornamental, Reinforcing, Structural, and Precast Concrete Erection	35.22	31.99 + a
---	-------	-----------

----OPERATORS----

Group 1: Crane handling or erecting structural steel or stone, hoisting engineer 2 drums or over, front end loader (7 cubic yards or over), work boat 26 ft. and over and Tunnel Boring Machines. (Trade License Required)	38.55	23.55 + a
--	-------	-----------

Group 2: Cranes (100 ton rate capacity and over); Excavator over 2 cubic yards; Piledriver (\$3.00 premium when operator controls hammer); Bauer Drill/Caisson. (Trade License Required)	38.23	23.55 + a
--	-------	-----------

Group 3: Excavator; Backhoe/Excavator under 2 cubic yards; Cranes (under 100 ton rated capacity), Grader/Blade; Master Mechanic; Hoisting Engineer (all types of equipment where a drum and cable are used to hoist or drag material regardless of motive power of operation), Rubber Tire Excavator (Drott-1085 or similar); Grader Operator; Bulldozer Fine Grade. (slopes, shaping, laser or GPS, etc.). (Trade License Required)	37.49	23.55 + a
--	-------	-----------

Project: Glastonbury Police Department Locker Replacement

Group 4: Trenching Machines; Lighter Derrick; Concrete Finishing Machine; CMI Machine or Similar; Koehring Loader (Skooper).	37.10	23.55 + a
--	-------	-----------

Group 5: Specialty Railroad Equipment; Asphalt Paver; Asphalt Reclaiming Machine; Line Grinder; Concrete Pumps; Drills with Self Contained Power Units; Boring Machine; Post Hole Digger; Auger; Pounder; Well Digger; Milling Machine (over 24" Mandrell)	36.51	23.55 + a
--	-------	-----------

Group 5 continued: Side Boom; Combination Hoe and Loader; Directional Driller; Pile Testing Machine.	36.51	23.55 + a
--	-------	-----------

Group 6: Front End Loader (3 up to 7 cubic yards); Bulldozer (rough grade dozer).	36.20	23.55 + a
---	-------	-----------

Group 7: Asphalt roller, concrete saws and cutters (ride on types), vermeer concrete cutter, Stump Grinder; Scraper; Snooper; Skidder; Milling Machine (24" and under Mandrell).	35.86	23.55 + a
--	-------	-----------

Group 8: Mechanic, grease truck operator, hydroblaster; barrier mover; power stone spreader; welding; work boat under 26 ft.; transfer machine.	35.46	23.55 + a
---	-------	-----------

Project: Glastonbury Police Department Locker Replacement

Group 9: Front end loader (under 3 cubic yards), skid steer loader regardless of attachments, (Bobcat or Similar): forklift, power chipper; landscape equipment (including Hydroseeder).	35.03	23.55 + a
--	-------	-----------

Group 10: Vibratory hammer; ice machine; diesel and air, hammer, etc.	32.99	23.55 + a
---	-------	-----------

Group 11: Conveyor, earth roller, power pavement breaker (whiphammer), robot demolition equipment.	32.99	23.55 + a
--	-------	-----------

Group 12: Wellpoint operator.	32.93	23.55 + a
-------------------------------	-------	-----------

Group 13: Compressor battery operator.	32.35	23.55 + a
--	-------	-----------

Group 14: Elevator operator; tow motor operator (solid tire no rough terrain).	31.21	23.55 + a
--	-------	-----------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

Group 15: Generator Operator; Compressor Operator; Pump Operator; Welding Machine Operator; Heater Operator.	30.80	23.55 + a
--	-------	-----------

Group 16: Maintenance Engineer/Oiler.	30.15	23.55 + a
---------------------------------------	-------	-----------

Group 17: Portable asphalt plant operator; portable crusher plant operator; portable concrete plant operator.	34.46	23.55 + a
---	-------	-----------

Group 18: Power safety boat; vacuum truck; zim mixer; sweeper; (Minimum for any job requiring a CDL license).	32.04	23.55 + a
---	-------	-----------

-----PAINTERS (Including Drywall Finishing)-----

10a) Brush and Roller	32.02	20.15
-----------------------	-------	-------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

10b) Taping Only/Drywall Finishing	32.77	20.15
------------------------------------	-------	-------

10c) Paperhanger and Red Label	32.52	20.15
--------------------------------	-------	-------

10e) Blast and Spray	35.02	20.15
----------------------	-------	-------

11) Plumber (excluding HVAC pipe installation) (Trade License required: P-1,2,6,7,8,9 J-1,2,3,4 SP-1,2)	40.62	29.71
--	-------	-------

12) Well Digger, Pile Testing Machine	33.01	19.40 + a
---------------------------------------	-------	-----------

13) Roofer (composition)	34.92	19.28
--------------------------	-------	-------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

14) Roofer (slate & tile)	35.42	19.28
---------------------------	-------	-------

15) Sheetmetal Worker (Trade License required for HVAC and Ductwork: SM-1,SM-2,SM-3,SM-4,SM-5,SM-6)	36.00	34.51
--	-------	-------

16) Pipefitter (Including HVAC work) (Trade License required: S-1,2,3,4,5,6,7,8 B-1,2,3,4 D-1,2,3,4, G-1, G-2, G-8 & G-9)	40.62	29.71
---	-------	-------

-----TRUCK DRIVERS-----

17a) 2 Axle	28.83	21.39 + a
-------------	-------	-----------

17b) 3 Axle, 2 Axle Ready Mix	28.93	21.39 + a
-------------------------------	-------	-----------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

17c) 3 Axle Ready Mix	28.98	21.39 + a
-----------------------	-------	-----------

17d) 4 Axle, Heavy Duty Trailer up to 40 tons	29.03	21.39 + a
---	-------	-----------

17e) 4 Axle Ready Mix	29.08	21.39 + a
-----------------------	-------	-----------

17f) Heavy Duty Trailer (40 Tons and Over)	29.28	21.39 + a
--	-------	-----------

17g) Specialized Earth Moving Equipment (Other Than Conventional Type on-the-Road Trucks and Semi-Trailers, Including Euclids)	29.08	21.39 + a
--	-------	-----------

18) Sprinkler Fitter (Trade License required: F-1,2,3,4)	42.62	20.77 + a
--	-------	-----------

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

19) Theatrical Stage Journeyman	25.76	7.34
---------------------------------	-------	------

Project: Glastonbury Police Department Locker Replacement

Welders: Rate for craft to which welding is incidental.

**Note: Hazardous waste removal work receives additional \$1.25 per hour for truck drivers.*

***Note: Hazardous waste premium \$3.00 per hour over classified rate*

ALL Cranes: When crane operator is operating equipment that requires a fully licensed crane operator to operate he receives an extra \$3.00 premium in addition to the hourly wage rate and benefit contributions:

1) Crane handling or erecting structural steel or stone; hoisting engineer (2 drums or over)

2) Cranes (100 ton rate capacity and over) Bauer Drill/Caisson

3) Cranes (under 100 ton rated capacity)

Crane with 150 ft. boom (including jib) - \$1.50 extra

Crane with 200 ft. boom (including jib) - \$2.50 extra

Crane with 250 ft. boom (including jib) - \$5.00 extra

Crane with 300 ft. boom (including jib) - \$7.00 extra

Crane with 400 ft. boom (including jib) - \$10.00 extra

All classifications that indicate a percentage of the fringe benefits must be calculated at the percentage rate times the "base hourly rate".

Apprentices duly registered under the Commissioner of Labor's regulations on "Work Training Standards for Apprenticeship and Training Programs" Section 31-51-d-1 to 12, are allowed to be paid the appropriate percentage of the prevailing journeymen hourly base and the full fringe benefit rate, providing the work site ratio shall not be less than one full-time journeyman instructing and supervising the work of each apprentice in a specific trade.

The Prevailing wage rates applicable to this project are subject to annual adjustments each July 1st for the duration of the project.

Each contractor shall pay the annual adjusted prevailing wage rate that is in effect each July 1st, as posted by the Department of Labor.

It is the contractor's responsibility to obtain the annual adjusted prevailing wage rate increases directly from the Department of Labor's website.

The annual adjustments will be posted on the Department of Labor's Web page: www.ct.gov/dol. For those without internet access, please contact the division listed below.

The Department of Labor will continue to issue the initial prevailing wage rate schedule to the Contracting Agency for the project.

All subsequent annual adjustments will be posted on our Web Site for contractor access.

Contracting Agencies are under no obligation pursuant to State labor law to pay any increase due to the annual adjustment provision.

As of: Tuesday, April 11, 2017

Project: Glastonbury Police Department Locker Replacement

Effective October 1, 2005 - Public Act 05-50: any person performing the work of any mechanic, laborer, or worker shall be paid prevailing wage

All Person who perform work ON SITE must be paid prevailing wage for the appropriate mechanic, laborer, or worker classification.

All certified payrolls must list the hours worked and wages paid to All Persons who perform work ON SITE regardless of their ownership i.e.: (Owners, Corporate Officers, LLC Members, Independent Contractors, et. al)

Reporting and payment of wages is required regardless of any contractual relationship alleged to exist between the contractor and such person.

~~Unlisted classifications needed for work not included within the scope of the classifications listed may be added after award only as provided in the labor standards contract clause (29 CFR 5.5 (a) (1) (ii)).

Please direct any questions which you may have pertaining to classification of work and payment of prevailing wages to the Wage and Workplace Standards Division, telephone (860)263-6790.

As of: Tuesday, April 11, 2017

PROJECT MANUAL

LOCKER ROOM RENOVATIONS GLASTONBURY POLICE DEPARTMENT GLASTONBURY, CONNECTICUT

**GLASTONBURY TRACKING NUMBER: GL-2017-26
JCJ PROJECT # MP16046.00**

March 15, 2017

JCJARCHITECTURE

©2017 JCJ Architecture

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

TABLE OF CONTENTS

Section	012100	Allowances
	024119	Selective Demolition
	035416	Hydraulic Cement Underlayment
	042200	Concrete Unit Masonry
	055000	Metal Fabrications
	078413	Penetration Firestopping
	081113	Hollow Metal Doors and Frames
	081416	Flush Wood Doors
	087100	Door Hardware
	095113	Acoustical Panel Ceilings
	096513	Resilient Base and Accessories
	096519	Resilient Tile Flooring
	099100	Painting
	105113	Welded Metal Lockers (personal storage lockers with built-in bench drawer)

END OF TABLE OF CONTENTS

SECTION 012100

ALLOWANCES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including terms and conditions, and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. Section includes administrative and procedural requirements governing allowances.
 - 1. Certain items are specified in the Contract Documents by allowances. Allowances have been established in lieu of additional requirements and to defer selection of actual materials and equipment to a later date when direction will be provided to Contractor. If necessary, additional requirements will be issued by Change Order.
- B. Types of allowances include the following:
 - 1. Lump-sum allowances.

1.3 SELECTION AND PURCHASE:

- A. At the earliest practical date after award of the Contract, advise Architect of the date when final selection and purchase of each product or system described by an allowance must be completed to avoid delaying the Work.
- B. At Architect's request, obtain proposals for each allowance for use in making final selections. Include recommendations that are relevant to performing the Work.
- C. Purchase products and systems selected by Architect from the designated supplier.

1.4 ACTION SUBMITTALS:

- A. Submit proposals for purchase of products or systems included in allowances, in the form specified for Change Orders.

1.5 INFORMATIONAL SUBMITTALS:

- A. Submit invoices or delivery slips to show actual quantities of materials delivered to the site for use in fulfillment of each allowance.
- B. Submit time sheets and other documentation to show labor time and cost for installation of allowance items that include installation as part of the allowance.
- C. Coordinate and process submittals for allowance items in same manner as for other portions of the Work.

1.6 COORDINATION:

- A. Coordinate allowance items with other portions of the Work. Furnish templates as required to coordinate installation.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

1.7 LUMP-SUM ALLOWANCES:

- A. Allowance shall include cost to Contractor of specific products and materials ordered by Owner or selected by Architect under allowance and shall include taxes, freight, and delivery to Project site.
- B. Unless otherwise indicated, Contractor's costs for receiving and handling at Project site, labor, installation, overhead and profit, and similar costs related to products and materials selected by Architect under allowance shall be included as part of the Contract Sum and not part of the allowance.
- C. Unused Materials: Return unused materials purchased under an allowance to manufacturer or supplier for credit to Owner, after installation has been completed and accepted.
 - 1. If requested by Architect, retain and prepare unused material for storage by Owner. Deliver unused material to Owner's storage space as directed.

1.8 ADJUSTMENT OF ALLOWANCES:

- A. Allowance Adjustment: To adjust allowance amounts, prepare a Change Order proposal based on the difference between purchase amount and the allowance, multiplied by final measurement of work-in-place where applicable. If applicable, include reasonable allowances for cutting losses, tolerances, mixing wastes, normal product imperfections, and similar margins.
 - 1. Include installation costs in purchase amount only where indicated as part of the allowance.
 - 2. If requested, prepare explanation and documentation to substantiate distribution of overhead costs and other margins claimed.
 - 3. Submit substantiation of a change in scope of work, if any, claimed in Change Orders related to unit-cost allowances.
 - 4. Owner reserves the right to establish the quantity of work-in-place by independent quantity survey, measure, or count.
- B. Submit claims for increased costs because of a change in scope or nature of the allowance described in the Contract Documents, whether for the purchase order amount or Contractor's handling, labor, installation, overhead, and profit.
 - 1. Do not include Contractor's or subcontractor's indirect expense in the Change Order cost amount unless it is clearly shown that the nature or extent of work has changed from what could have been foreseen from information in the Contract Documents.
 - 2. No change to Contractor's indirect expense is permitted for selection of higher- or lower-priced materials or systems of the same scope and nature as originally indicated.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

PART 2 - PRODUCTS (NOT APPLICABLE)

PART 3 - EXECUTION

3.1 INSPECTION:

- A. Promptly upon delivery, inspect products covered by an allowance for damage or defects.

3.2 PREPARATION:

- A. Coordinate installation of each allowance product to ensure that allowance item is completely integrated and interfaced with related materials and installations.

3.3 SCHEDULE OF ALLOWANCES:

- A. **Allowance No. 1:** Installation of firestopping allowance of \$5,000.

END OF SECTION 012100

SECTION 024119

SELECTIVE DEMOLITION

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. Section Includes:
 - 1. Demolition and removal of selected portions of building or structure.
 - 2. Demolition and removal of selected site elements.
 - 3. Salvage of existing items to be reused or recycled.
- B. Related Requirements:
 - 1. Division 01 Section "Temporary Facilities and Controls."
 - 2. Division 01 Section "Cutting and Patching" for cutting and patching procedures.

1.3 DEFINITIONS:

- A. Remove: Detach items from existing construction and legally dispose of them off-site unless indicated to be removed and salvaged or removed and reinstalled.
- B. Remove and Salvage: Carefully detach from existing construction, in a manner to prevent damage, and deliver to Owner ready for reuse.
- C. Remove and Reinstall: Detach items from existing construction, prepare for reuse, and reinstall where indicated.
- D. Existing to Remain: Existing items of construction that are not to be permanently removed and that are not otherwise indicated to be removed, removed and salvaged, or removed and reinstalled.
- E. "MEP" or "Mechanical Electrical Plumbing" is used broadly in this section to refer to Fire Protection, Plumbing, HVAC, Electrical, Fire Alarm, Communications, Low Voltage, and Electronic Safety and Security disciplines.

1.4 MATERIALS OWNERSHIP:

- A. Owner to have right of first refusal for all demolition waste, otherwise, demolition waste becomes property of Contractor.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- B. Historic items, relics, antiques, and similar objects including, but not limited to, cornerstones and their contents, commemorative plaques and tablets, and other items of interest or value to Owner that may be uncovered during demolition remain the property of Owner.
 - 1. Carefully salvage in a manner to prevent damage and promptly return to Owner.

1.5 PREDEMOLITION MEETINGS:

- A. Predemolition Conference: Conduct conference at Project site.
 - 1. Inspect and discuss condition of construction to be selectively demolished.
 - 2. Review structural load limitations of existing structure.
 - 3. Review and finalize selective demolition schedule and verify availability of materials, demolition personnel, equipment, and facilities needed to make progress and avoid delays.
 - 4. Review requirements of work performed by other trades that rely on substrates exposed by selective demolition operations.
 - 5. Review areas where existing construction is to remain and requires protection.

1.6 INFORMATIONAL SUBMITTALS:

- A. Qualification Data: For refrigerant recovery technician.
- B. Proposed Protection Measures: Submit report, including drawings, that indicates the measures proposed for protecting individuals and property, for environmental protection, for dust control and, for noise control. Indicate proposed locations and construction of barriers.
- C. Schedule of Selective Demolition Activities: Indicate the following:
 - 1. Detailed sequence of selective demolition and removal work, with starting and ending dates for each activity. Ensure Owner's on-site operations are uninterrupted.
 - 2. Interruption of utility services. Indicate how long utility services will be interrupted.
 - 3. Coordination for shutoff, capping, and continuation of utility services.
 - 4. Use of elevator and stairs.
 - 5. Coordination of Owner's continuing occupancy of portions of existing building and of Owner's partial occupancy of completed Work.
- D. Inventory: Submit a list of items to be removed and salvaged and deliver to Owner prior to start of demolition.
- E. Predemolition Photographs or Video: Submit before Work begins.
- F. Statement of Refrigerant Recovery: Signed by refrigerant recovery technician responsible for recovering refrigerant, stating that all refrigerant that was present was recovered and that recovery was performed according to EPA regulations. Include name and address of technician and date refrigerant was recovered.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- G. Warranties: Documentation indicated that existing warranties are still in effect after completion of selective demolition.

1.7 CLOSEOUT SUBMITTALS:

- A. Inventory: Submit a list of items that have been removed and salvaged.

1.8 QUALITY ASSURANCE:

- A. Refrigerant Recovery Technician Qualifications: Certified by an EPA-approved certification program.
- B. Comply with governing EPA regulatory requirements and notification requirements before beginning demolitions.
- C. Comply with hauling and disposal regulations of Authorities having jurisdiction.

1.9 FIELD CONDITIONS:

- A. Conditions existing at time of inspection for bidding purpose will be maintained by Owner as far as practical.
- B. Notify Architect of discrepancies between existing conditions and Drawings before proceeding with selective demolition.
- C. Hazardous Materials: It is not expected that hazardous materials will be encountered in the Work.
 - 1. Hazardous materials will be removed by Owner before start of the Work.
 - 2. If suspected hazardous materials are encountered, do not disturb; immediately notify Architect and Owner. Hazardous materials will be removed by Owner under a separate contract.
- D. Storage or sale of removed items or materials on-site is not permitted.
- E. Utility Service: Maintain existing utilities indicated to remain in service and protect them against damage during selective demolition operations.
 - 1. Maintain fire-protection facilities in service during selective demolition operations.

1.10 WARRANTY:

- A. Existing Warranties: Remove, replace, patch, and repair materials and surfaces cut or damaged during selective demolition, by methods and with materials so as not to void existing warranties. Notify warrantor before proceeding.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- B. Notify warrantor on completion of selective demolition, and obtain documentation verifying that existing system has been inspected and warranty remains in effect. Submit documentation at Project closeout.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS:

- A. Regulatory Requirements: Comply with governing EPA notification regulations before beginning selective demolition. Comply with hauling and disposal regulations of authorities having jurisdiction.
- B. Standards: Comply with ANSI/ASSE A10.6 and NFPA 241.

PART 3 - EXECUTION

3.1 EXAMINATION:

- A. Verify that utilities have been disconnected and capped before starting selective demolition operations.
- B. Review record documents of existing construction provided by Owner. Owner does not guarantee that existing conditions are same as those indicated in record documents.
- C. Survey existing conditions and correlate with requirements indicated to determine extent of selective demolition required.
- D. When unanticipated mechanical, electrical, or structural elements that conflict with intended function or design are encountered, investigate and measure the nature and extent of conflict. Promptly submit a written report to Architect.
- E. Perform an engineering survey of condition of building to determine whether removing any element might result in structural deficiency or unplanned collapse of any portion of structure or adjacent structures during selective building demolition operations.
 - 1. Perform surveys as the Work progresses to detect hazards resulting from selective demolition activities.
- F. Verify that hazardous materials have been remediated before proceeding with building demolition operations.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- G. Survey of Existing Conditions: Record existing conditions by use of measured drawings.
1. Before selective demolition or removal of existing building elements that will be reproduced or duplicated in final Work, make permanent record of measurements, materials, and construction details required to make exact reproduction.

3.2 UTILITY SERVICES AND MECHANICAL/ELECTRICAL SYSTEMS:

- A. Existing Services/Systems to Remain: Maintain services/systems indicated to remain and protect them against damage.
1. Comply with requirements for existing services/systems interruptions specified in Division 01 Section "Summary."
- B. Existing Services/Systems to Be Removed, Relocated, or Abandoned: Locate, identify, disconnect, and seal or cap off indicated utility services and mechanical/electrical systems serving areas to be selectively demolished.
1. General Contractor shall arrange to shut off indicated services/systems when requested by Contractor.
 2. Arrange to shut off indicated utilities with utility companies.
 3. If services/systems are required to be removed, relocated, or abandoned, provide temporary services/systems that bypass area of selective demolition and that maintain continuity of services/systems to other parts of building.
 4. Disconnect, demolish, and remove fire-suppression systems, plumbing, and HVAC systems, equipment, and components indicated to be removed.
 - a. Piping to Be Removed: Remove portion of piping indicated to be removed and cap or plug remaining piping with same or compatible piping material.
 - b. Piping to Be Abandoned in Place: Drain piping and cap or plug piping with same or compatible piping material.
 - c. Equipment to Be Removed: Disconnect and cap services and remove equipment.
 - d. Equipment to Be Removed and Reinstalled: Disconnect and cap services and remove, clean, and store equipment; when appropriate, reinstall, reconnect, and make equipment operational.
 - e. Equipment to Be Removed and Salvaged: Disconnect and cap services and remove equipment and deliver to Owner.
 - f. Ducts to Be Removed: Remove portion of ducts indicated to be removed and plug remaining ducts with same or compatible ductwork material.
 - g. Ducts to Be Abandoned in Place: Cap or plug ducts with same or compatible ductwork material.
- C. Refrigerant: Remove refrigerant from mechanical equipment to be selectively demolished according to 40 CFR 82 and regulations of authorities having jurisdiction.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

3.3 PREPARATION:

- A. Site Access and Temporary Controls: Conduct selective demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
 - 1. Comply with requirements for access and protection specified in Division 01 Section "Temporary Facilities and Controls."

- B. Temporary Facilities: Provide temporary barricades and other protection required to prevent injury to people and damage to adjacent buildings and facilities to remain.
 - 1. Provide protection to ensure safe passage of people around selective demolition area and to and from occupied portions of building.
 - 2. Provide temporary weather protection, during interval between selective demolition of existing construction on exterior surfaces and new construction, to prevent water leakage and damage to structure and interior areas.
 - 3. Protect walls, ceilings, floors, and other existing finish work that are to remain or that are exposed during selective demolition operations.
 - 4. Cover and protect furniture, furnishings, and equipment that have not been removed.
 - 5. Comply with requirements for temporary enclosures, dust control, heating, and cooling specified in Division 01 Section "Temporary Facilities and Controls."

- C. Temporary Shoring: Provide and maintain shoring, bracing, and structural supports as required to preserve stability and prevent movement, settlement, or collapse of construction and finishes to remain, and to prevent unexpected or uncontrolled movement or collapse of construction being demolished.
 - 1. Strengthen or add new supports when required during progress of selective demolition.

3.4 SELECTIVE DEMOLITION, GENERAL:

- A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations and as follows:
 - 1. Proceed with selective demolition systematically, from higher to lower level. Complete selective demolition operations above each floor or tier before disturbing supporting members on the next lower level.
 - 2. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction. Use hand tools or small power tools designed for sawing or grinding, not hammering and chopping, to minimize disturbance of adjacent surfaces. Temporarily cover openings to remain.
 - 3. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

4. Do not use cutting torches until work area is cleared of flammable materials. At concealed spaces, such as duct and pipe interiors, verify condition and contents of hidden space before starting flame-cutting operations. Maintain fire watch and portable fire-suppression devices during flame-cutting operations.
5. Maintain adequate ventilation when using cutting torches.
6. Remove decayed, vermin-infested, or otherwise dangerous or unsuitable materials and promptly dispose of off-site.
7. Remove structural framing members and lower to ground by method suitable to avoid free fall and to prevent ground impact or dust generation.
8. Locate selective demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
9. Dispose of demolished items and materials promptly. Comply with requirements in Division 01 Section "Construction Waste Management and Disposal."

B. Removed and Salvaged Items:

1. Clean salvaged items.
2. Pack or crate items after cleaning. Identify contents of containers.
3. Store items in a secure area until delivery to Owner.
4. Transport items to Owner's storage area on-site.
5. Protect items from damage during transport and storage.

C. Removed and Reinstalled Items:

1. Clean and repair items to functional condition adequate for intended reuse.
2. Pack or crate items after cleaning and repairing. Identify contents of containers.
3. Protect items from damage during transport and storage.
4. Reinstall items in locations indicated. Comply with installation requirements for new materials and equipment. Provide connections, supports, and miscellaneous materials necessary to make item functional for use indicated.

- D. Existing Items to Remain:** Protect construction indicated to remain against damage and soiling during selective demolition. When permitted by Architect, items may be removed to a suitable, protected storage location during selective demolition and cleaned and reinstalled in their original locations after selective demolition operations are complete.

3.5 SELECTIVE DEMOLITION PROCEDURES FOR SPECIFIC MATERIALS:

- A. Concrete: Demolish in small sections. Using power-driven saw, cut concrete to a depth of at least 3/4 inch (19 mm) at junctures with construction to remain. Dislodge concrete from reinforcement at perimeter of areas being demolished, cut reinforcement, and then remove remainder of concrete. Neatly trim openings to dimensions indicated.
- B. Concrete: Demolish in sections. Cut concrete full depth at junctures with construction to remain and at regular intervals using power-driven saw, then remove concrete between saw cuts.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Masonry: Demolish in small sections. Cut masonry at junctures with construction to remain, using power-driven saw, then remove masonry between saw cuts.
- D. Concrete Slabs-on-Grade: Saw-cut perimeter of area to be demolished, then break up and remove.
- E. Resilient Floor Coverings: Remove floor coverings and adhesive according to recommendations in RFCI's "Recommended Work Practices for the Removal of Resilient Floor Coverings." Do not use methods requiring solvent-based adhesive strippers.
- F. Roofing: Remove no more existing roofing than what can be covered in one day by new roofing and so that building interior remains watertight and weathertight.
 - 1. Remove existing roof membrane, flashings, copings, and roof accessories.
 - 2. Remove existing roofing system down to substrate.

3.6 DEMOLITION AND DEMOLITION DISPOSAL :

- A. General: Except for items or materials indicated to be recycled, reused, salvaged, reinstalled, or otherwise indicated to remain Owner's property, remove demolished materials from Project site and legally dispose of them in an EPA-approved landfill.
 - 1. Do not allow demolished materials to accumulate on-site.
 - 2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
 - 3. Remove debris from elevated portions of building by chute, hoist, or other device that will convey debris to grade level in a controlled descent.
 - 4. Comply with requirements specified in Division 01 Section "Construction Waste Management and Disposal."
- B. Burning: Do not burn demolished materials.
- C. Disposal: Transport demolished materials off Owner's property and legally dispose of them.
- D. All MEP contractors are responsible for disconnecting, cutting, capping and lowering to the floor or to grade all items to be demolished related to their respective trades and as shown on their respective demolition drawings. The scope of this demolition shall be inclusive of the disconnecting and lowering to the floor/grade all hangers, attachments, clips and similar such items associated with the items to be demolished. Cutting is defined as complete removal of materials or cutting materials to be flush with existing surface. All wall mounted materials shall be handled in the same manner.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- E. In the event of items to be demolished that have salvageable scrap or re-sale value, the contractor responsible for disconnecting and cutting free the item may, at its discretion, retain ownership rights of the item and become responsible for its removal and disposal off-site. All other demolished items not so retained by the removing contractor are to be dropped to the floor or grade and removed / disposed of by the General Contractor.
- F. Roofing Trade Contractor shall be fully responsible for the roof demolition shown on the Roof Demolition Architectural drawings, including legal off-site disposal of all demolished items.
- G. Masonry that is indicated to be removed and salvaged for re-use will be the full responsibility of the Masonry Trade Contractor, including cutting, removal, scraping, cleaning, storing, protecting and reinstalling the masonry units.
 - 1. In the event that the existing material cannot be salvaged (for any reason) it is the mason's responsibility to provide new material to match the existing. During the onsite review period the mason shall understand the scope of work for the glazed structural facing tile as this is known to be a long lead item.
 - 2. The Masonry Trade Contractor is responsible for off-site disposal of all masonry construction waste.
- H. All other demolition indicated on the Architectural Demolition drawings shall be by the General Contractor including removal and legal off-site disposal. This does not include any necessary roofing demolition, which shall be completed by the Roofing Trade Subcontractor.

3.7 CLEANING:

- A. Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Return adjacent areas to condition existing before selective demolition operations began.

3.8 SELECTIVE DEMOLITION SCHEDULE:

- A. Existing Construction to Be Removed: Reference Demolition Drawings.

END OF SECTION 024119

SECTION 035416

HYDRAULIC CEMENT UNDERLAYMENT

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes hydraulic-cement-based underlayment for use below interior floor coverings.
- B. Related Sections include the following:
 - 1. Division 09 Sections for patching and leveling compounds applied with floor coverings.

1.3 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Shop Drawings: Plans indicating substrates, locations, and average depths of underlayment based on survey of substrate conditions.
- C. Manufacturer Certificates: Signed by manufacturers of both underlayment and floor covering system certifying that products are compatible.
- D. Qualification Data: For Installer.
- E. Minutes of preinstallation conference.

1.4 QUALITY ASSURANCE

- A. Installer Qualifications: Installer who is approved by manufacturer for application of underlayment products required for this Project.
- B. Product Compatibility: Manufacturers of both underlayment and floor covering system certify in writing that products are compatible.
- C. Mockups: Apply hydraulic-cement-based underlayment mockups to demonstrate surface finish, bonding, texture, tolerances, and standard of workmanship.
 - 1. Apply mockups approximately 100 sq. ft. (9 sq. m) in area in location indicated or, if not indicated, as directed by Architect.
 - 2. Approved mockups may become part of the completed Work if undisturbed at time of Substantial Completion.
- D. Preinstallation Conference: Conduct conference at Project site to comply with requirements in Division 01 Section "Project Management and Coordination."

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store materials to comply with manufacturer's written instructions to prevent deterioration from moisture or other detrimental effects.

1.6 PROJECT CONDITIONS

- A. Environmental Limitations: Comply with manufacturer's written instructions for substrate temperature, ambient temperature and humidity, ventilation, and other conditions affecting underlayment performance.
 - 1. Place hydraulic-cement-based underlayments only when ambient temperature and temperature of substrates are between 50 and 80 deg F (10 and 27 deg C).

1.7 COORDINATION

- A. Coordinate application of underlayment with requirements of floor covering products, including adhesives, specified in Division 09 Sections, to ensure compatibility of products.

PART 2 - PRODUCTS

2.1 HYDRAULIC-CEMENT-BASED UNDERLAYMENTS

- A. Underlayment: Hydraulic-cement-based, polymer-modified, self-leveling product that can be applied in minimum uniform thicknesses of 1/8 inch (3 mm) and that can be feathered at edges to match adjacent floor elevations.
 - 1. Available Products: Subject to compliance with requirements, products that may be incorporated into the Work include, but are not limited to, the following:
 - a. Ardex; K-15 Self-Leveling Underlayment Concrete
 - b. Bonsal, W. R. Company; Self-Leveling Underlayment
 - c. ChemRex; MBT Mastertop 110 Plus Underlayment, Sonneborn Sonocrete Sonoflow, or Thoro Underlayment, Self-Leveling.
 - d. Conspec, a Dayton Superior Company; Conflow.
 - e. Dayton Superior Corporation; LeveLayer I.
 - f. Dependable Chemical Co., Inc.; Skimflow ES.
 - g. L&M Construction Chemicals, Inc.; Levelex.
 - h. MAPEI Corporation; Ultraplan 1.
 - i. Maxxon Corporation; Level-Right.
 - j. US Mix Products Company; US SPEC Self - Leveling Underlayment.
 - 2. Cement Binder: ASTM C 150, portland cement, or hydraulic or blended hydraulic cement as defined by ASTM C 219.
 - 3. Compressive Strength: Not less than 4100 psi (28 MPa) at 28 days when tested according to ASTM C 109/C 109M.
 - 4. Underlayment Additive: Resilient-emulsion product of underlayment manufacturer formulated for use with underlayment when applied to substrate and conditions indicated.

5. Underlayment product shall be compatible with the encapsulation product being proposed for approval by USEPA (United States Environmental Protection Agency).
- B. Aggregate: Well-graded, washed gravel, 1/8 to 1/4 inch (3 to 6 mm); or coarse sand as recommended by underlayment manufacturer.
 1. Provide aggregate when recommended in writing by underlayment manufacturer for underlayment thickness required.
- C. Water: Potable and at a temperature of not more than 70 deg F (21 deg C).
- D. Reinforcement: For underlayment applied to wood substrates, provide galvanized metal lath or other corrosion-resistant reinforcement recommended in writing by underlayment manufacturer.
- E. Primer: Product of underlayment manufacturer recommended in writing for substrate, conditions, and application indicated.
 1. Floors treated with epoxy encapsulate coating.
 2. Concrete.
 3. Non-porous substrates.
 4. Over metal.
- F. Corrosion-Resistant Coating: Recommended in writing by underlayment manufacturer for metal substrates.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, with Installer present, for conditions affecting performance.
 1. Proceed with application only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. General: Prepare and clean substrate according to manufacturer's written instructions.
 1. Treat nonmoving substrate cracks according to manufacturer's written instructions to prevent cracks from telegraphing (reflecting) through underlayment.
 2. Fill substrate voids to prevent underlayment from leaking.
- B. Concrete Substrates: Mechanically remove, according to manufacturer's written instructions, laitance, glaze, efflorescence, curing compounds, form-release agents, dust, dirt, grease, oil, and other contaminants that might impair underlayment bond.
 1. Moisture Testing: Perform anhydrous calcium chloride test, ASTM F 1869. Proceed with installation only after substrates do not exceed a maximum moisture-vapor-emission rate of 3 lb of water/1000 sq. ft. (1.36 kg of water/100 sq. m) in 24 hours.

- C. Wood Substrates: Mechanically fasten loose boards and panels to eliminate substrate movement and squeaks. Sand to remove coatings that might impair underlayment bond and remove sanding dust.
 - 1. Install underlayment reinforcement recommended in writing by manufacturer.
- D. Metal Substrates: Mechanically remove, according to manufacturer's written instructions, rust, foreign matter, and other contaminants that might impair underlayment bond. Apply corrosion-resistant coating compatible with underlayment if recommended in writing by underlayment manufacturer.
- E. Nonporous Substrates: For ceramic tile, quarry tile, and terrazzo substrates, remove waxes, sealants, and other contaminants that might impair underlayment bond, and prepare surfaces according to manufacturer's written instructions.
- F. Adhesion Tests: After substrate preparation, test substrate for adhesion with underlayment according to manufacturer's written instructions.

3.3 APPLICATION

- A. General: Mix and apply underlayment components according to manufacturer's written instructions.
 - 1. Close areas to traffic during underlayment application and for time period after application recommended in writing by manufacturer.
 - 2. Coordinate application of components to provide optimum underlayment-to-substrate and intercoat adhesion.
 - 3. At substrate expansion, isolation, and other moving joints, allow joint of same width to continue through underlayment.
- B. Apply primer over prepared substrate at manufacturer's recommended spreading rate.
- C. Apply underlayment to produce uniform, level surface.
 - 1. Apply a final layer without aggregate to produce surface.
 - 2. Feather edges to match adjacent floor elevations.
- D. Cure underlayment according to manufacturer's written instructions. Prevent contamination during application and curing processes.
- E. Do not install floor coverings over underlayment until after time period recommended in writing by underlayment manufacturer.
- F. Remove and replace underlayment areas that evidence lack of bond with substrate, including areas that emit a "hollow" sound when tapped.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

3.4 PROTECTION

- A. Protect underlayment from concentrated and rolling loads for remainder of construction period.

END OF SECTION 035416

SECTION 042200

CONCRETE UNIT MASONRY

PART 1 - GENERAL

1.1 SUMMARY:

- A. Section Includes:
1. Concrete masonry units (CMU's).
 2. Steel reinforcing bars.
 3. Mortar and grout.

1.2 PRECONSTRUCTION TESTING:

- A. Preconstruction Testing Service: Owner will engage a qualified independent testing agency to perform preconstruction testing indicated below. Retesting of materials that fail to comply with specified requirements shall be done at Contractor's expense.
1. Concrete Masonry Unit Test: For each type of unit required, according to ASTM C 140 for compressive strength.
 2. Mortar Test (Property Specification): For each mix required, according to ASTM C 109/C 109M for compressive strength.
 3. Grout Test (Compressive Strength): For each mix required, according to ASTM C 1019.

1.3 ACTION SUBMITTALS:

- A. Product Data: For each type of product indicated.
- B. Shop Drawings: For reinforcing steel. Detail bending and placement of unit masonry reinforcing bars. Comply with ACI 315, "Details and Detailing of Concrete Reinforcement." Show elevations of reinforced walls.
- C. Samples: For each type and color of exposed masonry unit.

1.4 INFORMATIONAL SUBMITTALS:

- A. Material Certificates: For each type and size of product indicated. For masonry units include data on material properties and material test reports substantiating compliance with requirements.
- B. Mix Designs: For each type of mortar and grout. Include description of type and proportions of ingredients.
1. Include test reports for mortar mixes required to comply with property specification. Test according to ASTM C 109/C 109M for compressive strength, ASTM C 1506 for water retention, and ASTM C 91 for air content.
 2. Include test reports, according to ASTM C 1019, for grout mixes required to comply with compressive strength requirement.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

1.5 QUALITY ASSURANCE:

- A. Masonry Standard: Comply with ACI 530.1/ASCE 6/TMS 602 and applicable State and County building code standards, unless modified by requirements in the Contract Documents.
- B. Performance Requirements: Concrete Masonry Assembly Compressive Strength (f'_m): 1,500 psi, determined by unit strength method.

1.6 PROJECT CONDITIONS:

- A. Cold-Weather Requirements: Do not use frozen materials or materials mixed or coated with ice or frost. Do not build on frozen substrates. Remove and replace unit masonry damaged by frost or by freezing conditions. Comply with cold-weather construction requirements contained in ACI 530.1/ASCE 6/TMS 602.
- B. Hot-Weather Requirements: Comply with hot-weather construction requirements contained in ACI 530.1/ASCE 6/TMS 602.

PART 2 - PRODUCTS

2.1 MASONRY UNITS, GENERAL:

- A. Defective Units: Referenced masonry unit standards may allow a certain percentage of units to contain chips, cracks, or other defects exceeding limits stated in the standard. Do not use units where such defects will be exposed in the completed Work.
- B. Fire-Resistance Ratings: Where indicated, provide units that comply with requirements for fire-resistance ratings indicated as determined by testing according to ASTM E 119, by equivalent masonry thickness, or by other means, as acceptable to authorities having jurisdiction.

2.2 CONCRETE MASONRY UNITS:

- A. Shapes: Provide shapes indicated and for lintels, corners, jambs, sashes, movement joints, headers, bonding, and other special conditions. Furnish solid, 1/2-height, sill and cap blocks where shown.
- B. CMUs: ASTM C 90.
 - 1. Unit Compressive Strength: Provide units with 1900 psi minimum net area compressive strength.
 - 2. Density Classification: Medium Weight unless otherwise indicated.

2.3 CONCRETE AND MASONRY LINTELS:

- A. General: Provide one of the following:
- B. Concrete Lintels: ASTM C 1623, matching CMUs in color, texture, and density classification; and with reinforcing bars indicated. Provide lintels with net-area compressive strength not less than CMUs.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Masonry Lintels: Prefabricated or built-in-place masonry lintels made from bond beam CMUs with reinforcing bars placed as indicated and filled with coarse grout.
- D. Steel Lintels: See Section 055000 - "Metal Fabrications."

2.4 MORTAR AND GROUT MATERIALS:

- A. Portland Cement: ASTM C 150, Type I or II, except Type III may be used for cold-weather construction. Provide natural color or white cement as required to produce mortar color indicated.
- B. Hydrated Lime: ASTM C 207, Type S.
- C. Portland Cement-Lime Mix: Packaged blend of portland cement and hydrated lime containing no other ingredients.
- D. Aggregate for Mortar: ASTM C 144.
- E. Aggregate for Grout: ASTM C 404.
- F. Water: Potable.

2.5 REINFORCEMENT:

- A. Uncoated Steel Reinforcing Bars: ASTM A 615/A 615M or ASTM A 996/A 996M, Grade 60 (Grade 420).
- B. Masonry Joint Reinforcement, General: ASTM A 951/A 951M.
 - 1. Interior Walls: Mill-galvanized, carbon steel.
 - 2. Wire Size for Side Rods: 0.148-inch (3.77-mm) diameter.
 - 3. Wire Size for Cross Rods: 0.148-inch (3.77-mm) diameter.
 - 4. Spacing of Cross Rods, Tabs, and Cross Ties: Not more than 16 inches (407 mm) o.c.
 - 5. Provide in lengths of not less than 10 feet (3 m), with prefabricated corner and tee units.

2.6 TIES AND ANCHORS:

- A. Materials: Provide ties and anchors specified in this article that are made from materials that comply with the following unless otherwise indicated.
 - 1. Hot-Dip Galvanized, Carbon-Steel Wire: ASTM A 82/A 82M; with ASTM A 153/A 153M, Class B-2 coating.
 - 2. Steel Sheet, Galvanized after Fabrication: ASTM A 1008/A 1008M, Commercial Steel, with ASTM A 153/A 153M, Class B coating.
 - 3. Steel Plates, Shapes, and Bars: ASTM A 36/A 36M.
- B. Adjustable Anchors for Connecting to Structural Steel Framing: Provide anchors that allow vertical or horizontal adjustment but resist tension and compression forces perpendicular to plane of wall.
 - 1. Anchor Section for Welding to Steel Frame: Crimped 1/4-inch- (6.35-mm-) diameter, hot-dip galvanized steel wire.
 - 2. Tie Section: Triangular-shaped wire tie, sized to extend within 1 inch (25 mm) of masonry face, made from 0.187-inch- (4.76-mm-) diameter, hot-dip galvanized steel wire.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Partition Top anchors: 0.105-inch- (2.66-mm-) thick metal plate with 3/8-inch- (9.5-mm-) diameter metal rod 6 inches (152 mm) long welded to plate and with closed-end plastic tube fitted over rod that allows rod to move in and out of tube. Fabricate from steel, hot-dip galvanized after fabrication.
- D. Rigid Anchors: Fabricate from steel bars 1-1/2 inches (38 mm) wide by 1/4 inch (6.35 mm) thick by 24 inches (610 mm) long, with ends turned up 2 inches (51 mm) or with cross pins unless otherwise indicated.
- E. Anchor Bolts: Headed or L-shaped steel bolts complying with ASTM A 307, Grade A (ASTM F 568M, Property Class 4.6); with ASTM A 563 (ASTM A 563M) hex nuts and, where indicated, flat washers; hot-dip galvanized to comply with ASTM A 153/A 153M, Class C; of dimensions indicated.
- F. Anchor Rods: ASTM A 325, Grade C, J- or L-shaped, sized for minimum 15-inch embedment; with ASTM A 153, Class B-2 galvanized finish. Furnish with washers and heavy hex nuts.

2.7 MISCELLANEOUS MASONRY ACCESSORIES:

- A. Compressible Filler: Premolded filler strips complying with ASTM D 1056, Grade 2A1; compressible up to 35 percent; formulated from neoprene, urethane or PVC.
- B. Preformed Control-Joint Gaskets: Made from styrene-butadiene-rubber compound, complying with ASTM D 2000, Designation M2AA-805 and designed to fit standard sash block and to maintain lateral stability in masonry wall; size and configuration as indicated.
- C. Bond-Breaker Strips: Asphalt-saturated, organic roofing felt complying with ASTM D 226, Type I (No. 15 asphalt felt).

2.8 MORTAR AND GROUT MIXES:

- A. General: Do not use admixtures, including pigments, air-entraining agents, accelerators, retarders, water-repellent agents, antifreeze compounds, or other admixtures unless otherwise indicated.
 - 1. Do not use calcium chloride in mortar or grout.
 - 2. Use portland cement-lime mortar unless otherwise indicated.
- B. Preblended, Dry Mortar Mix: Furnish dry mortar ingredients in form of a preblended mix. Measure quantities by weight to ensure accurate proportions, and thoroughly blend ingredients before delivering to Project site.
- C. Mortar for Unit Masonry: Comply with ASTM C 270, Proportion Specification. Provide the following types of mortar for applications stated unless another type is indicated.
 - 1. For reinforced masonry, use Type S.
 - 2. For interior non-load-bearing partitions, Type O may be used instead of Type N.
- D. Grout for Unit Masonry: Comply with ASTM C 476.
 - 1. Use grout of type indicated or, if not otherwise indicated, of type (fine or coarse) that will comply with Table 1.15.1 in ACI 530.1/ASCE 6/TMS 602 for dimensions of grout spaces and pour height.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

2. Proportion grout in accordance with ASTM C 476, Table 1 or paragraph 4.2.2 for specified 28-day compressive strength indicated, but not less than 2000 psi (14 MPa)].
3. Provide grout with a slump of 8 to 11 inches (203 to 279 mm) as measured according to ASTM C 143/C 143M.

PART 3 - EXECUTION

3.1 TOLERANCES:

A. Dimensions and Locations of Elements:

1. For dimensions in cross section or elevation do not vary by more than plus 1/2 inch (12 mm) or minus 1/4 inch (6 mm).
2. For location of elements in plan do not vary from that indicated by more than plus or minus 1/2 inch (12 mm).
3. For location of elements in elevation do not vary from that indicated by more than plus or minus 1/4 inch (6 mm) in a story height or 1/2 inch (12 mm) total.

B. Lines and Levels:

1. For bed joints and top surfaces of bearing walls do not vary from level by more than 1/4 inch in 10 feet (6 mm in 3 m), or 1/2 inch (12 mm) maximum.
2. For conspicuous horizontal lines, such as lintels, sills, parapets, and reveals, do not vary from level by more than 1/8 inch in 10 feet (3 mm in 3 m), 1/4 inch in 20 feet (6 mm in 6 m), or 1/2 inch (12 mm) maximum.
3. For vertical lines and surfaces do not vary from plumb by more than 1/4 inch in 10 feet (6 mm in 3 m), 3/8 inch in 20 feet (9 mm in 6 m), or 1/2 inch (12 mm) maximum.
4. For conspicuous vertical lines, such as external corners, door jambs, reveals, and expansion and control joints, do not vary from plumb by more than 1/8 inch in 10 feet (3 mm in 3 m), 1/4 inch in 20 feet (6 mm in 6 m), or 1/2 inch (12 mm) maximum.
5. For lines and surfaces do not vary from straight by more than 1/4 inch in 10 feet (6 mm in 3 m), 3/8 inch in 20 feet (9 mm in 6 m), or 1/2 inch (12 mm) maximum.

C. Joints:

1. For bed joints, do not vary from thickness indicated by more than plus or minus 1/8 inch (3 mm), with a maximum thickness limited to 1/2 inch (12 mm).
2. For head and collar joints, do not vary from thickness indicated by more than plus 3/8 inch (9 mm) or minus 1/4 inch (6 mm).
3. For exposed head joints, do not vary from thickness indicated by more than plus or minus 1/8 inch (3 mm).

3.2 LAYING MASONRY WALLS:

- A. Lay out walls in advance for accurate spacing of surface bond patterns with uniform joint thicknesses and for accurate location of openings, movement-type joints, returns, and offsets. Avoid using less-than-half-size units, particularly at corners, jambs, and, where possible, at other locations.
- B. Use full-size units without cutting if possible. If cutting is required to provide a continuous pattern or to fit adjoining construction, cut units with motor-driven saws; provide clean, sharp, unchipped edges. Allow units to dry before laying unless wetting of units is specified. Install cut units with cut surfaces and, where possible, cut edges concealed.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Bond Pattern for Exposed Masonry: Unless otherwise indicated, lay exposed masonry in running bond; do not use units with less than nominal 4-inch (100-mm) horizontal face dimensions at corners or jambs.
- D. Built-in Work: As construction progresses, build in items specified in this and other Sections. Fill in solidly with masonry around built-in items.
- E. Fill space between steel frames and masonry solidly with mortar unless otherwise indicated.
- F. Where built-in items are to be embedded in cores of hollow masonry units, place a layer of metal lath, wire mesh, or plastic mesh in the joint below and rod mortar or grout into core.
- G. Fill cores in hollow CMUs with grout 24 inches (600 mm) under bearing plates, beams, lintels, posts, and similar items unless otherwise indicated.

3.3 MORTAR BEDDING AND JOINTING:

- A. Lay hollow CMUs as follows:
 - 1. With face shells fully bedded in mortar and with head joints of depth equal to bed joints.
 - 2. With webs fully bedded in mortar in all courses of piers, columns, and pilasters.
 - 3. With webs fully bedded in mortar in grouted masonry, including starting course on footings.
 - 4. With entire units, including areas under cells, fully bedded in mortar at starting course on footings where cells are not grouted.
- B. Lay solid masonry units with completely filled bed and head joints; butter ends with sufficient mortar to fill head joints and shove into place. Do not deeply furrow bed joints or slush head joints.
- C. Tool exposed joints slightly concave when thumbprint hard, using a jointer larger than joint thickness unless otherwise indicated.
- D. Cut joints flush for masonry walls to receive plaster or other direct-applied finishes (other than paint), where cement parging is required, where resilient base is scheduled, or where dampproofing or waterproofing is indicated.

3.4 MASONRY JOINT REINFORCEMENT:

- A. General: Install entire length of longitudinal side rods in mortar with a minimum cover of 5/8 inch (16 mm) on exterior side of walls, 1/2 inch (13 mm) elsewhere. Lap reinforcement a minimum of 6 inches (150 mm).
 - 1. Space reinforcement not more than 16 inches (406 mm) o.c.
 - 2. Space reinforcement not more than 8 inches (203 mm) o.c. in foundation walls and parapet walls.
 - 3. Provide reinforcement not more than 8 inches (203 mm) above and below wall openings and extending 12 inches (305 mm) beyond openings in addition to continuous reinforcement.
- B. Interrupt joint reinforcement at control and expansion joints unless otherwise indicated.
- C. Provide continuity at wall intersections by using prefabricated T-shaped units.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- D. Provide continuity at corners by using prefabricated L-shaped units.

3.5 ANCHORING MASONRY TO STRUCTURAL STEEL AND CONCRETE:

- A. Anchor masonry to structural steel and concrete where masonry abuts or faces structural steel or concrete to comply with the following:
1. Provide an open space not less than 1/2 inch (13 mm) wide between masonry and structural steel or concrete unless otherwise indicated. Keep open space free of mortar and other rigid materials.
 2. Anchor masonry with anchors embedded in masonry joints and attached to structure.
 3. Space anchors as indicated, but not more than 24 inches (610 mm) o.c. vertically and 36 inches (915 mm) o.c. horizontally.

3.6 REINFORCED UNIT MASONRY INSTALLATION:

- A. Temporary Formwork and Shores: Construct formwork and shores as needed to support reinforced masonry elements during construction.
1. Construct formwork to provide shape, line, and dimensions of completed masonry as indicated. Make forms sufficiently tight to prevent leakage of mortar and grout. Brace, tie, and support forms to maintain position and shape during construction and curing of reinforced masonry.
 2. Do not remove forms and shores until reinforced masonry members have hardened sufficiently to carry their own weight and other loads that may be placed on them during construction.
- B. Placing Reinforcement: Comply with requirements in ACI 530.1/ASCE 6/TMS 602.
- C. Grouting: Do not place grout until entire height of masonry to be grouted has attained enough strength to resist grout pressure.
1. Comply with requirements in ACI 530.1/ASCE 6/TMS 602 for cleanouts and for grout placement, including minimum grout space and maximum pour height.
 2. Limit height of vertical grout pours to not more than 60 inches (1520 mm).

3.7 FIELD QUALITY CONTROL:

- A. Testing and Inspecting: Owner will engage special inspectors to perform tests and inspections and prepare reports. Allow inspectors access to scaffolding and work areas, as needed to perform tests and inspections. Retesting of materials that fail to meet specified requirements shall be done at Contractor's expense.
- B. Inspections: Level 1 special inspections according to the "International Building Code."
1. Begin masonry construction only after inspectors have verified proportions of site-prepared mortar.
 2. Place grout only after inspectors have verified compliance of grout spaces and of grades, sizes, and locations of reinforcement.
 3. Place grout only after inspectors have verified proportions of site-prepared grout.
- C. Testing Prior to Construction: One set of tests.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- D. Testing Frequency: One set of tests for each 5000 sq. ft. (464 sq. m) of wall area or portion thereof.
- E. Concrete Masonry Unit Test: For each type of unit provided, according to ASTM C 140 for compressive strength.
- F. Mortar Aggregate Ratio Test (Proportion Specification): For each mix provided, according to ASTM C 780.
- G. Mortar Test (Property Specification): For each mix provided, according to ASTM C 780. Test mortar for compressive strength.
- H. Grout Test (Compressive Strength): For each mix provided, according to ASTM C 1019.

3.8 REPAIRING, POINTING, AND CLEANING:

- A. In-Progress Cleaning: Clean unit masonry as work progresses by dry brushing to remove mortar fins and smears before tooling joints.
- B. Final Cleaning: After mortar is thoroughly set and cured, clean exposed masonry as follows:
 - 1. Test cleaning methods on sample wall panel; leave one-half of panel uncleaned for comparison purposes.
 - 2. Clean concrete masonry by cleaning method indicated in NCMA TEK 8-2A applicable to type of stain on exposed surfaces.

3.9 MASONRY WASTE DISPOSAL:

- A. Excess Masonry Materials: Unless otherwise indicated, excess masonry materials are Contractor's property. At completion of unit masonry work, remove from Project site.
- B. Masonry Waste: Remove masonry waste and legally dispose of off Owner's property.

END OF SECTION 042200

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. Products furnished, but not installed, under this Section include the following:
 - 1. Loose steel lintels.

1.3 SUBMITTALS:

- A. Product Data: For the following:
 - 1. Paint products.
- B. Shop Drawings: Show fabrication and installation details for metal fabrications.
 - 1. Include plans, elevations, sections, and details of metal fabrications and their connections. Show anchorage and accessory items.
 - 2. Provide templates for anchors and bolts specified for installation under other Sections.
 - 3. For installed products indicated to comply with design loads, include structural analysis data signed and sealed by the qualified professional engineer responsible for their preparation.
- C. Welding certificates.
- D. Qualification Data: For professional engineer.

1.4 QUALITY ASSURANCE:

- A. Welding: Qualify procedures and personnel according to the following:
 - 1. AWS D1.1, "Structural Welding Code--Steel."

1.5 PROJECT CONDITIONS:

- A. Field Measurements: Verify actual locations of walls and other construction contiguous with metal fabrications by field measurements before fabrication and indicate measurements on Shop Drawings.
 - 1. Established Dimensions: Where field measurements cannot be made without delaying the Work, establish dimensions and proceed with fabricating metal fabrications without field measurements. Coordinate wall and other contiguous construction to ensure that actual dimensions correspond to established dimensions.
 - 2. Provide allowance for trimming and fitting at site.

1.6 COORDINATION:

- A. Coordinate installation of anchorages for metal fabrications. Furnish setting drawings, templates, and directions for installing anchorages, including sleeves, concrete inserts, anchor bolts, and items with integral anchors, that are to be embedded in concrete or masonry. Deliver such items to Project site in time for installation.
- B. Coordinate installation of steel weld plates and angles for casting into concrete that are specified in this Section but required for work of another Section. Deliver such items to Project site in time for installation.

PART 2 - PRODUCTS

2.1 METALS, GENERAL:

- A. Metal Surfaces, General: Provide materials with smooth, flat surfaces, unless otherwise indicated. For metal fabrications exposed to view in the completed Work, provide materials without seam marks, roller marks, rolled trade names, or blemishes.

2.2 FERROUS METALS:

- A. Steel Plates, Shapes, and Bars: ASTM A 36/A 36M.

2.3 FASTENERS:

- A. General: Unless otherwise indicated, provide Type 304 stainless-steel fasteners for exterior use and zinc-plated fasteners with coating complying with ASTM B 633, Class Fe/Zn 5, at exterior walls. Provide stainless-steel fasteners for fastening aluminum. Select fasteners for type, grade, and class required.
- B. Steel Bolts and Nuts: Regular hexagon-head bolts, ASTM A 307, Grade A (ASTM F 568M, Property Class 4.6); with hex nuts, ASTM A 563 (ASTM A 563M); and, where indicated, flat washers.
- C. Anchor Bolts: ASTM F 1554, Grade 36.
 - 1. Provide hot-dip or mechanically deposited, zinc-coated anchor bolts where item being fastened is indicated to be galvanized.
- D. Eyebolts: ASTM A 489.
- E. Machine Screws: ASME B18.6.3 (ASME B18.6.7M).
- F. Lag Bolts: ASME B18.2.1 (ASME B18.2.3.8M).
- G. Plain Washers: Round, ASME B18.22.1 (ASME B18.22M).
- H. Lock Washers: Helical, spring type, ASME B18.21.1 (ASME B18.21.2M).
- I. Expansion Anchors: Anchor bolt and sleeve assembly with capability to sustain, without failure, a load equal to six times the load imposed when installed in unit masonry and four times the load imposed when installed in concrete, as determined by testing according to ASTM E 488, conducted by a qualified independent testing agency.
 - 1. Material for Anchors in Interior Locations: Carbon-steel components zinc-plated to comply with ASTM B 633, Class Fe/Zn 5.

2. Material for Anchors in Exterior Locations: Alloy Group 1 (A1) stainless-steel bolts complying with ASTM F 593 (ASTM F 738M) and nuts complying with ASTM F 594 (ASTM F 836M).

2.4 MISCELLANEOUS MATERIALS:

- A. Welding Rods and Bare Electrodes: Select according to AWS specifications for metal alloy welded.
- B. Universal Shop Primer: Fast-curing, lead- and chromate-free, universal modified-alkyd primer complying with MPI#79.
 1. Use primer with a VOC content of 420 g/L (3.5 lb/gal.) or less when calculated according to 40 CFR 59, Subpart D (EPA Method 24).
 2. Use primer containing pigments that make it easily distinguishable from zinc-rich primer.
- C. Bituminous Paint: Cold-applied asphalt emulsion complying with ASTM D 1187.
- D. Nonshrink, Metallic Grout: Factory-packaged, ferrous-aggregate grout complying with ASTM C 1107, specifically recommended by manufacturer for heavy-duty loading applications.
- E. Nonshrink, Nonmetallic Grout: Factory-packaged, nonstaining, noncorrosive, nongaseous grout complying with ASTM C 1107. Provide grout specifically recommended by manufacturer for interior and exterior applications.

2.5 FABRICATION, GENERAL:

- A. Shop Assembly: Preassemble items in the shop to greatest extent possible. Disassemble units only as necessary for shipping and handling limitations. Use connections that maintain structural value of joined pieces. Clearly mark units for reassembly and coordinated installation.
- B. Cut, drill, and punch metals cleanly and accurately. Remove burrs and ease edges to a radius of approximately 1/32 inch (1 mm), unless otherwise indicated. Remove sharp or rough areas on exposed surfaces.
- C. Form bent-metal corners to smallest radius possible without causing grain separation or otherwise impairing work.
- D. Form exposed work true to line and level with accurate angles and surfaces and straight edges.
- E. Weld corners and seams continuously to comply with the following:
 1. Use materials and methods that minimize distortion and develop strength and corrosion resistance of base metals.
 2. Obtain fusion without undercut or overlap.
 3. Remove welding flux immediately.
 4. At exposed connections, finish exposed welds and surfaces smooth and blended so no roughness shows after finishing and contour of welded surface matches that of adjacent surface.
- F. Form exposed connections with hairline joints, flush and smooth, using concealed fasteners where possible. Where exposed fasteners are required, use Phillips flat-head (countersunk) screws or bolts, unless otherwise indicated. Locate joints where least conspicuous.
- G. Fabricate seams and other connections that will be exposed to weather in a manner to exclude water. Provide weep holes where water may accumulate.

- H. Cut, reinforce, drill, and tap metal fabrications as indicated to receive finish hardware, screws, and similar items.
- I. Provide for anchorage of type indicated; coordinate with supporting structure. Space anchoring devices to secure metal fabrications rigidly in place and to support indicated loads.
 - 1. Where units are indicated to be cast into concrete or built into masonry, equip with integrally welded steel strap anchors, 1/8 by 1-1/2 inches (3.2 by 38 mm), with a minimum 6-inch (150-mm) embedment and 2-inch (50-mm) hook, not less than 8 inches (200 mm) from ends and corners of units and 24 inches (600 mm) o.c., unless otherwise indicated.

2.6 LOOSE STEEL LINTELS:

- A. Fabricate loose steel lintels from steel angles and shapes of size indicated for openings and recesses in masonry walls and partitions at locations indicated. Weld adjoining members together to form a single unit where indicated.
- B. Size loose lintels to provide bearing length at each side of openings equal to 1/12 of clear span but not less than 8 inches (200 mm), unless otherwise indicated.

2.7 MISCELLANEOUS FRAMING AND SUPPORTS:

- A. General: Provide steel framing and supports not specified in other Sections as needed to complete the Work.
- B. Fabricate units from steel shapes, plates, and bars of welded construction, unless otherwise indicated. Fabricate to sizes, shapes, and profiles indicated and as necessary to receive adjacent construction retained by framing and supports. Cut, drill, and tap units to receive hardware, hangers, and similar items.
 - 1. Fabricate units from slotted channel framing where indicated.
 - 2. Furnish inserts if units are installed after concrete is placed.
- C. Fabricate supports for operable partitions from continuous steel beams of sizes indicated with attached bearing plates, anchors, and braces as indicated. Drill bottom flanges of beams to receive partition track hanger rods; locate holes where indicated on operable partition Shop Drawings.
- D. Prime miscellaneous framing and supports with zinc-rich primer.

2.8 FINISHES, GENERAL:

- A. Comply with NAAMM's "Metal Finishes Manual for Architectural and Metal Products" for recommendations for applying and designating finishes.
- B. Finish metal fabrications after assembly.

2.9 STEEL AND IRON FINISHES:

- A. Preparation for Shop Priming: Prepare uncoated ferrous-metal surfaces to comply with minimum requirements indicated below for SSPC surface preparation specifications and environmental exposure conditions of installed metal fabrications:
 - 1. Interiors (SSPC Zone 1A): SSPC-SP 3, "Power Tool Cleaning."

- B. Shop Priming: Apply shop primer to uncoated surfaces of metal fabrications, except those with galvanized finishes and those to be embedded in concrete, sprayed-on fireproofing, or masonry, unless otherwise indicated. Comply with SSPC-PA 1, "Paint Application Specification No. 1: Shop, Field, and Maintenance Painting of Steel," for shop painting.
 - 1. Stripe paint corners, crevices, bolts, welds, and sharp edges.

PART 3 - EXECUTION

3.1 INSTALLATION, GENERAL:

- A. Cutting, Fitting, and Placement: Perform cutting, drilling, and fitting required for installing metal fabrications. Set metal fabrications accurately in location, alignment, and elevation; with edges and surfaces level, plumb, true, and free of rack; and measured from established lines and levels.
- B. Fit exposed connections accurately together to form hairline joints. Weld connections that are not to be left as exposed joints but cannot be shop welded because of shipping size limitations. Do not weld, cut, or abrade surfaces of exterior units that have been hot-dip galvanized after fabrication and are for bolted or screwed field connections.
- C. Fastening to In-Place Construction: Provide anchorage devices and fasteners where metal fabrications are required to be fastened to in-place construction. Provide threaded fasteners for use with concrete and masonry inserts, toggle bolts, through bolts, lag bolts, wood screws, and other connectors.
- D. Provide temporary bracing or anchors in formwork for items that are to be built into concrete, masonry, or similar construction.
- E. Corrosion Protection: Coat concealed surfaces of aluminum that will come into contact with grout, concrete, masonry, wood, or dissimilar metals with a heavy coat of bituminous paint.

3.2 INSTALLING MISCELLANEOUS FRAMING AND SUPPORTS:

- A. General: Install framing and supports to comply with requirements of items being supported, including manufacturers' written instructions and requirements indicated on Shop Drawings.
- B. Anchor supports for operable partitions securely to and rigidly brace from building structure.

3.3 ADJUSTING AND CLEANING:

- A. Touchup Painting: Immediately after erection, clean field welds, bolted connections, and abraded areas. Paint uncoated and abraded areas with the same material as used for shop painting to comply with SSPC-PA 1 for touching up shop-painted surfaces.
 - 1. Apply by brush or spray to provide a minimum 2.0-mil (0.05-mm) dry film thickness.

END OF SECTION 055000

SECTION 078413

PENETRATION FIRESTOPPING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. Section Includes:
 - 1. Penetrations in fire-resistance-rated walls.
 - 2. Penetrations in horizontal assemblies.
 - 3. Penetrations in smoke barriers.

- B. Related Requirements:
 - 1. Section 012100 "Allowances."

1.3 PREINSTALLATION MEETINGS:

- A. Preinstallation Conference: Conduct conference at Project site.

1.4 ACTION SUBMITTALS:

- A. Product Data: For each type of product.
- B. Product Schedule: For each penetration firestopping system. Include location, illustration of firestopping system, and design designation of qualified testing and inspecting agency.
 - 1. Engineering Judgments: Where Project conditions require modification to a qualified testing and inspecting agency's illustration for a particular penetration firestopping system, submit illustration, with modifications marked, approved by penetration firestopping system manufacturer's fire-protection engineer as an engineering judgment or equivalent fire-resistance-rated assembly. Obtain approval of authorities having jurisdiction prior to submittal.

1.5 INFORMATIONAL SUBMITTALS:

- A. Qualification Data: For Installer.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- B. Product Test Reports: For each penetration firestopping system, for tests performed by a qualified testing agency.

1.6 CLOSEOUT SUBMITTALS:

- A. Installer Certificates: From Installer indicating that penetration firestopping systems have been installed in compliance with requirements and manufacturer's written instructions.

1.7 QUALITY ASSURANCE:

- A. Installer Qualifications: A firm that has been approved by FM Global according to FM Global 4991, "Approval of Firestop Contractors," or been evaluated by UL and found to comply with its "Qualified Firestop Contractor Program Requirements."

1.8 PROJECT CONDITIONS:

- A. Environmental Limitations: Do not install penetration firestopping system when ambient or substrate temperatures are outside limits permitted by penetration firestopping system manufacturers or when substrates are wet because of rain, frost, condensation, or other causes.
- B. Install and cure penetration firestopping materials per manufacturer's written instructions using natural means of ventilations or, where this is inadequate, forced-air circulation.

1.9 COORDINATION:

- A. Coordinate construction of openings and penetrating items to ensure that penetration firestopping systems can be installed according to specified firestopping system design.
- B. Coordinate sizing of sleeves, openings, core-drilled holes, or cut openings to accommodate penetration firestopping systems.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS:

- A. Fire-Test-Response Characteristics:
 - 1. Perform penetration firestopping system tests by a qualified testing agency acceptable to authorities having jurisdiction.
 - 2. Test per testing standards referenced in "Penetration Firestopping Systems" Article. Provide rated systems complying with the following requirements:
 - a. Penetration firestopping systems shall bear classification marking of a qualified testing agency.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- 1) UL in its "Fire Resistance Directory."
- 2) Intertek Group in its "Directory of Listed Building Products."
- 3) FM Global in its "Building Materials Approval Guide."

2.2 PENETRATION FIRESTOPPING SYSTEMS:

- A. Penetration Firestopping Systems: Systems that resist spread of fire, passage of smoke and other gases, and maintain original fire-resistance rating of construction penetrated. Penetration firestopping systems shall be compatible with one another, with the substrates forming openings, and with penetrating items if any.
1. Manufacturers: Subject to compliance with requirements, provide products by the following:
 - a. 3M Fire Protection Products.
 - b. A/D Fire Protection Systems Inc.
 - c. Grabber Construction Products.
 - d. Hilti, Inc.
 - e. HOLDRITE.
 - f. NUCO Inc.
 - g. Passive Fire Protection Partners.
 - h. RectorSeal.
 - i. Specified Technologies, Inc.
 - j. Tremco, Inc.
- B. Penetrations in Fire-Resistance-Rated Walls: Penetration firestopping systems with ratings determined per ASTM E 814 or UL 1479, based on testing at a positive pressure differential of 0.01-inch wg (2.49 Pa).
1. F-Rating: Not less than the fire-resistance rating of constructions penetrated.
- C. Penetrations in Horizontal Assemblies: Penetration firestopping systems with ratings determined per ASTM E 814 or UL 1479, based on testing at a positive pressure differential of 0.01-inch wg (2.49 Pa).
1. F-Rating: At least one hour, but not less than the fire-resistance rating of constructions penetrated.
 2. T-Rating: At least one hour, but not less than the fire-resistance rating of constructions penetrated except for floor penetrations within the cavity of a wall.
 3. W-Rating: Provide penetration firestopping systems showing no evidence of water leakage when tested according to UL 1479.
- D. Penetrations in Smoke Barriers: Penetration firestopping systems with ratings determined per UL 1479, based on testing at a positive pressure differential of 0.30-inch wg (74.7 Pa).
1. L-Rating: Not exceeding 5.0 cfm/sq. ft. (0.025 cu. m/s per sq. m) of penetration opening at and no more than 50-cfm (0.024-cu. m/s) cumulative total for any 100 sq. ft. (9.3 sq. m) at both ambient and elevated temperatures.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- E. Exposed Penetration Firestopping Systems: Flame-spread and smoke-developed indexes of less than 25 and 450, respectively, per ASTM E 84.
- F. VOC Content: Penetration firestopping sealants and sealant primers shall comply with the following limits for VOC content:
 - 1. Sealants: 250 g/L.
 - 2. Sealant Primers for Nonporous Substrates: 250 g/L.
 - 3. Sealant Primers for Porous Substrates: 775 g/L.
- G. Low-Emitting Materials: Penetration firestopping sealants and sealant primers shall comply with the testing and product requirements of the California Department of Public Health's "Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers."
- H. Accessories: Provide components for each penetration firestopping system that are needed to install fill materials and to maintain ratings required. Use only those components specified by penetration firestopping system manufacturer and approved by qualified testing and inspecting agency for conditions indicated.
 - 1. Permanent forming/damming/backing materials.
 - 2. Substrate primers.
 - 3. Collars.
 - 4. Steel sleeves.

2.3 **FILL MATERIALS:**

- A. Cast-in-Place Firestop Devices: Factory-assembled devices for use in cast-in-place concrete floors and consisting of an outer sleeve lined with an intumescent strip, a flange attached to one end of the sleeve for fastening to concrete formwork, and a neoprene gasket.
- B. Latex Sealants: Single-component latex formulations that do not re-emulsify after cure during exposure to moisture.
- C. Firestop Devices: Factory-assembled collars formed from galvanized steel and lined with intumescent material sized to fit specific diameter of penetrant.
- D. Intumescent Composite Sheets: Rigid panels consisting of aluminum-foil-faced intumescent elastomeric sheet bonded to galvanized-steel sheet.
- E. Intumescent Putties: Nonhardening, water-resistant, intumescent putties containing no solvents or inorganic fibers.
- F. Intumescent Wrap Strips: Single-component intumescent elastomeric sheets with aluminum foil on one side.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- G. Mortars: Prepackaged dry mixes consisting of a blend of inorganic binders, hydraulic cement, fillers and lightweight aggregate formulated for mixing with water at Project site to form a nonshrinking, homogeneous mortar.
- H. Pillows/Bags: Reusable heat-expanding pillows/bags consisting of glass-fiber cloth cases filled with a combination of mineral-fiber, water-insoluble expansion agents, and fire-retardant additives. Where exposed, cover openings with steel-reinforcing wire mesh to protect pillows/bags from being easily removed.
- I. Silicone Foams: Multicomponent, silicone-based liquid elastomers that, when mixed, expand and cure in place to produce a flexible, nonshrinking foam.
- J. Silicone Sealants: Single-component, silicone-based, neutral-curing elastomeric sealants.

2.4 MIXING:

- A. Penetration Firestopping Materials: For those products requiring mixing before application, comply with penetration firestopping system manufacturer's written instructions for accurate proportioning of materials, water (if required), type of mixing equipment, selection of mixer speeds, mixing containers, mixing time, and other items or procedures needed to produce products of uniform quality with optimum performance characteristics for application indicated.

PART 3 - EXECUTION

3.1 EXAMINATION:

- A. Examine substrates and conditions, with Installer present, for compliance with requirements for opening configurations, penetrating items, substrates, and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION:

- A. Surface Cleaning: Before installing penetration firestopping systems, clean out openings immediately to comply with manufacturer's written instructions and with the following requirements:
 - 1. Remove from surfaces of opening substrates and from penetrating items foreign materials that could interfere with adhesion of penetration firestopping materials.
 - 2. Clean opening substrates and penetrating items to produce clean, sound surfaces capable of developing optimum bond with penetration firestopping materials. Remove loose particles remaining from cleaning operation.
 - 3. Remove laitance and form-release agents from concrete.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- B. Prime substrates where recommended in writing by manufacturer using that manufacturer's recommended products and methods. Confine primers to areas of bond; do not allow spillage and migration onto exposed surfaces.

3.3 INSTALLATION:

- A. General: Install penetration firestopping systems to comply with manufacturer's written installation instructions and published drawings for products and applications.
- B. Install forming materials and other accessories of types required to support fill materials during their application and in the position needed to produce cross-sectional shapes and depths required to achieve fire ratings.
 - 1. After installing fill materials and allowing them to fully cure, remove combustible forming materials and other accessories not forming permanent components of firestopping.
- C. Install fill materials by proven techniques to produce the following results:
 - 1. Fill voids and cavities formed by openings, forming materials, accessories and penetrating items to achieve required fire-resistance ratings.
 - 2. Apply materials so they contact and adhere to substrates formed by openings and penetrating items.
 - 3. For fill materials that will remain exposed after completing the Work, finish to produce smooth, uniform surfaces that are flush with adjoining finishes.

3.4 IDENTIFICATION:

- A. Wall Identification: Permanently label walls containing penetration firestopping systems with the words "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS," using lettering not less than 3 inches (76 mm) high and with minimum 0.375-inch (9.5-mm) strokes.
 - 1. Locate in accessible concealed floor, floor-ceiling, or attic space at 15 feet (4.57 m) from end of wall and at intervals not exceeding 30 feet (9.14 m).
- B. Penetration Identification: Identify each penetration firestopping system with legible metal or plastic labels. Attach labels permanently to surfaces adjacent to and within 6 inches (150 mm) of penetration firestopping system edge so labels are visible to anyone seeking to remove penetrating items or firestopping systems. Use mechanical fasteners or self-adhering-type labels with adhesives capable of permanently bonding labels to surfaces on which labels are placed. Include the following information on labels:
 - 1. The words "Warning - Penetration Firestopping - Do Not Disturb. Notify Building Management of Any Damage."
 - 2. Contractor's name, address, and phone number.
 - 3. Designation of applicable testing and inspecting agency.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

4. Date of installation.
5. Manufacturer's name.
6. Installer's name.

3.5 FIELD QUALITY CONTROL:

- A. Owner will engage a qualified testing agency to perform tests and inspections according to ASTM E 2174.
- B. Where deficiencies are found or penetration firestopping system is damaged or removed because of testing, repair or replace penetration firestopping system to comply with requirements.
- C. Proceed with enclosing penetration firestopping systems with other construction only after inspection reports are issued and installations comply with requirements.

3.6 CLEANING AND PROTECTION:

- A. Clean off excess fill materials adjacent to openings as the Work progresses by methods and with cleaning materials that are approved in writing by penetration firestopping system manufacturers and that do not damage materials in which openings occur.
- B. Provide final protection and maintain conditions during and after installation that ensure that penetration firestopping systems are without damage or deterioration at time of Substantial Completion. If, despite such protection, damage or deterioration occurs, immediately cut out and remove damaged or deteriorated penetration firestopping material and install new materials to produce systems complying with specified requirements.

3.7 PENETRATION FIRESTOPPING SYSTEM SCHEDULE:

- A. Where UL-classified systems are indicated, they refer to system numbers in UL's "Fire Resistance Directory" under product Category XHEZ.
- B. Where Intertek Group-listed systems are indicated, they refer to design numbers in Intertek Group's "Directory of Listed Building Products" under "Firestop Systems."
- C. Where FM Global-approved systems are indicated, they refer to design numbers listed in FM Global's "Building Materials Approval Guide" under "Wall and Floor Penetration Fire Stops."
- D. Penetration Firestopping Systems with No Penetrating Items[**FS-1**]:
 1. UL-Classified Systems: W-L-]0016.
 2. F-Rating: 1 hour and 2 hours.
 3. T-Rating: 1 hour and 2 hours.
 4. L-Rating at Ambient: Less than 1cfm/sq. ft. (cu. m/s per sq. m).
 5. L-Rating at 400 Deg F (204 Deg C): Less than 1 cfm/sq. ft. (cu. m/s per sq. m)>.
 6. W-Rating: No leakage of water at completion of water leakage testing.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

7. Type of Fill Materials: As required to achieve rating.
- E. Penetration Firestopping Systems for Metallic Pipes, Conduit, or Tubing [FS-2]:
1. UL-Classified Systems: W-L-1029.
 2. F-Rating: 1 hour and 2 hours.
 3. T-Rating: 0 hour.
 4. L-Rating at Ambient: Less than 1cfm/sq. ft. (cu. m/s per sq. m).
 5. L-Rating at 400 Deg F (204 Deg C): Less than 1 cfm/sq. ft. (cu. m/s per sq. m).
 6. W-Rating: No leakage of water at completion of water leakage testing.
 7. Type of Fill Materials: As required to achieve rating.
- F. Penetration Firestopping Systems for Nonmetallic Pipe, Conduit, or Tubing [FS-3]:
1. UL-Classified Systems: W-L-2046.
 2. F-Rating: 1 hour and 2 hours.
 3. T-Rating: 1/2 hour.
 4. L-Rating at Ambient: Less than 1cfm/sq. ft. (cu. m/s per sq. m).
 5. L-Rating at 400 Deg F (204 Deg C): Less than 1cfm/sq. ft. (cu. m/s per sq. m).
 6. W-Rating: No leakage of water at completion of water leakage testing.
 7. Type of Fill Materials: As required to achieve rating.
- G. Penetration Firestopping Systems for Electrical Cables [FS-4]:
1. UL-Classified Systems: W-L-3210.
 2. F-Rating: 1 hour and 2 hours.
 3. T-Rating: 3/4 hour.
 4. L-Rating at Ambient: N/A.
 5. L-Rating at 400 Deg F (204 Deg C): N/A.
 6. W-Rating: No leakage of water at completion of water leakage testing.
 7. Type of Fill Materials: As required to achieve rating.
- H. Penetration Firestopping Systems for Cable Trays with Electric Cables [FS-5]:
1. UL-Classified Systems: W-L-4005.
 2. F-Rating: 1 hour and 2 hours.
 3. T-Rating: 0 hour.
 4. L-Rating at Ambient: N/A.
 5. L-Rating at 400 Deg F (204 Deg C): N/A.
 6. W-Rating: No leakage of water at completion of water leakage testing.
 7. Type of Fill Materials: As required to achieve rating.
- I. Penetration Firestopping Systems for Insulated Pipes [FS-6]:
1. UL-Classified Systems: W-L-5159.
 2. F-Rating: 3 hour and 4hours.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

3. T-Rating: 1-1/2 hour.
4. L-Rating at Ambient: Less than 1cfm/sq. ft. (cu. m/s per sq. m).
5. L-Rating at 400 Deg F (204 Deg C): Less than 1cfm/sq. ft. (cu. m/s per sq. m).
6. W-Rating: No leakage of water at completion of water leakage testing.
7. Type of Fill Materials: As required to achieve rating.

J. Penetration Firestopping Systems for Miscellaneous Electrical Penetrants [FS-7]:

1. UL-Classified Systems: W-L- 6001.
2. F-Rating: 1 hour and 2 hours.
3. T-Rating: 0 hours.
4. L-Rating at Ambient: Less than 1cfm/sq. ft. (cu. m/s per sq. m).
5. L-Rating at 400 Deg F (204 Deg C): Less than 1cfm/sq. ft. (cu. m/s per sq. m).
6. W-Rating: No leakage of water at completion of water leakage testing.
7. Type of Fill Materials: As required to achieve rating.

K. Penetration Firestopping Systems for Miscellaneous Mechanical Penetrants [FS-8]:

1. UL-Classified Systems: W-L- 7029.
2. F-Rating: 1 hour and 2 hours.
3. T-Rating: 1/4 hour.
4. L-Rating at Ambient: N/A.
5. L-Rating at 400 Deg F (204 Deg C): N/A.
6. W-Rating: No leakage of water at completion of water leakage testing.
7. Type of Fill Materials: As required to achieve rating.

L. Penetration Firestopping Systems for Groupings of Penetrants [FS-9]:

1. UL-Classified Systems: W-L-8011.
2. F-Rating: 1 hour and 2 hours.
3. T-Rating: 1/2 hour.
4. L-Rating at Ambient: N/A.
5. L-Rating at 400 Deg F (204 Deg C): N/A.
6. W-Rating: No leakage of water at completion of water leakage testing.
7. Type of Fill Materials: As required to achieve rating.

END OF SECTION 078413

SECTION 081113

HOLLOW METAL DOORS AND FRAMES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Standard hollow metal door frames.
- B. Related Sections:
 - 1. Division 09 Section "Painting" for field painting hollow metal doors and frames.

1.3 DEFINITIONS

- A. Minimum Thickness: Minimum thickness of base metal without coatings.
- B. Standard Hollow Metal Work: Hollow metal work fabricated according to ANSI/SDI A250.8.
- C. Custom Hollow Metal Work: Hollow metal work fabricated according to ANSI/NAAMM-HMMA 861.

1.4 SUBMITTALS

- A. Product Data: For each type of product indicated. Include construction details, material descriptions, core descriptions, fire-resistance rating, and finishes.
- B. Shop Drawings: Include the following:
 - 1. Elevations of each door design.
 - 2. Details of doors, including vertical and horizontal edge details and metal thicknesses.
 - 3. Frame details for each frame type, including dimensioned profiles and metal thicknesses.
 - 4. Locations of reinforcement and preparations for hardware.
 - 5. Details of each different wall opening condition.
 - 6. Details of anchorages, joints, field splices, and connections.
 - 7. Details of accessories.
- C. Samples for Verification:
 - 1. For each type of exposed finish required, prepared on Samples of not less than 3 by 5 inches (75 by 125 mm).
 - 2. For the following items, prepared on Samples about 12 by 12 inches (305 by 305 mm) to demonstrate compliance with requirements for quality of materials and construction:
 - a. Frames: Show profile, corner joint, floor and wall anchors, and silencers. Include separate section showing fixed hollow metal panels and glazing if applicable.

D. Other Action Submittals:

1. Schedule: Provide a schedule of hollow metal work prepared by or under the supervision of supplier, using same reference numbers for details and openings as those on Drawings. Coordinate with door hardware schedule.

E. Oversize Construction Certification: For assemblies required to be fire rated and exceeding limitations of labeled assemblies.

F. Product Test Reports: Based on evaluation of comprehensive tests performed by a qualified testing agency, for each type of hollow metal door frame assembly.

1.5 QUALITY ASSURANCE

A. Source Limitations: Obtain hollow metal work from single source from single manufacturer.

B. Preinstallation Conference: Conduct conference at Project site.

1.6 DELIVERY, STORAGE, AND HANDLING

A. Deliver hollow metal work palletized, wrapped, or crated to provide protection during transit and Project-site storage. Do not use nonvented plastic.

1. Provide additional protection to prevent damage to finish of factory-finished units.

B. Deliver welded frames with two removable spreader bars across bottom of frames, tack welded to jambs and mullions.

C. Store hollow metal work under cover at Project site. Place in stacks of five units maximum in a vertical position with heads up, spaced by blocking, on minimum 4-inch- (102-mm-) high wood blocking. Do not store in a manner that traps excess humidity.

1.7 PROJECT CONDITIONS

A. Field Measurements: Verify actual dimensions of openings by field measurements before fabrication.

1.8 COORDINATION

A. Coordinate installation of anchorages for hollow metal frames. Furnish setting drawings, templates, and directions for installing anchorages, including sleeves, concrete inserts, anchor bolts, and items with integral anchors. Deliver such items to Project site in time for installation.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

1. Amweld Building Products, LLC.
2. Benchmark; a division of Therma-Tru Corporation.
3. Ceco Door Products; an Assa Abloy Group company.
4. Curries Company; an Assa Abloy Group company.
5. Deansteel Manufacturing Company, Inc.

6. Firedoor Corporation.
7. Fleming Door Products Ltd.; an Assa Abloy Group company.
8. Habersham Metal Products Company.
9. Kewanee Corporation (The).
10. Mesker Door Inc.
11. Pioneer Industries, Inc.
12. Security Metal Products Corp.
13. Steelcraft; an Ingersoll-Rand company.
14. Windsor Republic Doors.
15. de La Fontaine Industries.
16. The Philipp Manufacturing Company.

2.2 MATERIALS

- A. Cold-Rolled Steel Sheet: ASTM A 1008/A 1008M, Commercial Steel (CS), Type B; suitable for exposed applications.
- B. Hot-Rolled Steel Sheet: ASTM A 1011/A 1011M, Commercial Steel (CS), Type B; free of scale, pitting, or surface defects; pickled and oiled.
- C. Metallic-Coated Steel Sheet: ASTM A 653/A 653M, Commercial Steel (CS), Type B; with minimum G60 (Z180) or A60 (ZF180) metallic coating.
- D. Frame Anchors: ASTM A 591/A 591M, Commercial Steel (CS), 40Z (12G) coating designation; mill phosphatized.
 1. For anchors built into exterior walls, steel sheet complying with ASTM A 1008/A 1008M or ASTM A 1011/A 1011M, hot-dip galvanized according to ASTM A 153/A 153M, Class B.
- E. Inserts, Bolts, and Fasteners: Hot-dip galvanized according to ASTM A 153/A 153M.
- F. Powder-Actuated Fasteners in Concrete: Fastener system of type suitable for application indicated, fabricated from corrosion-resistant materials, with clips or other accessory devices for attaching hollow metal frames of type indicated.
- G. Grout: ASTM C 476, except with a maximum slump of 4 inches (102 mm), as measured according to ASTM C 143/C 143M.
- H. Bituminous Coating: Cold-applied asphalt mastic, SSPC-Paint 12, compounded for 15-mil (0.4-mm) dry film thickness per coat. Provide inert-type noncorrosive compound free of asbestos fibers, sulfur components, and other deleterious impurities.

2.3 STANDARD HOLLOW METAL FRAMES

- A. General: Comply with ANSI/SDI A250.8 and with details indicated for type and profile.
- B. Interior Frames: Fabricated from cold-rolled steel sheet unless metallic-coated sheet is indicated.
 1. Fabricate frames with mitered or coped corners.
 2. Fabricate frames as face welded unless otherwise indicated.
 3. Frames shall be fully-welded seamless construction.
 4. Frames for Wood Doors: 0.053-inch- (1.3-mm-) thick steel sheet.

- C. Hardware Reinforcement: Fabricate according to ANSI/SDI A250.6 with reinforcement plates from same material as frames.

2.4 FRAME ANCHORS

A. Jamb Anchors:

1. Masonry Type: Adjustable strap-and-stirrup or T-shaped anchors to suit frame size, not less than 0.042 inch (1.0 mm) thick, with corrugated or perforated straps not less than 2 inches (50 mm) wide by 10 inches (250 mm) long; or wire anchors not less than 0.177 inch (4.5 mm) thick.
2. Stud-Wall Type: Designed to engage stud, welded to back of frames; not less than 0.042 inch (1.0 mm) thick.
3. Compression Type for Drywall Slip-on Frames: Adjustable compression anchors.
4. Postinstalled Expansion Type for In-Place Concrete or Masonry: Minimum 3/8-inch- (9.5-mm-) diameter bolts with expansion shields or inserts. Provide pipe spacer from frame to wall, with throat reinforcement plate, welded to frame at each anchor location.

B. Floor Anchors: Formed from same material as frames, not less than 0.042 inch (1.0 mm) thick, and as follows:

1. Monolithic Concrete Slabs: Clip-type anchors, with two holes to receive fasteners.
2. Separate Topping Concrete Slabs: Adjustable-type anchors with extension clips, allowing not less than 2-inch (50-mm) height adjustment. Terminate bottom of frames at finish floor surface.

2.5 FABRICATION

- A. Fabricate hollow metal work to be rigid and free of defects, warp, or buckle. Accurately form metal to required sizes and profiles, with minimum radius for thickness of metal. Where practical, fit and assemble units in manufacturer's plant. To ensure proper assembly at Project site, clearly identify work that cannot be permanently factory assembled before shipment.

- B. Tolerances: Fabricate hollow metal work to tolerances indicated in SDI 117.

- C. Hollow Metal Frames: Where frames are fabricated in sections due to shipping or handling limitations, provide alignment plates or angles at each joint, fabricated of same thickness metal as frames.

1. Welded Frames: Weld flush face joints continuously; grind, fill, dress, and make smooth, flush, and invisible.
2. Provide countersunk, flat- or oval-head exposed screws and bolts for exposed fasteners unless otherwise indicated.
3. Grout Guards: Weld guards to frame at back of hardware mortises in frames to be grouted.
4. Floor Anchors: Weld anchors to bottom of jambs and mullions with at least four spot welds per anchor.
5. Jamb Anchors: Provide number and spacing of anchors as follows:
 - a. Masonry Type: Locate anchors not more than 18 inches (457 mm) from top and bottom of frame. Space anchors not more than 32 inches (813 mm) o.c. and as follows:
 - 1) Two anchors per jamb up to 60 inches (1524 mm) high.
 - 2) Three anchors per jamb from 60 to 90 inches (1524 to 2286 mm) high.
 - 3) Four anchors per jamb from 90 to 120 inches (2286 to 3048 mm) high.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- 4) Four anchors per jamb plus 1 additional anchor per jamb for each 24 inches (610 mm) or fraction thereof above 120 inches (3048 mm) high.
 - b. Compression Type: Not less than two anchors in each jamb.
 - c. Postinstalled Expansion Type: Locate anchors not more than 6 inches (152 mm) from top and bottom of frame. Space anchors not more than 26 inches (660 mm) o.c.
- 6. Door Silencers: Except on weather-stripped doors, drill stops to receive door silencers as follows. Keep holes clear during construction.
 - a. Single-Door Frames: Drill stop in strike jamb to receive three door silencers.
 - b. Double-Door Frames: Drill stop in head jamb to receive two door silencers.
- D. Fabricate concealed stiffeners, edge channels, and hardware reinforcement from either cold- or hot-rolled steel sheet.
- E. Hardware Preparation: Factory prepare hollow metal work to receive templated mortised hardware; include cutouts, reinforcement, mortising, drilling, and tapping according to the Door Hardware Schedule and templates furnished as specified in Division 08 Section "Door Hardware."
 - 1. Locate hardware as indicated, or if not indicated, according to ANSI/SDI A250.8.
 - 2. Reinforce door frames to receive nontemplated, mortised and surface-mounted door hardware.
 - 3. Comply with applicable requirements in ANSI/SDI A250.6 and ANSI/DHI A115 Series specifications for preparation of hollow metal work for hardware.
 - 4. Coordinate locations of conduit and wiring boxes for electrical connections with Division 26 Sections.

2.6 STEEL FINISHES

- A. Prime Finish: Apply manufacturer's standard primer immediately after cleaning and pretreating.
 - 1. Shop Primer: Manufacturer's standard, fast-curing, lead- and chromate-free primer complying with ANSI/SDI A250.10 acceptance criteria; recommended by primer manufacturer for substrate; compatible with substrate and field-applied coatings despite prolonged exposure.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of the Work.
- B. Examine roughing-in for embedded and built-in anchors to verify actual locations before frame installation.
- C. For the record, prepare written report, endorsed by Installer, listing conditions detrimental to performance of the Work.
- D. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Remove welded-in shipping spreaders installed at factory. Restore exposed finish by grinding, filling, and dressing, as required to make repaired area smooth, flush, and invisible on exposed faces.
- B. Prior to installation, adjust and securely brace welded hollow metal frames for squareness, alignment, twist, and plumbness to the following tolerances:
 - 1. Squareness: Plus or minus 1/16 inch (1.6 mm), measured at door rabbet on a line 90 degrees from jamb perpendicular to frame head.
 - 2. Alignment: Plus or minus 1/16 inch (1.6 mm), measured at jambs on a horizontal line parallel to plane of wall.
 - 3. Twist: Plus or minus 1/16 inch (1.6 mm), measured at opposite face corners of jambs on parallel lines, and perpendicular to plane of wall.
 - 4. Plumbness: Plus or minus 1/16 inch (1.6 mm), measured at jambs on a perpendicular line from head to floor.
- C. Drill and tap door frames to receive door hardware.

3.3 INSTALLATION

- A. General: Install hollow metal work plumb, rigid, properly aligned, and securely fastened in place; comply with Drawings and manufacturer's written instructions.
- B. Hollow Metal Frames: Install hollow metal frames of size and profile indicated. Comply with ANSI/SDI A250.11.
 - 1. Set frames accurately in position, plumbed, aligned, and braced securely until permanent anchors are set. After wall construction is complete, remove temporary braces, leaving surfaces smooth and undamaged.
 - a. At fire-protection-rated openings, install frames according to NFPA 80.
 - b. Where frames are fabricated in sections because of shipping or handling limitations, field splice at approved locations by welding face joint continuously; grind, fill, dress, and make splice smooth, flush, and invisible on exposed faces.
 - c. Install frames with removable glazing stops located on secure side of opening.
 - d. Install door silencers in frames before grouting.
 - e. Remove temporary braces necessary for installation only after frames have been properly set and secured.
 - f. Check plumbness, squareness, and twist of frames as walls are constructed. Shim as necessary to comply with installation tolerances.
 - g. Field apply bituminous coating to backs of frames that are filled with grout containing antifreezing agents.
 - 2. Floor Anchors: Provide floor anchors for each jamb and mullion that extends to floor, and secure with postinstalled expansion anchors.
 - a. Floor anchors may be set with powder-actuated fasteners instead of postinstalled expansion anchors if so indicated and approved on Shop Drawings.
 - 3. Metal-Stud Partitions: Solidly pack mineral-fiber insulation behind frames.
 - 4. Masonry Walls: Coordinate installation of frames to allow for solidly filling space between frames and masonry with grout.

5. Concrete Walls: Solidly fill space between frames and concrete with grout. Take precautions, including bracing frames, to ensure that frames are not deformed or damaged by grout forces.
6. In-Place Concrete or Masonry Construction: Secure frames in place with postinstalled expansion anchors. Countersink anchors, and fill and make smooth, flush, and invisible on exposed faces.
7. In-Place Gypsum Board Partitions: Secure frames in place with postinstalled expansion anchors through floor anchors at each jamb. Countersink anchors, and fill and make smooth, flush, and invisible on exposed faces.
8. Ceiling Struts: Extend struts vertically from top of frame at each jamb to overhead structural supports or substrates above frame unless frame is anchored to masonry or to other structural support at each jamb. Bend top of struts to provide flush contact for securing to supporting construction. Provide adjustable wedged or bolted anchorage to frame jamb members.
9. Installation Tolerances: Adjust hollow metal door frames for squareness, alignment, twist, and plumb to the following tolerances:
 - a. Squareness: Plus or minus 1/16 inch (1.6 mm), measured at door rabbet on a line 90 degrees from jamb perpendicular to frame head.
 - b. Alignment: Plus or minus 1/16 inch (1.6 mm), measured at jambs on a horizontal line parallel to plane of wall.
 - c. Twist: Plus or minus 1/16 inch (1.6 mm), measured at opposite face corners of jambs on parallel lines, and perpendicular to plane of wall.
 - d. Plumbness: Plus or minus 1/16 inch (1.6 mm), measured at jambs at floor.

3.4 ADJUSTING AND CLEANING

- A. Final Adjustments: Check and readjust operating hardware items immediately before final inspection. Leave work in complete and proper operating condition. Remove and replace defective work, including hollow metal work that is warped, bowed, or otherwise unacceptable.
- B. Remove grout and other bonding material from hollow metal work immediately after installation.
- C. Prime-Coat Touchup: Immediately after erection, sand smooth rusted or damaged areas of prime coat and apply touchup of compatible air-drying, rust-inhibitive primer.
- D. Metallic-Coated Surfaces: Clean abraded areas and repair with galvanizing repair paint according to manufacturer's written instructions.

END OF SECTION 081113

SECTION 081416

FLUSH WOOD DOORS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. This Section includes the following:
 - 1. Solid-core doors with wood-veneer faces.
 - 2. Factory finishing flush wood doors.
 - 3. Factory machining for hardware.
- B. Related Sections include the following:
 - 1. Division 08 Section "Door Hardware" for hardware requirements.

1.3 SUBMITTALS:

- A. Product Data: For each type of door. Include details of core and edge construction, trim for openings, and louvers.
 - 1. Include factory-finishing specifications.
- B. Shop Drawings: Indicate location, size, and hand of each door; elevation of each kind of door; construction details not covered in Product Data; location and extent of hardware blocking; and other pertinent data.
 - 1. Indicate dimensions and locations of mortises and holes for hardware.
 - 2. Indicate dimensions and locations of cutouts.
 - 3. Indicate requirements for veneer matching.
 - 4. Indicate doors to be factory finished and finish requirements.
- C. Samples for Initial Selection: Color charts consisting of actual materials in small sections for the following:
 - 1. Faces of factory-finished doors with transparent finish. Show the full range of colors available for stained finishes.

D. Samples for Verification: As follows:

1. Factory finishes applied to actual door face materials, approximately 8 by 10 inches, for each material and finish. For each wood species and transparent finish, provide set of three samples showing typical range of color and grain to be expected in the finished work.
2. Corner sections of doors approximately 8 by 10 inches with door faces and edgings representing the typical range of color and grain for each species of veneer and solid lumber required. Finish sample with same materials proposed for factory-finished doors.
3. Louver blade and frame sections, 6 inches long, for each material and finish specified.
4. Frames for light openings, 6 inches long, for each material, type, and finish required.

1.4 QUALITY ASSURANCE:

- A. Source Limitations: Obtain flush wood doors through one source from a single manufacturer.
- B. Quality Standard: In addition to requirements specified, comply with WDMA I.S.1-A-04, Industry Standard for "Architectural Wood Flush Doors."

1.5 DELIVERY, STORAGE, AND HANDLING:

- A. Protect doors during transit, storage, and handling to prevent damage, soiling, and deterioration. Comply with requirements of referenced standard and manufacturer's written instructions.
 1. Individually package doors in plastic bags or cardboard cartons.
- B. Mark each door with individual opening numbers used on Shop Drawings. Use removable tags or concealed markings.

1.6 PROJECT CONDITIONS:

- A. Environmental Limitations: Do not deliver or install doors until conditions for temperature and relative humidity have been stabilized and will be maintained in storage and installation areas during the remainder of the construction period to comply with requirements of the referenced quality standard for Project's geographical location.

1.7 WARRANTY:

- A. General Warranty: Door manufacturer's warranty specified in this Article shall not deprive the Owner of other rights the Owner may have under other provisions of the Contract Documents and shall be in addition to, and run concurrent with, other warranties made by the Contractor under requirements of the Contract Documents.

GLASTONBURY TRACKING NUMBER: GL-2017-26

- B. Door Manufacturer's Warranty: Submit written agreement on door manufacturer's standard form, signed by manufacturer, Installer, and Contractor, agreeing to repair or replace defective doors that have warped (bow, cup, or twist) more than 1/4 inch in a 42-by-84-inch section or that show telegraphing of core construction in face veneers exceeding 0.01 inch in a 3-inch span, or do not comply with tolerances in referenced quality standard.
1. Warranty shall also include installation and finishing that may be required due to repair or replacement of defective doors.
 2. Warranty shall be in effect during the following period of time after the date of Substantial Completion:
 - a. Solid-Core Interior Doors: Life of installation.

PART 2 - PRODUCTS

2.1 MANUFACTURERS:

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. Flush Wood Doors:
 - a. Algoma Hardwoods Inc.
 - b. Eggers Industries; Architectural Door Division.
 - c. Marshfield Door Systems, Inc.
 - d. VT Industries Inc.
 - e. Oshkosh Door Company.
 - f. Graham Wood Doors.

2.2 DOOR CONSTRUCTION, GENERAL:

- A. Low-Emitting Materials: Provide doors made with adhesives and composite wood products that do not contain urea formaldehyde.
- B. WDMA I.S.1-A Performance Grade: Extra Heavy Duty.

2.3 INTERIOR FLUSH WOOD DOORS:

- A. Doors for Transparent Finish: Comply with the following requirements:
1. Grade: Premium, with Grade A faces.
 2. Faces: Select white birch plain sawn/sliced.
 3. Match between Veneer Leaves: Book match.
 4. Match within Door Faces: Center balance match.
 5. Pair and Set Match: Provide for pairs of doors and for doors hung in adjacent sets.

6. Stiles: Same species as face or a compatible species.
 - a. Provide manufacturer's standard laminated-edge construction for improved screw-holding capability and split resistance as compared to edges composed of a single layer of treated lumber.
- B. Particleboard Cores: Comply with the following requirements:
 1. Particleboard: ANSI A208.1, Grade LD-2.
 2. Blocking: Provide wood blocking at particleboard-core doors as follows:
 - a. 5-inch top-rail blocking.
 - b. 5-inch bottom-rail blocking.
 - c. 5-by-10-inch inner blocking for all surface mounted hardware.
 - d. 5-inch midrail blocking, at doors indicated to have exit devices.

2.4 FABRICATION:

- A. Fabricate flush wood doors in sizes indicated for Project site fitting.
- B. Factory fit doors to suit frame-opening sizes indicated, with the following uniform clearances and bevels, unless otherwise indicated:
 1. Comply with clearance requirements of referenced quality standard for fitting. Comply with requirements of NFPA 80 for fire-rated doors.
- C. Factory machine doors for hardware that is not surface applied. Locate hardware to comply with DHI-WDHS-3. Comply with final hardware schedules, door frame Shop Drawings, DHI A115-W series standards, and hardware templates.

2.5 FACTORY FINISHING:

- A. General: Comply with referenced quality standard's requirements for factory finishing.
- B. Finish wood doors at factory.
- C. Transparent Finish: Comply with requirements indicated for grade, finish system, staining effect, and sheen.
 1. Grade: Premium.
 2. Finish: WDMA System TR-6 catalyzed polyurethane.
 3. Staining "ST-1": Match #AL07 "Alpine;" VT Industries or Architect approved equal.
 4. Effect: Filled finish.
 5. Sheen: Satin.

PART 3 - EXECUTION

3.1 EXAMINATION:

- A. Examine installed door frames before hanging doors.
 - 1. Verify that frames comply with indicated requirements for type, size, location, and swing characteristics and have been installed with plumb jambs and level heads.
 - 2. Reject doors with defects.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION:

- A. Hardware: For installation, see Division 8 Section "Door Hardware."
- B. Manufacturer's Written Instructions: Install wood doors to comply with manufacturer's written instructions, referenced quality standard, and as indicated.
- C. Factory-Fitted Doors: Align in frames for uniform clearance at each edge.
- D. Factory-Finished Doors: Restore finish before installation, if fitting or machining is required at Project site.

3.3 ADJUSTING AND PROTECTING:

- A. Operation: Rehang or replace doors that do not swing or operate freely.
- B. Finished Doors: Replace doors that are damaged or do not comply with requirements. Doors may be repaired or refinished if work complies with requirements and shows no evidence of repair or refinishing.
- C. Protect doors as recommended by door manufacturer to ensure that wood doors are without damage or deterioration at the time of Substantial Completion.

END OF SECTION 081416

SECTION 087100

DOOR HARDWARE

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes:
 - 1. Mechanical door hardware for the following:
 - a. Swinging doors.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Shop Drawings: Details of electrified door hardware.
- C. Samples: For each exposed product and for each color and texture specified.
- D. Other Action Submittals:
 - 1. Door Hardware Schedule: Prepared by or under the supervision of Installer, detailing fabrication and assembly of door hardware, as well as installation procedures and diagrams. Coordinate final door hardware schedule with doors, frames, and related work to ensure proper size, thickness, hand, function, and finish of door hardware.
 - a. Format: Use same scheduling sequence and format as in the Contract Documents.
 - b. Content: Include the following information:
 - 1) Identification number, location, hand, fire rating, size, and material of each door and frame.
 - 2) Locations of each door hardware set, cross-referenced to Drawings on floor plans and to door and frame schedule.
 - 3) Complete designations, including name and manufacturer, type, style, function, size, quantity, function, and finish of each door hardware product.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

1.3 QUALITY ASSURANCE

- A. **Installer Qualifications:** Supplier of products and an employer of workers trained and approved by product manufacturers and an Architectural Hardware Consultant who is available during the course of the Work to consult with Contractor, Architect, and Owner about door hardware and keying.
- B. **Architectural Hardware Consultant Qualifications:** A person who is experienced in providing consulting services for door hardware installations that are comparable in material, design, and extent to that indicated for this Project.
- C. **Source Limitations:** Provide electrified door hardware from same manufacturer as mechanical door hardware, unless otherwise indicated. Manufacturers that perform electrical modifications and that are listed by a testing and inspecting agency acceptable to authorities having jurisdiction are acceptable.
- D. **Fire-Rated Door Assemblies:** Where fire-rated door assemblies are indicated, provide door hardware rated for use in assemblies complying with NFPA 80 that are listed and labeled by a qualified testing agency, for fire-protection ratings indicated, based on testing at positive pressure according to NFPA 252 or UL 10C, unless otherwise indicated.
- E. **Means of Egress Doors:** Latches do not require more than 15 lbf (67 N) to release the latch. Locks do not require use of a key, tool, or special knowledge for operation.
- F. **Accessibility Requirements:** For door hardware on doors in an accessible route, comply with the U.S. Architectural & Transportation Barriers Compliance Board's ADA-ABA Accessibility Guidelines, and ICC/ANSI A117.1.
 - 1. Provide operating devices that do not require tight grasping, pinching, or twisting of the wrist and that operate with a force of not more than 5 lbf (22.2 N).
 - 2. Comply with the following maximum opening-force requirements:
 - a. Interior, Non-Fire-Rated Hinged Doors: 5 lbf (22.2 N) applied perpendicular to door.

1.4 DELIVERY, STORAGE, AND HANDLING

- A. Deliver keys to manufacturer of key control system for subsequent delivery to Owner.

1.5 WARRANTY

- A. **Special Warranty:** Manufacturer's standard form in which manufacturer agrees to repair or replace components of door hardware that fail in materials or workmanship within specified warranty period.
 - 1. **Warranty Period:** Three years from date of Substantial Completion, unless otherwise indicated.

PART 2 - PRODUCTS

2.1 SCHEDULED DOOR HARDWARE

- A. Provide door hardware for each door as scheduled in Part 3 "Door Hardware Schedule" Article to comply with requirements in this Section.
 - 1. Door Hardware Sets: Provide quantity, item, size, finish or color indicated, and named manufacturers' products.
 - 2. Sequence of Operation: Provide electrified door hardware function, sequence of operation, and interface with other building control systems indicated.

- B. Designations: Requirements for design, grade, function, finish, size, and other distinctive qualities of each type of door hardware are indicated in Part 3 "Door Hardware Schedule" Article. Products are identified by using door hardware designations, as follows:
 - 1. Named Manufacturers' Products: Manufacturer and product designation are listed for each door hardware type required for the purpose of establishing minimum requirements. Manufacturers' names are abbreviated in Part 3 "Door Hardware Schedule" Article.
 - 2. References to BHMA Designations: Provide products complying with these designations and requirements for description, quality, and function.

2.2 HINGES

- A. Hinges: BHMA A156.1. Provide template-produced hinges for hinges installed on hollow-metal doors and hollow-metal frames.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by the following:
 - a. Stanley Commercial Hardware; Div. Of The Stanley Works.

2.3 MECHANICAL LOCKS AND LATCHES

- A. Strikes: Provide manufacturer's standard strike for each lock bolt or latchbolt complying with requirements indicated for applicable lock or latch and with strike box and curved lip extended to protect frame; finished to match lock or latch.
 - 1. Flat-Lip Strikes: For locks with three-piece antifriction latchbolts, as recommended by manufacturer.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- B. Bored Locks: BHMA A156.2; Grade 1; Series 4000.
 - 1. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on schedule or comparable product by one of the following:
 - a. Corbin Russwin Architectural Hardware; an ASSA ABLOY Group Company.
 - b. SARGENT Manufacturing Company; an ASSA ABLOY Group company.
 - c. Schlage Commercial Lock Division; an Ingersoll-Rand company.
 - d. Yale Security Inc.; an ASSA ABLOY Group company.

2.4 LOCK CYLINDERS

- A. Lock Cylinders: Tumbler type, constructed from brass or bronze, stainless steel, or nickel silver.
 - 1. Manufacturer: Same manufacturer as for locking devices.
- B. Construction Master Keys: Provide cylinders with feature that permits voiding of construction keys without cylinder removal. Provide 10 construction master keys.
- C. Construction Cores: Provide construction cores that are replaceable by permanent cores. Provide 10 construction master keys.

2.5 KEYING

- A. Keying System: Factory registered, complying with guidelines in BHMA A156.28, Appendix A. Incorporate decisions made in keying conference.
 - 1. Existing System:
 - a. Master key or grand master key locks to Owner's existing system.
 - b. Re-key Owner's existing master key system into new keying system.
 - 2. Keyed Alike: Key all cylinders to same change key.
- B. Keys: Nickel silver.
 - 1. Stamping: Permanently inscribe each key with a visual key control number and include the following notation:
 - a. Notation: "DO NOT DUPLICATE."
 - 2. Quantity: In addition to one extra key blank for each lock, provide the following:
 - a. Cylinder Change Keys: Three.
 - b. Master Keys: Three.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

2.6 SURFACE CLOSERS

- A. Surface Closers: BHMA A156.4; rack-and-pinion hydraulic type with adjustable sweep and latch speeds controlled by key-operated valves and forged-steel main arm. Comply with manufacturer's written recommendations for size of door closers depending on size of door, exposure to weather, and anticipated frequency of use. Provide factory-sized closers, adjustable to meet field conditions and requirements for opening force.
- B. Manufacturers: Subject to compliance with requirements, provide products by the following:
 - 1. LCN Closers; an Ingersoll-Rand company.

2.7 MECHANICAL STOPS AND HOLDERS

- A. Wall- and Floor-Mounted Stops: BHMA A156.16; polished cast brass, bronze, or aluminum base metal.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Rockwood Manufacturing Company.
 - b. Stanley Commercial Hardware; Div. Of The Stanley Works.
 - c. Trimco.

2.8 ARCHITECTURAL TRIM

- A. Door Protective Trim:
 - 1. General: Door protective trim units to be of type and design as specified below or in the Hardware Sets.
 - 2. Size: Fabricate protection plates (kick, armor, or mop) not more than 2" less than door width (LDW) on stop side of single doors and 1" LDW on stop side of pairs of doors, and not more than 1" less than door width on pull side. Coordinate and provide proper width and height as required where conflicting hardware dictates. Height to be as specified in the Hardware Sets.
 - 3. Metal Protection Plates: ANSI/BHMA A156.6 certified metal protection plates (kick, armor, or mop), beveled on four edges (B4E), fabricated from the following.
 - a. Stainless Steel: 050-inch ()thick, with countersunk screw holes (CSK).
 - b. Brass or Bronze: 050-inch ()thick, with countersunk screw holes (CSK).
 - c. Laminate Plastic or Acrylic: 1/8-inch thick, with countersunk screw holes (CSK).
 - 4. Fasteners: Provide manufacturer's designated fastener type as specified in the Hardware Sets.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

5. Acceptable Manufacturers:
 - a. Burns Manufacturing (BU).
 - b. Rockwood Manufacturing (RO).
 - c. Trimco (TC).
 - d. Or Approved Equal.

2.9 FABRICATION

- A. Fasteners: Provide door hardware manufactured to comply with published templates prepared for machine, wood, and sheet metal screws. Provide screws that comply with commercially recognized industry standards for application intended, except aluminum fasteners are not permitted. Provide Phillips flat-head screws with finished heads to match surface of door hardware, unless otherwise indicated.
 1. Concealed Fasteners: For door hardware units that are exposed when door is closed, except for units already specified with concealed fasteners. Do not use through bolts for installation where bolt head or nut on opposite face is exposed unless it is the only means of securely attaching the door hardware. Where through bolts are used on hollow door and frame construction, provide sleeves for each through bolt.
 2. Fire-Rated Applications:
 - a. Machine Screws: For the following:
 - 1) Hinges mortised to doors or frames.
 - 2) Strike plates to frames.
 - 3) Closers to doors and frames.
 - b. Steel Through Bolts: For the following unless door blocking is provided:
 - 1) Surface hinges to doors.
 - 2) Closers to doors and frames.
 - 3) Surface-mounted exit devices.
 3. Spacers or Sex Bolts: For through bolting of hollow-metal doors.
 4. EGasketing Fasteners: Provide noncorrosive fasteners for exterior applications and elsewhere as indicated.

2.10 FINISHES

- A. Provide finishes complying with BHMA A156.18 as indicated in door hardware schedule.
- B. Protect mechanical finishes on exposed surfaces from damage by applying a strippable, temporary protective covering before shipping.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Steel Doors and Frames: For surface applied door hardware, drill and tap doors and frames according to ANSI/SDI A250.6.
- B. Wood Doors: Comply with DHI WDHS.5 "Recommended Hardware Reinforcement Locations for Mineral Core Wood Flush Doors."
- C. Mounting Heights: Mount door hardware units at heights to comply with the following] unless otherwise indicated or required to comply with governing regulations.
 - 1. Standard Steel Doors and Frames: ANSI/SDI A250.8.
 - 2. Custom Steel Doors and Frames: HMMA 831.
 - 3. Wood Doors: DHI WDHS.3, "Recommended Locations for Architectural Hardware for Wood Flush Doors."
- D. Install each door hardware item to comply with manufacturer's written instructions. Where cutting and fitting are required to install door hardware onto or into surfaces that are later to be painted or finished in another way, coordinate removal, storage, and reinstallation of surface protective trim units with finishing work. Do not install surface-mounted items until finishes have been completed on substrates involved.
 - 1. Set units level, plumb, and true to line and location. Adjust and reinforce attachment substrates as necessary for proper installation and operation.
 - 2. Drill and countersink units that are not factory prepared for anchorage fasteners. Space fasteners and anchors according to industry standards.
- E. Hinges: Install types and in quantities indicated in door hardware schedule but not fewer than the number recommended by manufacturer for application indicated or one hinge for every 30 inches (750 mm) of door height, whichever is more stringent, unless other equivalent means of support for door, such as spring hinges or pivots, are provided.
- F. Stops: Provide floor stops for doors unless wall or other type stops are indicated in door hardware schedule. Do not mount floor stops where they will impede traffic.

3.2 FIELD QUALITY CONTROL

- A. Independent Architectural Hardware Consultant: Owner will engage a qualified independent Architectural Hardware Consultant to perform inspections and to prepare inspection reports.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

3.3 DOOR HARDWARE SCHEDULE

A. Door 101:

- | | | |
|----|--|-----------|
| 1. | 3 Hinge, Ball Bearing 191 - 4.5 x 4.5 - US32D | Stanley. |
| 2. | 1 Lockset, Classroom Security Lock ND75PD - 8-RHO - 626 - 10-025 | Schlage. |
| 3. | 1 Stop, Wall 409 - US26D | Rockwood. |
| 4. | 1 Closer, Overhead Parallel Arm 4040XP - AL - HEDA - TB | L.C.N. |
| 5. | 2 Kick Plates K1050 8" 4BE CSK US32D | RO |
| 6. | Prep hollow metal door frame for Owner provided electric strike in.
Accordance with drawing attached. | |

END OF SECTION 087100

3478

Electric Strike Metal Frame Preparation




1440 Ferris Place • Bronx • New York • 10461-3699

Telephone Number: (718) 829-2332

Fax Number: (718) 829-6405

Email: CustomerService@Trineonline.com

Website: www.Trineonline.com



SECTION 095113

ACOUSTICAL PANEL CEILINGS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes acoustical panels and exposed suspension systems for ceilings.
- B. Products furnished, but not installed under this Section, include anchors, clips, and other ceiling attachment devices to be cast in concrete at ceilings.

1.3 DEFINITIONS

- A. AC: Articulation Class.
- B. CAC: Ceiling Attenuation Class.
- C. LR: Light Reflectance coefficient.
- D. NRC: Noise Reduction Coefficient.

1.4 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Coordination Drawings: Reflected ceiling plans, drawn to scale, on which the following items are shown and coordinated with each other, based on input from installers of the items involved:
 - 1. Ceiling suspension system members.
 - 2. Method of attaching hangers to building structure.
 - a. Furnish layouts for cast-in-place anchors, clips, and other ceiling attachment devices whose installation is specified in other Sections.
 - 3. Ceiling-mounted items including lighting fixtures, diffusers, grilles, speakers, sprinklers, access panels, and special moldings.
 - 4. Minimum Drawing Scale: 1/8 inch = 1 foot (1:96).
- C. Samples for Initial Selection: For components with factory-applied color finishes.
- D. Samples for Verification: For each component indicated and for each exposed finish required, prepared on Samples of size indicated below.
 - 1. Acoustical Panel: Set of 6-inch- (150-mm-) square. Samples of each type, color, pattern, and texture.
 - 2. Exposed Suspension System Members, Moldings, and Trim: Set of 12-inch- (300-mm-) long Samples of each type, finish, and color.

- E. Qualification Data: For testing agency.
- F. Field quality-control test reports.
- G. Product Test Reports: Based on evaluation of comprehensive tests performed by a qualified testing agency, for each acoustical panel ceiling.
- H. Research/Evaluation Reports: For each acoustical panel ceiling and components and anchor and fastener type.
- I. Maintenance Data: For finishes to include in maintenance manuals.

1.5 QUALITY ASSURANCE

- A. Acoustical Testing Agency Qualifications: An independent testing laboratory, or an NVLAP-accredited laboratory, with the experience and capability to conduct the testing indicated. NVLAP-accredited laboratories must document accreditation, based on a "Certificate of Accreditation" and a "Scope of Accreditation" listing the test methods specified.
- B. Source Limitations:
 - 1. Acoustical Ceiling Panel: Obtain each type through one source from a single manufacturer.
 - 2. Suspension System: Obtain each type through one source from a single manufacturer.
- C. Source Limitations: Obtain each type of acoustical ceiling panel and supporting suspension system through one source from a single manufacturer.
- D. Fire-Test-Response Characteristics: Provide acoustical panel ceilings that comply with the following requirements:
 - 1. Surface-Burning Characteristics: Provide acoustical panels with the following surface-burning characteristics complying with ASTM E 1264 for Class A materials as determined by testing identical products per ASTM E 84:
 - a. Smoke-Developed Index: 450 or less.
- E. Seismic Standard: Provide acoustical panel ceilings designed and installed to withstand the effects of earthquake motions according to the following:
 - 1. Standard for Ceiling Suspension Systems Requiring Seismic Restraint: Comply with ASTM E 580.
 - 2. ASCE 7, "Minimum Design Loads for Buildings and Other Structures": Section 9, "Earthquake Loads."
- F. Mockups: Build mockups to verify selections made under sample submittals and to demonstrate aesthetic effects and set quality standards for materials and execution.
 - 1. Approved mockups may become part of the completed Work if undisturbed at time of Substantial Completion.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Deliver acoustical panels, suspension system components, and accessories to Project site in original, unopened packages and store them in a fully enclosed, conditioned space where they will be protected against damage from moisture, humidity, temperature extremes, direct sunlight, surface contamination, and other causes.

- B. Before installing acoustical panels, permit them to reach room temperature and a stabilized moisture content.
- C. Handle acoustical panels carefully to avoid chipping edges or damaging units in any way.

1.7 PROJECT CONDITIONS

- A. Environmental Limitations: Do not install acoustical panel ceilings until spaces are enclosed and weatherproof, wet work in spaces is complete and dry, work above ceilings is complete, and ambient temperature and humidity conditions are maintained at the levels indicated for Project when occupied for its intended use.

1.8 COORDINATION

- A. Coordinate layout and installation of acoustical panels and suspension system with other construction that penetrates ceilings or is supported by them, including light fixtures, HVAC equipment, fire-suppression system, and partition assemblies.

1.9 EXTRA MATERIALS

- A. Furnish extra materials described below that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Acoustical Ceiling Panels: 2 (two) boxes of full-size panels.

PART 2 - PRODUCTS

2.1 ACOUSTICAL PANELS, GENERAL

- A. Acoustical Panel Standard: Provide manufacturer's standard panels of configuration indicated that comply with ASTM E 1264 classifications as designated by types, patterns, acoustical ratings, and light reflectances, unless otherwise indicated.
 - 1. Mounting Method for Measuring NRC: Type E-400; plenum mounting in which face of test specimen is 15-3/4 inches (400 mm) away from test surface per ASTM E 795.
- B. Acoustical Panel Colors and Patterns: Match appearance characteristics indicated for each product type.
 - 1. Where appearance characteristics of acoustical panels are indicated by referencing pattern designations in ASTM E 1264 and not manufacturers' proprietary product designations, provide products selected by Architect from each manufacturer's full range that comply with requirements indicated for type, pattern, color, light reflectance, acoustical performance, edge detail, and size.
- C. Broad Spectrum Antimicrobial Fungicide and Bactericide Treatment: Provide acoustical panels treated with manufacturer's standard antimicrobial formulation that inhibits fungus, mold, mildew, and gram-positive and gram-negative bacteria and showing no mold, mildew, or bacterial growth when tested according to ASTM D 3273 and evaluated according to ASTM D 3274 or ASTM G 21.

- D. Antimicrobial Fungicide Treatment: Provide acoustical panels with face and back surfaces coated with antimicrobial treatment consisting of manufacturer's standard formulation with fungicide added to inhibit growth of mold and mildew and showing no mold or mildew growth when tested according to ASTM D 3273 and evaluated according to ASTM D 3274 or ASTM G 21.

2.2 ACOUSTICAL PANELS FOR ACOUSTICAL PANEL CEILING (ACP-1):

- A. Products: Subject to compliance with requirements, provide one of the following:
 - 1. Armstrong World Industries, Inc.; "Ultima," #1910.
 - 2. USG Interiors, Inc.; "Mars ClimaPlus," #86185.
- B. Classification: Provide panels complying with ASTM E 1264 for type, form, and pattern as follows:
 - 1. Type and Form: Type IV, mineral base with membrane-faced overlay; Form 2, water felted; with factory applied latex paint finish.
 - 2. Pattern: E (lightly textured).
- C. Color: White.
- D. LR: Not less than 0.90.
- E. NRC: Not less than 0.70.
- F. CAC: Not less than 35.
- G. Edge/Joint Detail: Square.
- H. Thickness: ¾ -inch.
- I. Modular Size: 24-inches by 24-inches.
- J. Antimicrobial Treatment: Broad spectrum fungicide and bactericide based.

2.3 METAL SUSPENSION SYSTEMS, GENERAL

- A. Metal Suspension System Standard: Provide manufacturer's standard direct-hung metal suspension systems of types, structural classifications, and finishes indicated that comply with applicable requirements in ASTM C 635.
- B. Finishes and Colors, General: Comply with NAAMM's "Metal Finishes Manual for Architectural and Metal Products" for recommendations for applying and designating finishes. Provide manufacturer's standard factory-applied finish for type of system indicated.
 - 1. High-Humidity Finish: Comply with ASTM C 635 requirements for "Coating Classification for Severe Environment Performance" where high-humidity finishes are indicated.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Attachment Devices: Size for five times the design load indicated in ASTM C 635, Table 1, "Direct Hung," unless otherwise indicated. Comply with seismic design requirements.
1. Anchors in Concrete: Anchors of type and material indicated below, with holes or loops for attaching hangers of type indicated and with capability to sustain, without failure, a load equal to five times that imposed by ceiling construction, as determined by testing per ASTM E 488 or ASTM E 1512 as applicable, conducted by a qualified testing and inspecting agency.
 - a. Type: Postinstalled expansion and postinstalled bonded anchors.
 - b. Corrosion Protection: Stainless-steel components complying with ASTM F 593 and ASTM F 594, Group 1 Alloy 304 or 316 for bolts; Alloy 304 or 316 for anchor.
 - c. Corrosion Protection: Components fabricated from nickel-copper-alloy rods complying with ASTM B 164 for UNS No. N04400 alloy.
 2. Power-Actuated Fasteners in Concrete: Fastener system of type suitable for application indicated, fabricated from corrosion-resistant materials, with clips or other accessory devices for attaching hangers of type indicated, and with capability to sustain, without failure, a load equal to 10 times that imposed by ceiling construction, as determined by testing per ASTM E 1190, conducted by a qualified testing and inspecting agency.
- D. Wire Hangers, Braces, and Ties: Provide wires complying with the following requirements:
1. Zinc-Coated, Carbon-Steel Wire: ASTM A 641/A 641M, Class 1 zinc coating, soft temper.
 2. Stainless-Steel Wire: ASTM A 580/A 580M, Type 304, nonmagnetic in high humidity locations.
 3. Nickel-Copper-Alloy Wire: ASTM B 164, nickel-copper-alloy UNS No. N04400.
 4. Size: Select wire diameter so its stress at 3 times hanger design load (ASTM C 635, Table 1, "Direct Hung") will be less than yield stress of wire, but provide not less than 0.135-inch- (3.5-mm-) diameter wire.
- E. Seismic Stabilizer Bars: Manufacturer's standard perimeter stabilizers designed to accommodate seismic forces.
- F. Seismic Struts: Manufacturer's standard compression struts designed to accommodate seismic forces.
- G. Seismic Clips: Manufacturer's standard seismic clips designed and spaced to secure acoustical panels in-place.
- H. Impact Clips: Where indicated, provide manufacturer's standard impact-clip system designed to absorb impact forces against acoustical panels.

2.4 METAL SUSPENSION SYSTEM FOR ACOUSTICAL PANEL CEILING (ACP-1):

- A. Available Products: Subject to compliance with requirements, products that may be incorporated into the Work include, but are not limited to, the following:
1. Armstrong World Industries, Inc.; "Prelude Plus XL 15/16" Exposed Tee System."
 2. USG Interiors, Inc.; "Donn DX."

- B. Wide-Face, Capped, Double-Web, Steel Suspension System: Main and cross runners roll formed from cold-rolled steel sheet, prepainted, electrolytically zinc coated, or hot-dip galvanized according to ASTM A 653/A 653M, not less than G30 (Z90) coating designation, with prefinished 15/16-inch- (24-mm-) wide metal caps on flanges.
1. Structural Classification: Intermediate-duty system.
 2. End Condition of Cross Runners: Override (stepped) or butt-edge type.
 3. Face Design: Flat, flush.
 4. Cap Material: Steel cold-rolled sheet.
 5. Cap Finish: White

2.5 METAL EDGE MOLDINGS AND TRIM

- A. Roll-Formed, Sheet-Metal Edge Moldings and Trim: Type and profile indicated or, if not indicated, manufacturer's standard moldings for edges and penetrations that comply with seismic design requirements; formed from sheet metal of same material, finish, and color as that used for exposed flanges of suspension system runners.
1. Provide manufacturer's standard edge moldings that fit acoustical panel edge details and suspension systems indicated and that match width and configuration of exposed runners, unless otherwise indicated.
 2. For lay-in panels with reveal edge details, provide stepped edge molding that forms reveal of same depth and width as that formed between edge of panel and flange at exposed suspension member.
 3. For circular penetrations of ceiling, provide edge moldings fabricated to diameter required to fit penetration exactly.

2.6 ACOUSTICAL SEALANT

- A. Available Products: Subject to compliance with requirements, products that may be incorporated into the Work include, but are not limited to, the following:
1. Acoustical Sealant for Exposed and Concealed Joints:
 - a. Pecora Corporation; AC-20 FTR Acoustical and Insulation Sealant.
 - b. USG Corporation; SHEETROCK Acoustical Sealant.
 2. Acoustical Sealant for Concealed Joints:
 - a. OSI Sealants, Inc.; Pro-Series SC-175 Rubber Base Sound Sealant.
 - b. Pecora Corporation; BA-98.
 - c. Tremco, Inc.; Tremco Acoustical Sealant.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, including structural framing to which acoustical panel ceilings attach or abut, with Installer present, for compliance with requirements specified in this and other Sections that affect ceiling installation and anchorage and with requirements for installation tolerances and other conditions affecting performance of acoustical panel ceilings.
1. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Measure each ceiling area and establish layout of acoustical panels to balance border widths at opposite edges of each ceiling. Avoid using less-than-half-width panels at borders, and comply with layout shown on reflected ceiling plans.

3.3 INSTALLATION

- A. General: Install acoustical panel ceilings to comply with ASTM C 636 and seismic design requirements indicated, and per manufacturer's written instructions.
- B. Suspend ceiling hangers from building's structural members and as follows:
 - 1. Install hangers plumb and free from contact with insulation or other objects within ceiling plenum that are not part of supporting structure or of ceiling suspension system.
 - 2. Splay hangers only where required to miss obstructions; offset resulting horizontal forces by bracing, countersplaying, or other equally effective means.
 - 3. Splay hangers only where required to miss obstructions; offset resulting horizontal forces by bracing, countersplaying, or other equally effective means.
 - 4. Where width of ducts and other construction within ceiling plenum produces hanger spacings that interfere with location of hangers at spacings required to support standard suspension system members, install supplemental suspension members and hangers in form of trapezes or equivalent devices.
 - 5. Secure wire hangers to ceiling suspension members and to supports above with a minimum of three tight turns. Connect hangers directly either to structures or to inserts, eye screws, or other devices that are secure and appropriate for substrate and that will not deteriorate or otherwise fail due to age, corrosion, or elevated temperatures.
 - 6. Secure flat, angle, channel, and rod hangers to structure, including intermediate framing members, by attaching to inserts, eye screws, or other devices that are secure and appropriate for both structure to which hangers are attached and type of hanger involved. Install hangers in a manner that will not cause them to deteriorate or fail due to age, corrosion, or elevated temperatures.
 - 7. Do not support ceilings directly from permanent metal forms or floor deck. Fasten hangers to cast-in-place hanger inserts, postinstalled mechanical or adhesive anchors, or power-actuated fasteners that extend through forms into concrete.
 - 8. When steel framing does not permit installation of hanger wires at spacing required, install carrying channels or other supplemental support for attachment of hanger wires.
 - 9. Do not attach hangers to steel deck tabs.
 - 10. Do not attach hangers to steel roof deck. Attach hangers to structural members.
 - 11. Space hangers not more than 48 inches (1200 mm) o.c. along each member supported directly from hangers, unless otherwise indicated; provide hangers not more than 8 inches (200 mm) from ends of each member.
 - 12. Size supplemental suspension members and hangers to support ceiling loads within performance limits established by referenced standards and publications.
- C. Secure bracing wires to ceiling suspension members and to supports with a minimum of four tight turns. Suspend bracing from building's structural members as required for hangers, without attaching to permanent metal forms, steel deck, or steel deck tabs. Fasten bracing wires into concrete with cast-in-place or postinstalled anchors.
- D. Install edge moldings and trim of type indicated at perimeter of acoustical ceiling area and where necessary to conceal edges of acoustical panels.
 - 1. Where indicated, apply acoustical sealant in a continuous ribbon concealed on back of vertical legs of moldings before they are installed.

2. Screw attach moldings to substrate at intervals not more than 16 inches (400 mm) o.c. and not more than 3 inches (75 mm) from ends, leveling with ceiling suspension system to a tolerance of 1/8 inch in 12 feet (3.2 mm in 3.6 m). Miter corners accurately and connect securely.
 3. Do not use exposed fasteners, including pop rivets, on moldings and trim.
- E. Install suspension system runners so they are square and securely interlocked with one another. Remove and replace dented, bent, or kinked members.
- F. Install acoustical panels with undamaged edges and fit accurately into suspension system runners and edge moldings. Scribe and cut panels at borders and penetrations to provide a neat, precise fit.
1. Arrange directionally patterned acoustical panels as follows:
 - a. As indicated on reflected ceiling plans.
 2. For square-edged panels, install panels with edges fully hidden from view by flanges of suspension system runners and moldings.
 3. For reveal-edged panels on suspension system runners, install panels with bottom of reveal in firm contact with top surface of runner flanges.
 4. For reveal-edged panels on suspension system members with box-shaped flanges, install panels with reveal surfaces in firm contact with suspension system surfaces and panel faces flush with bottom face of runners.
 5. Paint cut edges of panel remaining exposed after installation; match color of exposed panel surfaces using coating recommended in writing for this purpose by acoustical panel manufacturer.
 6. Install hold-down clips in areas indicated, in areas required by authorities having jurisdiction, and for fire-resistance ratings; space as recommended by panel manufacturer's written instructions, unless otherwise indicated.
 7. Install clean-room gasket system in areas indicated, sealing each panel and fixture as recommended by panel manufacturer's written instructions.
 8. Protect lighting fixtures and air ducts to comply with requirements indicated for fire-resistance-rated assembly.

3.4 FIELD QUALITY CONTROL

- A. Special Inspections: Owner will engage a qualified special inspector to perform the following special inspections and prepare reports:
1. Suspended ceiling system.
 2. Hangers, anchors and fasteners.
- B. Testing Agency: Owner will engage a qualified testing agency to perform tests and inspections and prepare test reports.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Tests and Inspections: Testing and inspecting of completed installations of acoustical panel ceiling hangers and anchors and fasteners shall take place in successive stages, in areas of extent and using methods as follows. Do not proceed with installations of acoustical panel ceiling hangers for the next area until test results for previously completed installations of acoustical panel ceiling hangers show compliance with requirements.
1. Extent of Each Test Area: When installation of ceiling suspension systems on each floor has reached 20 percent completion but no panels have been installed.
 - a. Within each test area, testing agency will select 1 of every 10 power-actuated fasteners and postinstalled anchors used to attach hangers to concrete and will test them for 200 lbf (890 N) of tension; it will also select one of every 2 postinstalled anchors used to attach bracing wires to concrete and will test them for 440 lbf (1957 N) of tension.
 - b. When testing discovers fasteners and anchors that do not comply with requirements, testing agency will test those anchors not previously tested until 20 pass consecutively and then will resume initial testing frequency.
- D. Remove and replace acoustical panel ceiling hangers and anchors and fasteners that do not pass tests and inspections and retest as specified above.

3.5 CLEANING

- A. Clean exposed surfaces of acoustical panel ceilings, including trim, edge moldings, and suspension system members. Comply with manufacturer's written instructions for cleaning and touchup of minor finish damage. Remove and replace ceiling components that cannot be successfully cleaned and repaired to permanently eliminate evidence of damage.

END OF SECTION 095113

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. This Section includes the following:
 - 1. Resilient wall base.
 - 2. Resilient flooring accessories.
- B. Related Sections include the following:
 - 1. Division 09 Section "Resilient Flooring."

1.3 SUBMITTALS:

- A. Product Data: For each type of product specified.
- B. Samples for Initial Selection: Manufacturer's standard sample sets consisting of sections of units showing the full range of colors and patterns available for each type of product indicated.
- C. Samples for Verification: In manufacturer's standard sizes, but not less than 12 inches long, of each product color and pattern specified.
- D. Product Certificates: Signed by manufacturers of resilient wall base and accessories certifying that each product furnished complies with requirements.

1.4 QUALITY ASSURANCE:

- A. Installer Qualifications: Engage an experienced installer to perform work of this Section who has specialized in installing resilient products similar to those required for this Project and with a record of successful in-service performance.
- B. Source Limitations: Obtain each type and color of product specified from one source with resources to provide products of consistent quality in appearance and physical properties without delaying the Work.

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Fire-Test-Response Characteristics: Provide products with the following fire-test-response characteristics as determined by testing identical products per test method indicated below by a testing and inspecting agency acceptable to authorities having jurisdiction.
 - 1. Critical Radiant Flux: 0.45 W/sq. cm or greater when tested per ASTM E 648.
 - 2. Smoke Density: Maximum specific optical density of 450 or less when tested per ASTM E 662.

1.5 DELIVERY, STORAGE, AND HANDLING:

- A. Deliver products to Project site in manufacturer's original, unopened cartons and containers, each bearing names of product and manufacturer, Project identification, and shipping and handling instructions.
- B. Store products in dry spaces protected from the weather, with ambient temperatures maintained between 50 and 90 deg F.
- C. Move products into spaces where they will be installed at least 48 hours before installation, unless longer conditioning period is recommended in writing by manufacturer.

1.6 PROJECT CONDITIONS:

- A. Maintain a temperature of not less than 70 deg F or more than 95 deg F in spaces to receive resilient products for at least 48 hours before installation, during installation, and for at least 48 hours after installation, unless manufacturer's written recommendations specify longer time periods. After postinstallation period, maintain a temperature of not less than 55 deg F or more than 95 deg F.
- B. Do not install products until they are at the same temperature as the space where they are to be installed.
- C. For resilient products installed on traffic surfaces, close spaces to traffic during installation and for time period after installation recommended in writing by manufacturer.
- D. Coordinate resilient product installation with other construction to minimize possibility of damage and soiling during remainder of construction period. Install resilient products after other finishing operations, including painting, have been completed.

1.7 EXTRA MATERIALS:

- A. Furnish extra materials described below that match products installed, are packaged with protective covering for storage, and are identified with labels describing contents.
 - 1. Furnish not less than 16 linear feet for each different type, color, pattern, and size of resilient product installed.
 - 2. Deliver extra materials to Owner.

PART 2 - PRODUCTS

2.1 MANUFACTURERS:

- A. Products: Subject to compliance with requirements, provide one of the products indicated for each designation in the Resilient Wall Base and Accessory Schedule at the end of Part 3.

2.2 RESILIENT WALL BASE:

- A. Rubber Wall Base: Products complying with FS SS-W-40, Type I and with requirements specified in the Resilient Wall Base and Accessory Schedule.

2.3 RESILIENT ACCESSORIES:

- A. Rubber Accessories: Products complying with requirements specified in the Resilient Wall Base and Accessory Schedule.
- B. Vinyl Accessories: Products complying with requirements specified in the Resilient Wall Base and Accessory Schedule.

2.4 INSTALLATION ACCESSORIES:

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland-cement-based formulation provided or approved by resilient product manufacturer for applications indicated.
- B. Adhesives: Water-resistant type recommended by manufacturer to suit resilient products and substrate conditions indicated.

PART 3 - EXECUTION

3.1 EXAMINATION:

- A. Examine substrates, areas, and conditions where installation of resilient products will occur, with Installer present, for compliance with manufacturer's requirements, including those for maximum moisture content. Verify that substrates and conditions are satisfactory for resilient product installation and comply with requirements specified. Do not proceed with installation until unsatisfactory conditions have been corrected.

3.2 PREPARATION:

- A. General: Comply with manufacturer's written installation instructions for preparing substrates indicated to receive resilient products.
- B. Use trowelable leveling and patching compounds, according to manufacturer's written instructions, to fill cracks, holes, and depressions in substrates.

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Remove coatings, including curing compounds, and other substances that are incompatible with adhesives and that contain soap, wax, oil, or silicone, using mechanical methods recommended by manufacturer. Do not use solvents.
- D. Broom and vacuum clean substrates to be covered immediately before installing resilient products. After cleaning, examine substrates for moisture, alkaline salts, carbonation, or dust. Do not proceed with installation until unsatisfactory conditions have been corrected.

3.3 INSTALLATION:

- A. General: Install resilient products according to manufacturer's written installation instructions.
- B. Apply resilient wall base to walls, columns, pilasters, casework and cabinets in toe spaces, and other permanent fixtures in rooms and areas where base is required.
 - 1. Install wall base in lengths as long as practicable without gaps at seams and with tops of adjacent pieces aligned.
 - 2. Tightly adhere wall base to substrate throughout length of each piece, with base in continuous contact with horizontal and vertical substrates.
 - 3. Do not stretch base during installation.
 - 4. On masonry surfaces or other similar irregular substrates, fill voids along top edge of resilient wall base with manufacturer's recommended adhesive filler material.
 - 5. Install premolded outside and inside corners before installing straight pieces.
- C. Place resilient products so they are butted to adjacent materials and bond to substrates with adhesive. Install reducer strips at edges of flooring that would otherwise be exposed.

3.4 CLEANING AND PROTECTING:

- A. Perform the following operations immediately after installing resilient products:
 - 1. Remove adhesive and other surface blemishes using cleaner recommended by resilient product manufacturers.
 - 2. Sweep or vacuum horizontal surfaces thoroughly.
 - 3. Do not wash resilient products until after time period recommended by resilient product manufacturer.
 - 4. Damp-mop or sponge resilient products to remove marks and soil.
- B. Apply resilient products to stairs as indicated and according to manufacturer's written installation instructions.

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Protect resilient products against mars, marks, indentations, and other damage from construction operations and placement of equipment and fixtures during the remainder of construction period. Use protection methods indicated or recommended in writing by resilient product manufacturer.
1. Apply protective floor polish to vinyl resilient products installed on floors and stairs that are free from soil, visible adhesive, and surface blemishes, if recommended by manufacturer.
 - a. Use commercially available product acceptable to resilient product manufacturer.
 - b. Coordinate selection of floor polish with Owner's maintenance service.
 2. Cover resilient products installed on floors and stairs with undyed, untreated building paper until inspection for Substantial Completion.
- D. Clean resilient products not more than 4 days before dates scheduled for inspections intended to establish date of Substantial Completion in each area of Project. Clean products according to manufacturer's written recommendations.
1. Before cleaning, strip protective floor polish that was applied to vinyl products on floors and stairs after completing installation only if required to restore polish finish and if recommended by resilient product manufacturer.
 2. After cleaning, reapply polish on vinyl products on floors and stairs to restore protective floor finish according to resilient product manufacturer's written recommendations. Coordinate with Owner's maintenance program.

3.5 RESILIENT WALL BASE AND ACCESSORY SCHEDULE:

- A. Basis-of-Design Product: Subject to compliance with requirements, provide **Traditional Wall Base; Johnsonite, Inc.** or a comparable product by one of the following:
1. Roppe Corporation
 2. Nora Rubber Flooring, Inc.
 3. Color and Pattern:
 - a. **WB-1:**
 - 1) Color: #20, "Charcoal;" Johnsonite.
 - 2) Height: 6 inches, unless otherwise noted.
 - 3) Location: Men' locker room.
 - b. **WB-2:**
 - 1) Color: #283, "Toast;" Johnsonite.
 - 2) Height: 6 inches, unless otherwise noted.
 - 3) Location: Women's locker room.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

4. Style: Cove with top-set toe.
5. Minimum Thickness: 1/8 inch.
6. Lengths: Coils in lengths standard with manufacturer, but not less than 96 feet.
7. Outside Corners: Field fabricated.
8. Inside Corners: Field fabricated.
9. Ends: Field fabricated.
10. Surface: Smooth.

B. Vinyl Accessory Molding: Where flooring materials change, provide vinyl accessory moldings complying with the following:

1. Products: As follows:
 - a. Adapter [TS-1]: Model No. **CTA-XX-KC**, 3/8" (9.53mm) carpet to 1/8"(6.35mm) resilient material to floor. 3' pieces; Johnsonite or equivalent as approved by the Architect.
 - b. Adapter [TS-2]: Model No. **CTA-XX-N**, 1/8"(6.35mm) resilient material to 1/8"(6.35mm) resilient material. 3' pieces; Johnsonite or equivalent as approved by the Architect.
2. Color: Wall base color in room.
3. Profile and Dimensions: As specified by product designation indicated above.

END OF SECTION 096513

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Vinyl composition floor tile.
- B. Related Sections:
 - 1. Division 09 Section "Resilient Base and Accessories" for resilient base, reducer strips, and other accessories installed with resilient floor coverings.

1.3 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Shop Drawings: For each type of floor tile. Include floor tile layouts, edges, columns, doorways, enclosing partitions, built-in furniture, cabinets, and cutouts.
 - 1. Show details of special patterns.
- C. Samples for Initial Selection: For each type of floor tile indicated.
- D. Samples for Verification: Full-size units of each color and pattern of floor tile required.
- E. Product Schedule: For floor tile. Use same designations indicated on Drawings.
- F. Qualification Data: For qualified Installer.
- G. Maintenance Data: For each type of floor tile to include in maintenance manuals.

1.4 QUALITY ASSURANCE

- A. Installer Qualifications: A qualified installer who employs workers for this Project who are competent in techniques required by manufacturer for floor tile installation indicated.
- B. Mockups: Build mockups to verify selections made under sample submittals and to demonstrate aesthetic effects and set quality standards for materials and execution.
 - 1. Build mockups for floor tile including resilient base and accessories.
 - a. Size: Minimum 100 sq. ft. (9.3 sq. m) for each type, color, and pattern in locations directed by Architect.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store floor tile and installation materials in dry spaces protected from the weather, with ambient temperatures maintained within range recommended by manufacturer, but not less than 50 deg F (10 deg C) or more than 90 deg F (32 deg C). Store floor tiles on flat surfaces.

1.6 PROJECT CONDITIONS

- A. Maintain ambient temperatures within range recommended by manufacturer, but not less than 70 deg F (21 deg C) or more than 95 deg F (35 deg C), in spaces to receive floor tile during the following time periods:
 - 1. 48 hours before installation.
 - 2. During installation.
 - 3. 48 hours after installation.
- B. Until Substantial Completion, maintain ambient temperatures within range recommended by manufacturer, but not less than 55 deg F (13 deg C) or more than 95 deg F (35 deg C).
- C. Close spaces to traffic during floor tile installation.
- D. Close spaces to traffic for 48 hours after floor tile installation.
- E. Install floor tile after other finishing operations, including painting, have been completed.

1.7 EXTRA MATERIALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Floor Tile: Furnish 1 box of each type, color, and pattern of floor tile installed.

PART 2 - PRODUCTS

2.1 VINYL COMPOSITION FLOOR TILE:

- A. Products: Subject to compliance with requirements, available products that may be incorporated into the Work include, but are not limited to, the following:
 - 1. Mannington Commercial Progressions.
- B. Tile Standard: ASTM F 1066, Class 2, through-pattern tile.
- C. Wearing Surface: Smooth.
- D. Thickness: 0.125 inch (3.2 mm).
- E. Size: 12 by 12 inches (305 by 305 mm).
- F. Colors and Patterns:
 - 1. **VCT-1:** Mannington Commercial Progressions 55135 Seaspray Men's Locker Room Checkerboard pattern with VCT-2.
 - 2. **VCT-2:** Mannington Commercial Progressions 55110 Colony Men's Locker Room, checkerboard pattern with VCT-1.

3. **VCT-3:** Mannington Commercial Progressions 55507 Almond Buff Women's Locker Room, Checkerboard pattern with VCT-4.
4. **VCT-4:** Mannington Commercial Progressions 55123 Wheat Women's Locker Room, Checkerboard pattern with VCT-3.

2.2 INSTALLATION MATERIALS

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland cement based or blended hydraulic-cement-based formulation provided or approved by manufacturer for applications indicated.
- B. Adhesives: Water-resistant type recommended by manufacturer to suit floor tile and substrate conditions indicated.
- C. Floor Polish: Provide protective liquid floor polish products as recommended by manufacturer.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, with Installer present, for compliance with requirements for maximum moisture content and other conditions affecting performance of the Work.
- B. Verify that finishes of substrates comply with tolerances and other requirements specified in other Sections and that substrates are free of cracks, ridges, depressions, scale, and foreign deposits that might interfere with adhesion of floor tile.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Prepare substrates according to manufacturer's written instructions to ensure adhesion of resilient products.
- B. Concrete Substrates: Prepare according to ASTM F 710.
 1. Verify that substrates are dry and free of curing compounds, sealers, and hardeners.
 2. Remove substrate coatings and other substances that are incompatible with adhesives and that contain soap, wax, oil, or silicone, using mechanical methods recommended by manufacturer. Do not use solvents.
 3. Alkalinity and Adhesion Testing: Perform tests recommended by manufacturer. Proceed with installation only after substrates pass testing.
 4. Moisture Testing: Perform tests recommended by manufacturer and as follows. Proceed with installation only after substrates pass testing.
 - a. Perform anhydrous calcium chloride test, ASTM F 1869. Proceed with installation only after substrates have maximum moisture-vapor-emission rate of 3 lb of water/1000 sq. ft. (1.36 kg of water/92.9 sq. m) in 24 hours and;
 - b. Perform relative humidity test using in situ probes, ASTM F 2170. Proceed with installation only after substrates have a maximum 75% relative humidity level measurement.
- C. Fill cracks, holes, and depressions in substrates with trowelable leveling and patching compound and remove bumps and ridges to produce a uniform and smooth substrate.

- D. Do not install floor tiles until they are same temperature as space where they are to be installed.
 - 1. Move resilient products and installation materials into spaces where they will be installed at least 48 hours in advance of installation.
- E. Sweep and vacuum clean substrates to be covered by resilient products immediately before installation.

3.3 FLOOR TILE INSTALLATION

- A. Comply with manufacturer's written instructions for installing floor tile.
- B. Lay out floor tiles from center marks established with principal walls, discounting minor offsets, so tiles at opposite edges of room are of equal width. Adjust as necessary to avoid using cut widths that equal less than one-half tile at perimeter.
 - 1. Lay tiles square with room axis.
- C. Match floor tiles for color and pattern by selecting tiles from cartons in the same sequence as manufactured and packaged, if so numbered. Discard broken, cracked, chipped, or deformed tiles.
 - 1. Lay tiles in pattern of colors and sizes indicated.
- D. Scribe, cut, and fit floor tiles to butt neatly and tightly to vertical surfaces and permanent fixtures including built-in furniture, cabinets, pipes, outlets, and door frames.
- E. Extend floor tiles into toe spaces, door reveals, closets, and similar openings. Extend floor tiles to center of door openings.
- F. Maintain reference markers, holes, and openings that are in place or marked for future cutting by repeating on floor tiles as marked on substrates. Use chalk or other nonpermanent, nonstaining marking device.
- G. Install floor tiles on covers for telephone and electrical ducts, building expansion-joint covers, and similar items in finished floor areas. Maintain overall continuity of color and pattern between pieces of tile installed on covers and adjoining tiles. Tightly adhere tile edges to substrates that abut covers and to cover perimeters.
- H. Adhere floor tiles to flooring substrates using a full spread of adhesive applied to substrate to produce a completed installation without open cracks, voids, raising and puckering at joints, telegraphing of adhesive spreader marks, and other surface imperfections.

3.4 CLEANING AND PROTECTION

- A. Comply with manufacturer's written instructions for cleaning and protection of floor tile.
- B. Perform the following operations immediately after completing floor tile installation:
 - 1. Remove adhesive and other blemishes from exposed surfaces.
 - 2. Sweep and vacuum surfaces thoroughly.
 - 3. Damp-mop surfaces to remove marks and soil.
- C. Protect floor tile products from mars, marks, indentations, and other damage from construction operations and placement of equipment and fixtures during remainder of construction period.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- D. Floor Polish: Remove soil, visible adhesive, and surface blemishes from floor tile surfaces before applying liquid floor polish.
 - 1. Apply three coats.
- E. Cover floor tile until Substantial Completion.

END OF SECTION 096519

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY:

- A. This Section includes surface preparation and field painting of the following:
1. Exposed interior items and surfaces.
 2. Surface preparation, priming, and finish coats specified in this Section are in addition to shop priming and surface treatment specified in other Sections.
- B. Paint exposed surfaces, except where the paint schedules indicate that a surface or material is not to be painted or is to remain natural. If the paint schedules do not specifically mention an item or a surface, paint the item or surface the same as similar adjacent materials or surfaces whether or not schedules indicate colors. If the schedules do not indicate color or finish, the Architect will select from standard colors and finishes available.
1. Painting includes field painting of exposed bare and covered pipes and ducts, hangers, exposed steel and iron work, and primed metal surfaces of mechanical and electrical equipment.
- C. Do not paint prefinished items, concealed surfaces, finished metal surfaces, operating parts, and labels.
1. Prefinished items include the following factory-finished components:
 - a. Metal lockers.
 - b. Elevator entrance doors and frames.
 - c. Elevator equipment.
 - d. Finished mechanical and electrical equipment.
 - e. Light fixtures.
 - f. Distribution cabinets.
 - g. Switchgear.
 - h. Panelboards.
 - i. Motors and mechanical equipment.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

SECTION 105113 – WELDED METAL LOCKERS (PERSONAL STORAGE LOCKERS WITH BUILT-IN BENCH DRAWER)

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

This Section includes the following:

1. Installation of Personal Storage Lockers with built-in bench drawers, purchased by Owner.
 - a. All lockers include electrical functionality as required.
2. All Personal Storage Lockers, Personal Storage with built-in bench drawers, and Personal Storage Lockers with built-in external access drawers must include environmental ventilation functionality as required.
 - a. Attachment to building HVAC system and balancing air flow through locker system. Manufacturer will provide guidance only upon request.

Related Sections:

Sections in Division 9 – Finishes, relating to finish floor and base materials

1.3 REFERENCES

American National Standards Institute (ANSI) Standards:

Applicable standards for fasteners used for assembly.

American Society for Testing and Materials (ASTM) Standards:

Applicable standards for steel sheet materials used for fabrication

Applicable standards for the testing of electrostatically applied Powder Coat Paint

American Institute Of Steel Construction (AISC) Standards:

Applicable standards for steel materials used for fabrication.

1.4 DESCRIPTION

General: Welded Metal Lockers only with end-user reconfigurable interior. Specialized lances to provide the flexibility of on-site, end-user reconfiguration/addition of internal components anytime, anywhere, now or in the future.

Finishes:

Fabricated Metal Components and Assemblies: All components to be painted with an electrostatically applied Powder Coat paint that can meet or exceed test requirements set out by ASTM standard D3451-06 Standard Guide for Testing Coating Powders and Powder Coatings.

Sizes:

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

Personal Storage Lockers with built-in bench drawers: height to be [84] inches or [2133.6] millimeters respectively; Built-in bench drawer height is [18] inches or [457.2] millimeters and depth is [36] inches or [914.4] millimeters.

1.5 PERFORMANCE REQUIREMENTS

Design Requirements:

Limit overall width not to exceed specified nominal width; locker width designed for zero growth.

Seismic Performance: Provide Welded Metal Lockers capable of withstanding the effects of earthquake movement when required by applicable building codes.

ADA Requirements: Personal Storage Lockers with nominal height of [72] inches or [1828.8] millimeters meet ADA requirements.

1.6 SUBMITTALS

Product Data: Submit manufacturer's product literature and installation instructions for each type of welded metal locker required. Include data substantiating that products to be furnished comply with requirements of the contract documents.

Shop Drawings: Show fabrication, assembly, and installation details, including descriptions of procedures and diagrams. Show complete locker installation layout, including quantities, locations and types of accessory units required. Include notations and descriptions of all installation items and components.

Show installation details at non-standard conditions, if any.

Provide layout, dimensions, and identification of each unit, corresponding to sequence of installation procedures.

Provide installation schedule and procedures to ensure proper installation.

Samples: Provide minimum [3] inches or [76] millimeters square example of each color and texture on actual substrate for each component to remain exposed after installation.

Selection Samples: For initial selection of colors and textures, submit manufacturer's color charts, consisting of actual product pieces, showing full range of colors and textures available.

Warranty: Submit draft copy of proposed warranty for review by the Architect.

Maintenance Data: Provide written documentation of the manufacturer's statement, claiming the maintenance free nature of the product.

Reference List: Provide a list of recently installed welded metal lockers to be visited by owner, architect, and contractor. Intent of list is to aid in verifying the suitability of manufacturer's products and comparison with materials and product specified in this section. Include contact name, address, and phone numbers.

1.7 QUALITY ASSURANCE

Manufacturer Qualifications: Engage an experienced manufacturer who is ISO 9001:2008 certified for the design, production, installation and service of welded metal lockers. Furnish certification attesting ISO 9001:2008 quality system registration.

Installer Qualifications: Engage an experienced installer who is the manufacturer's authorized representative for the specified products for installing welded metal lockers.

Minimum Qualifications: 1-year experience installing welded metal lockers of comparable size and complexity to specified project requirements.

1.8 DELIVERY, STORAGE AND HANDLING

Follow manufacturer's instructions and recommendations for delivery, storage and handling requirements.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

1.9 PROJECT CONDITIONS

Field Measurements: Verify quantities of welded metal locker units before fabrication. Indicate verified measurements on shop drawings. Coordinate fabrication and delivery to ensure no delay in progress of the work.

Established Dimensions: Where field measurements cannot be made without delaying the Work, establish dimensions and proceed with fabricating welded metal lockers units without field measurements. Coordinate construction to ensure actual dimensions correspond to established dimensions.

1.10 SEQUENCING AND SCHEDULING

Sequence welded metal lockers [with other work] to minimize possibility of damage and soiling, during remainder of construction period.

Schedule installation of specified welded metal lockers after finishing operations, including painting, have been completed.

Provide components, which must be built in at a time, which causes no delays in the general progress of the work.

Pre-installation Conference: Schedule and conduct conference on project site to review methods and procedures for installing welded Metal Lockers including, but not limited to, the following:

Recommended attendees include:

1. Owner's Representative.
2. Contractor.
3. Architect.
4. Manufacturer's representative.
5. Subcontractors or installers whose work may affect, or be affected by, the work of this section.

1.11 WARRANTY

Provide a written warranty, executed by Contractor, Installer, and Manufacturer, agreeing to repair or replace units, which fail in materials or workmanship within the established warranty period. This warranty shall be in addition to, and not a limitation of, other rights the Owner may have under General Condition's provisions of the Contract Documents.

Limited Lifetime Warranty: Subject to the terms in the written warranty, warrant the original purchaser exclusively that the locker frames manufactured by it will be free from defects in materials and workmanship for the lifetime of the locker.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

General: **FreeStyle™** Personal Storage with built-in bench drawers, based upon welded metal lockers manufactured by Spacesaver Corporation, 1450 Janesville Avenue, Fort Atkinson, Wisconsin 53538-2798. Telephone: 800-492-3434.

2.2 BASIC MATERIALS

General: Provide materials and quality of workmanship, which meets or exceeds established industry standards for products specified. Use furniture grade sheet metal, solid hardwood benches and fasteners for component fabrication unless indicated otherwise. Material thicknesses/gauges are manufacturer's option unless indicated otherwise.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

2.3 LOCKER TYPES

Personal Storage Lockers. Provide personal storage lockers with built-in bench drawers by Spacesaver Corporation.

1. All locker types (except Multi-Tier) to be equipped with environmental ventilation functionality for applications where Mechanical Air Extraction is desired to remove unpleasant odors from the locker.
2. All locker types (except Multi-Tier) to be equipped with the functionality of attaching a modular electrical system as required.
3. All locker types to be equipped with the functionality of attaching a continuous sloped top.

2.4 MANUFACTURED COMPONENTS

Welded Frame:

1. The welded frame must consist of top, bottom, back, and sides constructed of a minimum of 18-gauge or [1.214] millimeters steel. All frame components shall be joined using resistance welding. Riveting of structural members will not be permitted.
2. Horizontal front flanges will be a minimum of [2] inches or [50.8] millimeters. Vertical front flanges will be a minimum of [1] inch or [25.4] millimeters. Horizontal and vertical flanges will overlap and be secured with a minimum two (2) resistance welds per corner.
3. Corner gussets shall be MIG and spot welded in each of the four front corners of the locker for increased stiffness and rigidity.
4. Provide side panel lances evenly spaced on [3] inch or [76.2] millimeter centers. Lances to provide the flexibility of on-site, end-user reconfiguration/addition of internal components anytime, anywhere, now or in the future.
5. Bench Housing for built-in bench drawer
 - a. Welded frame construction shall consist of top, bottom, and side components joined by using resistance welding. Riveting of bench housing structural members will not be permitted.
 - b. Corner gussets shall be welded in the two (2) front bottom corners of the bench housing for increased stiffness and rigidity.
 - c. Horizontal front flanges will be a minimum of [1] inch or [25.4] millimeters
 - d. Vertical front flanges will be a minimum of [1] inch or [25.4] millimeters
 - e. Horizontal and Vertical front flanges will overlap and shall be secured with minimum of one (1) resistance weld per corner.
 - f. Side panels – Lances symmetric and evenly spaced to provide optimum component locations (standard based on [3] inch or [76.2] millimeter on center vertical placement to match mating locker lance design).
 - g. Return flanges on housing to securely fasten housing to welded frame of locker.
 - h. Base of bench housing shall include four (4) 3/8"-16 UNC threaded weld-nuts and corresponding leveling feet.
 - i. Top of bench housing shall include hole pattern for mating bench seat.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- j. Sides of bench housing shall include mounting holes in the event lockers are ganged together.
- 6. Lockers with built-in bench drawer and built-in external access drawer shall have intermediate base shelf with interlocking mechanism for securing drawer when locker door is closed.
- 7. Provide four (4) [0.875] inch or [22.23] millimeter diameter electrical knock-outs per locker, two (2) located on top of the locker in both right and left rear corners, and two (2) located in the back of locker centered at a distance no greater than [24] inches or [609.6] millimeters from the top and bottom. Knock-outs allow end-user flexibility of adding electrical capability to lockers.
- 8. Provide a minimum of four (4) duplex receptacle electrical knock-outs per locker; to be used with a UL listed manufactured electrical wiring system as required. This manufactured electrical wiring system is a simple, unique, flexible, and cost effective method of providing electrical capability to the lockers. This electrical system can be added in the future.
 - a. Top of locker shall have electrical duplex receptacle knock-outs located on both right and left side of locker.
 - b. Back panel of locker shall have a minimum of two (2) duplex electrical knock-outs.
 - c. Back of locker shall have electrical duplex receptacle knock-outs located on both right and left side of locker and no farther than [24] inches or [609.6] millimeters from the top of the locker.
- 9. Provide ventilation holes in top of locker to allow mechanically extracted air to be pulled up through the locker system as required. Ventilation shall be controlled by eight (8) evenly spaced [0.625] inch or [15.875] millimeter diameter holes. Proper ventilation system ensures unpleasant odors are removed from locker system.
- 10. Lockers shall be prepared with mounting holes for use with the continuous sloped top system.
- 11. Lockers shall be prepared with mounting holes for attaching necessary trim components
- 12. Locker shall be prepared with mounting holes for ganging lockers back-to-back or side-by-side
- 13. Base of lockers shall include four (4) 3/8"-16 UNC threaded weld-nuts and corresponding leveling feet.
- 14. Base shelf for lockers with built-in external access drawers and bench drawers shall have holes to accommodate double-door lock rod and door stop bracket. (only on [24] inch or [609.6] millimeters wide and larger)
- 15. End Panels: End Panels with no exposed fasteners shall be provided on the end of each locker run; thus providing a clean and aesthetically pleasing appearance.
- 16. All locker sizes and types to be specified by architect.
 - a. Width:
 - 1) Personal Storage Locker with built-in bench drawer or external access drawer. [24] inches or [609.6] millimeters

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- b. Height:
 - 1) Personal Storage Locker with built in bench drawer or external access drawer: [84] inches or [2133.6] millimeters
- c. Depth:
 - 1) All lockers [24] inches or [609.6] millimeters
 - 2) Bench drawers: [36] inches or [914.4] millimeters
 - c) Bench seat depth [9.5] inches or [241.3] millimeters
 - c) Leading edge of bench seat to extend [1.125] inches or [28.6] millimeters from front of bench drawer

Ventilation:

- 17. Provide ventilation holes in top of locker to allow mechanically extracted air to be pulled up through the locker system as required. Ventilation shall be controlled by eight (8) evenly spaced [0.625] inch or [15.875] millimeter diameter holes. Proper ventilation system ensures odors are removed from locker system.
- 18. Provide an adjustable air baffle for system balancing when mechanical air extraction is used. Upon balancing system, air baffle shall be secured with a fastener to maintain ventilation setting.
- 19. Provide louvered air vents in bottom of the main locker door/s to allow mechanically extracted air to be pulled up through the locker system.
- 20. Provide louvered air vents in drawer front when built-in bench drawer or built-in external access drawer models are required.
- 21. Minimum [0.500] inch or [12.7] millimeter gap between back of shelving components and back of locker to provide uninterrupted air flow up the rear of the locker system.
- 22. Minimum [2.00] inches or [558.8] millimeter gap between front of shelving and locker door to provide uninterrupted air flow up the front of the locker system.
- 23. Multi-Tier ventilation is provided thru door panels
- 24. Upon request manufacturer shall provide HVAC tech data to serve as a guideline for the General Contractor and HVAC Contactor. It is the General Contractor and/or HVAC contractors' responsibility to establish/balance air flow through locker system according to building HVAC constraints.

Electrical

- 25. Shall provide four (4) electrical knock-outs per locker as described in section 2.4-A item 7. This feature provides the end-user the opportunity for hard wire electrical connection points for each locker. End-user or General Contractor is responsible for final electrical installation.
- 26. Shall provide a minimum of four (4) duplex receptacle electrical knock-outs per locker as described in section 2.4-A item 8.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

27. Shall provide UL Listed manufactured electrical wiring system as required. This manufactured electrical wiring system provides connection for a maximum of 78 receptacles per hardwired power in-feed (Note: total number of receptacles is dependent on load requirements). This manufactured electrical wiring system is a modular, unique, flexible, and cost effective method of providing electrical capability to the lockers. This electrical system can be added in the future.

Drawers (for bench drawer and external access drawer):

28. Drawer body wrapper shall have welded frame construction. Riveting of structural members will not be permitted.
29. Drawers for locker with built-in bench drawers and built-in external access drawers shall have box-formed drawer front.
30. Provide interlock system for securing drawer when main locker doors are closed and provide access only when main locker door/s is opened.
31. Built-in bench drawer shall have a nominal [36] inches or [914.4] millimeters depth.
32. Provide a flush mounted pull handle.
33. Drawer Slides: Provide [200] lbs or [90.72] kilograms maximum load capacity and pass 50,000 cycle performance testing (Max. load, uniform distribution) (Test data to be provided by manufacturer upon request)
34. Drawer base minimum [21] inches [533.4] millimeter drawer extension
35. Bench drawer minimum [26.5] inches [673.1] millimeter drawer extension
36. Provide louvered air vents in drawer front when built-in bench drawer or built-in external access drawer models are required.
37. Provide capability of attaching glides for Body Armored Drying Rack, as requested.

Bench Seat:

38. Provide [9.5] inches or [241.3] millimeter deep laminated kiln dried maple bench seat; material thickness [1.25] inches or [31.8] millimeters.
39. Front (leading edge) of bench seat to have [.625] inch or [15.88] millimeter radius bull nose.
40. Finish of bench seat shall be sanded smooth and have two (2) coats of catalyzed varnish applied.

Single-Piece Welded Doors (Single and Double Door Models):

41. Shall be formed from two (2) pieces of minimum 18-gauge [1.2] millimeter cold rolled steel box formed and welded together using modern GMAW techniques. Single-piece door with inner and outer door panels shall have a combined steel thickness of no less than [0.096] inches or [2.4] millimeters thick. Welded door design with inner panel optimizes structural integrity of locker door system over and above any single frame door design.
42. Exterior door panel shall be constructed with formed flanges and return flanges to add stiffness.
43. Internal door panel shall be constructed with formed flanges for added stiffness.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

44. All inner door panel (except Multi-Tier) heights shall be minimum 70% of external door height.
45. Single-piece welded door frame shall consist of internal door panel nested inside exterior door panel and welded per the following requirements:
 - a. Top / bottom. Exterior and Interior panels to be welded in a minimum of three (3) places with weld spacing not to exceed [6] inches or [152.4] millimeters between adjacent welds and [1] inch or [25.4] millimeters from any corner.
 - b. Sides. Exterior and interior panels to be welded with spacing not to exceed [12] inches or [304.8] millimeters between adjacent welds and [1] inch or [25.4] millimeters from any corner.
46. Inner door panel to have peg board style hole pattern, allowing the attachment of Document Holder and any standard peg board accessory.
47. Inner door panel to have [4] inch or [101.6] millimeter rectangular slot centered towards the top of the locker.
48. External door panel shall have louvers to provide adequate air circulation throughout locker system.
 - a. Louvered air vents shall be located at the bottom of the locker door to enhance circulation of mechanically extracted air from the bottom of the locker out of the top.
 - b. Louvered air vents shall be approximately [3] inches or [76.2] millimeters in width and [0.75] inches or [19.05] millimeters in height and spaced on [1] inch or [25.4] millimeter centers.
49. Single door designs available in [12] [18] and [24] inch or [304.8] [457.2] and [609.6] millimeter locker widths
50. Double door designs shall consist of the following:
 - a. Design available in [24] [30] and [36] inch or [609.6] [762.0] and [914.4] millimeter locker widths
 - b. Primary door located on the right and the secondary door located on the left-hand side of the locker.
 - c. Secondary door locking mechanism shall consist of the following:
 - 1) Return flange for supporting primary door
 - 2) Catch bracket
 - 3) One lower lock rod
51. All doors shall have neoprene silencers on each door for noise reduction
52. Door torsional deflection shall not exceed [0.1875] inch or [4.76] millimeter with a [20] lb or [9.071] kilogram point load. (Test data to be provided by manufacturer upon request)
53. Hinge:
 - a. Provide 16-gauge full length hinge for increased strength and security of locker system.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- b. Hinges to be welded to door frame with spot welds not to exceed [6] inch or [152.4] millimeter separation.
- 54. Door assembly to be riveted to door frame on factory pre-established hole pattern.
- 55. Locking Mechanism.
 - a. Provide three locking options (all locking options have protective stainless steel cover plate for durability and scratch resistance):
 - 1) Padlock hasp only.
 - 2) Keyed lock with master and padlock hasp.
 - 3) Combination lock with master and padlock hasp.
 - b. Keyed and combination locking mechanisms shall have the capability of locking automatically.
 - c. Keyed and Combination locking mechanisms shall have master key override.
 - d. Combination locking mechanism shall have user changeable preset combinations.
 - e. Single door models: Provide three locking options as listed above.
 - f. Double door models: Provide three locking options on the primary door and simple secure lift latch mechanism with [0.3125] inch or [7.94] millimeter lock rod for secondary door.

Interior/Accessory components:

- 56. All interior components must be constructed of minimum 18-gauge or [1.214] millimeter steel (unless otherwise clarified in specification).
- 57. For added security, internal component can be secured utilizing blind rivets, threaded fasteners, or bending specially designed tab.
- 58. All interior components available at time of order and as post-installation upgrades in the future.
- 59. Shelves (available all locker models)
 - a. Shelf with integral hanger bracket
 - 1) Size specified by locker width
 - 2) Hanger bracket designed with perforations on approximately [3] inch or [76.2] millimeter centers to insure clothing separation for optimum ventilation
 - 3) Performance: Uniform load rating [300] lbs or [136.08] kilograms
 - b. Plain
 - 1) Size specified by locker width
 - 2) Performance: Uniform load rating [100] lbs or [45.36] kilograms
 - c. Heavy Duty
 - 1) Size specified by locker width
 - 2) Performance: Uniform load rating [300] lbs or [136.08] kilograms

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- d. Perforated (use as drying rack)
 - 1) Size specified by locker width
 - 2) Tested performance: Uniform load rating [100] lbs or [45.36] kilograms
 - e. Shelf rear return flange stops minimum [0.50] inch or [12.7] millimeters short of locker back panel on order to allow air circulation throughout entire locker assembly
 - f. All performance test data shall be provided by manufacturer upon request.
 - g. Provide modular shelf with slots for connection with file dividers and shelf back stop. File dividers will aid in maintaining a neat and orderly locker system.
60. Provide lockable compartment for small valuables (available in all models except Multi-Tier)
- a. Lockable compartment shall be integral to modular shelf accessory
 - b. Provide a 14-gauge [1.897] millimeter padlock-able compartment door.
 - c. Provide [0.188] inch or [4.77] millimeter diameter zinc plated steel hinge rod.
 - d. Door to be mounted with zinc plated steel hinge rod and two shoulder washers for smooth, quiet operation.
 - e. Provide an 18-gauge or [1.214] millimeter hasp bracket for securing lockable compartment door.
61. Boot Tray
- a. Material – Rubber
 - b. Dimensions:
 - 1) Width – [12.90] inches or [327.7] millimeters
 - 2) Depth – [19.90] inches or [505.5] millimeters
 - 3) Height – [1.25] inches or [34.75] millimeters
 - c. Manufactured from Natural rubber compounds, environmentally friendly, durable, water repellant easily cleaned with soap and water, resistant to alkalis and weak acids, mold, mildew, and dust mites.
62. Body Armor Drying Rack
- a. Shall be available in bench drawer model widths of [18] [24] [30] [36] inch or [457.2] [609.6] [762.0] and [914.4] millimeters
 - b. Size of tray is controlled by locker width
 - c. Bottom of drying tray shall have louvered pattern to provide air circulation throughout
 - d. Shall have the ability to adjust/glide frontward and backward, while mounted in the bench drawer.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

63. Hooks

- a. Hook Bracket Hanger Assembly – shall have the ability to attach a three-hook bracket assembly to any lanced location on the side panels of the locker.

Electrical system

64. UL listed manufactured electrical wiring system with plug-in-play component design

65. Receptacles – standard 20 amp duplex receptacles and 20 amp GFCI duplex receptacles
HVAC

66. All lockers (except Multi-Tier) shall be equipped with mechanical air extraction capabilities and adjustable air balancing capabilities

67. When mechanical air extraction is required, manufacturer shall provide locker system HVAC guidelines and recommendations to aid in overall locker and building system integration. It is the General Contractor and HVAC Contractors' responsibility to establish/balance air flow through locker system according to building HVAC constraints.

Locker Tag Numbers

68. Shall provide locker numbers on each locker per customer requirement

ACCESSORIES:

69. Trim and Fillers: Provide manufacturer's standard.

2.5 FABRICATION

General: Coordinate fabrication and delivery to ensure no delay in progress of the work.

2.6 FINISHES

Colors: Selected from manufacturer's standard available colors by Architect.

Paint Finish: Textured (Standard) – Provide factory applied electrostatic powder coat paint. Meet or exceed specifications of the American Society for Testing and Materials (ASTM) Standards:

PART 3 - EXECUTION

3.1 EXAMINATION

Examine Lockers scheduled to receive accessories with Installer present for compliance with requirements for installation tolerances and other conditions affecting performance of specified accessory items.

Proceed with accessory installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

General: Follow manufacturer's written instructions for installation of each type of accessory item specified.

3.3 FIELD QUALITY CONTROL

Verify accessory unit alignment and plumb after installation. Correct if required, following manufacturer's instructions.

Remove components that are chipped, scratched, or otherwise damaged and which do not match adjoining work. Replace with new matching units, installed as specified and in manner to eliminate evidence of replacement.

3.4 ADJUSTING

Adjust all accessories to provide smoothly operating, visually acceptable installation.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- 3.5 **CLEANING**
Immediately upon completion of installation, clean components and surfaces. Remove surplus materials, rubbish and debris, resulting from installation, upon completion of work and leave areas of installation in neat, clean condition.
- 3.6 **DEMONSTRATION/TRAINING**
Schedule and conduct demonstration of installed accessory items and features with Owner's personnel.
Schedule and conduct maintenance training with Owner's maintenance personnel. Training session should include lecture and demonstration of all maintenance and repair procedures that end-user personnel would normally perform.
- 3.7 **PROTECTION**
Protect system against damage during remainder of construction period. Advise owner of additional protection needed to ensure that system will be without damage or deterioration at time of substantial completion.

END OF SECTION

2. Concealed surfaces include walls or ceilings in the following generally inaccessible spaces:
 - a. Foundation spaces.
 - b. Furred areas.
 - c. Ceiling plenums.
 - d. Utility tunnels.
 - e. Pipe spaces.
 - f. Duct shafts.
 - g. Elevator shafts.
 3. Finished metal surfaces include the following:
 - a. Anodized aluminum.
 - b. Stainless steel.
 - c. Chromium plate.
 - d. Copper.
 - e. Bronze and brass.
 4. Operating parts include moving parts of operating equipment and the following:
 - a. Valve and damper operators.
 - b. Linkages.
 - c. Sensing devices.
 - d. Motor and fan shafts.
 5. Labels: Do not paint over Underwriters Laboratories (UL), Factory Mutual (FM), or other code-required labels or equipment name, identification, performance rating, or nomenclature plates.
- D. Related Sections include the following:
1. Division 05 Section "Metal Fabrications" for shop priming ferrous metal.
 2. Division 08 Section "Hollow Metal Doors and Frames" for shop priming steel doors and frames.

1.3 DEFINITIONS:

- A. General: Standard coating terms defined in ASTM D 16 apply to this Section.
1. Flat refers to a lusterless or matte finish with a gloss range below 15 when measured at an 85-degree meter.
 2. Eggshell refers to low-sheen finish with a gloss range between 5 and 20 when measured at a 60-degree meter.
 3. Satin refers to low-sheen finish with a gloss range between 15 and 35 when measured at a 60-degree meter.
 4. Semigloss refers to medium-sheen finish with a gloss range between 30 and 65 when measured at a 60-degree meter.

5. Full gloss refers to high-sheen finish with a gloss range more than 65 when measured at a 60-degree meter.

1.4 SUBMITTALS:

- A. **Product Data:** For each paint system specified. Include block fillers and primers.
 1. **Material List:** Provide an inclusive list of required coating materials. Indicate each material and cross-reference specific coating, finish system, and application. Identify each material by manufacturer's catalog number and general classification.
 2. **Manufacturer's Information:** Provide manufacturer's technical information, including label analysis and instructions for handling, storing, and applying each coating material proposed for use.
- B. **Samples for Initial Selection:** Manufacturer's color charts showing the full range of colors available for each type of finish-coat material indicated.
 1. After color selection, the Architect will furnish color chips for surfaces to be coated.
- C. **Samples for Verification:** Of each color and material to be applied, with texture to simulate actual conditions, on representative Samples of the actual substrate.
 1. Provide stepped Samples, defining each separate coat, including block fillers and primers. Use representative colors when preparing Samples for review. Resubmit until required sheen, color, and texture are achieved.
 2. Provide a list of materials and applications for each coat of each sample. Label each sample for location and application.
 3. Submit Samples on the following substrates for the Architect's review of color and texture only:
 - a. **Concrete:** Provide two 4-inch- square samples for each color and finish.
 - b. **Concrete Masonry:** Provide two 4-by-8-inch samples of masonry, with mortar joint in the center, for each finish and color.
 - c. **Painted Wood:** Provide two 12-inch- square samples of each color and material on hardboard.
 - d. **Ferrous Metal:** Provide two 4-inch- square samples of flat metal and two 8-inch- long samples of solid metal for each color and finish.
- D. **Qualification Data:** For firms and persons specified in the "Quality Assurance" Article to demonstrate their capabilities and experience. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.

1.5 QUALITY ASSURANCE:

- A. Applicator Qualifications: Engage an experienced applicator who has completed painting system applications similar in material and extent to that indicated for this Project with a record of successful in-service performance.
- B. Source Limitations: Obtain block fillers, primers, and undercoat materials for each coating system from the same manufacturer as the finish coats.

1.6 DELIVERY, STORAGE, AND HANDLING:

- A. Deliver materials to the Project Site in manufacturer's original, unopened packages and containers bearing manufacturer's name and label, and the following information:
 - 1. Product name or title of material.
 - 2. Product description (generic classification or binder type).
 - 3. Manufacturer's stock number and date of manufacture.
 - 4. Contents by volume, for pigment and vehicle constituents.
 - 5. Thinning instructions.
 - 6. Application instructions.
 - 7. Color name and number.
 - 8. VOC content.
- B. Store materials not in use in tightly covered containers in a well-ventilated area at a minimum ambient temperature of 45 deg F. Maintain containers used in storage in a clean condition, free of foreign materials and residue.
 - 1. Protect from freezing. Keep storage area neat and orderly. Remove oily rags and waste daily. Take necessary measures to ensure that workers and work areas are protected from fire and health hazards resulting from handling, mixing, and application.

1.7 PROJECT CONDITIONS:

- A. Apply water-based paints only when the temperature of surfaces to be painted and surrounding air temperatures are between 50 and 90 deg F.
- B. Apply solvent-thinned paints only when the temperature of surfaces to be painted and surrounding air temperatures are between 45 and 95 deg F.
- C. Do not apply paint in snow, rain, fog, or mist; or when the relative humidity exceeds 85 percent; or at temperatures less than 5 deg F above the dew point; or to damp or wet surfaces.
 - 1. Painting may continue during inclement weather if surfaces and areas to be painted are enclosed and heated within temperature limits specified by manufacturer during application and drying periods.

1.8 EXTRA MATERIALS:

- A. Furnish extra paint materials from the same production run as the materials applied in the quantities described below. Package paint materials in unopened, factory-sealed containers for storage and identify with labels describing contents. Deliver extra materials to the Owner.
 - 1. Quantity:
 - a. Furnish the Owner with an additional 1 gallon of each wall paint and color applied. No partial filled paint containers.
 - b. Furnish the Owner with an additional 1 quart of each door frame paint and color applied. No partial filled paint containers.

PART 2 - PRODUCTS

2.1 MANUFACTURERS:

- A. Products: Subject to compliance with requirements, provide one of the products in the paint schedules.
- B. Manufacturers Names: The following manufacturers are referred to in the paint schedules by use of shortened versions of their names, which are shown in parentheses:
 - 1. Benjamin Moore & Co. (Moore).

2.2 PAINT MATERIALS, GENERAL:

- A. Material Compatibility: Provide block fillers, primers, undercoats, and finish-coat materials that are compatible with one another and the substrates indicated under conditions of service and application, as demonstrated by manufacturer based on testing and field experience.
- B. Material Quality: Provide manufacturer's best-quality paint material of the various coating types specified. Paint-material containers not displaying manufacturer's product identification will not be acceptable.
 - 1. Proprietary Names: Use of manufacturer's proprietary product names to designate colors or materials is not intended to imply that products named are required to be used to the exclusion of equivalent products of other manufacturers. Furnish manufacturer's material data and certificates of performance for proposed substitutions.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- C. Chemical Components of Field-Applied Interior Paints and Coatings: Provide topcoat paints and anti-corrosive and anti-rust paints applied to ferrous metals that comply with the following chemical restrictions; these requirements do not apply to paints and coatings that are applied in a fabrication or finishing shop:
1. Aromatic Compounds: Paints and coatings shall not contain more than 1.0 percent by weight of total aromatic compounds (hydrocarbon compounds containing one or more benzene rings).
 2. Restricted Components: Paints and coatings shall not contain any of the following:
 - a. Acrolein.
 - b. Acrylonitrile.
 - c. Antimony.
 - d. Benzene.
 - e. Butyl benzyl phthalate.
 - f. Cadmium.
 - g. Di (2-ethylhexyl) phthalate.
 - h. Di-n-butyl phthalate.
 - i. Di-n-octyl phthalate.
 - j. 1,2-dichlorobenzene.
 - k. Diethyl phthalate.
 - l. Dimethyl phthalate.
 - m. Ethylbenzene.
 - n. Formaldehyde.
 - o. Hexavalent chromium.
 - p. Isophorone.
 - q. Lead.
 - r. Mercury.
 - s. Methyl ethyl ketone.
 - t. Methyl isobutyl ketone.
 - u. Methylene chloride.
 - v. Naphthalene.
 - w. Toluene (methylbenzene).
 - x. 1,1,1-trichloroethane.
 - y. Vinyl chloride.
- D. Paint Colors:
1. **EP-1:** Benjamin Moore, epoxy, Semigloss 2134-50 Gull Wing Gray Men's Locker Room - Walls
 2. **P-2:** Benjamin Moore Semigloss 2065-10 Admiral Blue Men's Locker Room - Door Frames
 3. **EP-3:** Benjamin Moore , epoxy, Semigloss HC-27 Monterey White Women's Locker Room - Walls
 4. **P-4:** Benjamin Moore Semigloss HC-44 Lenox Tan Women's Locker Room - Door Frames

PART 3 - EXECUTION

3.1 EXAMINATION:

- A. Examine substrates, areas, and conditions, with the Applicator present, under which painting will be performed for compliance with paint application requirements.
 - 1. Do not begin to apply paint until unsatisfactory conditions have been corrected and surfaces receiving paint are thoroughly dry.
 - 2. Start of painting will be construed as the Applicator's acceptance of surfaces and conditions within a particular area.
- B. Coordination of Work: Review other Sections in which primers are provided to ensure compatibility of the total system for various substrates. On request, furnish information on characteristics of finish materials to ensure use of compatible primers.
 - 1. Notify the Architect about anticipated problems using the materials specified over substrates primed by others.

3.2 PREPARATION:

- A. General: Remove hardware and hardware accessories, plates, machined surfaces, lighting fixtures, and similar items already installed that are not to be painted. If removal is impractical or impossible because of the size or weight of the item, provide surface-applied protection before surface preparation and painting.
 - 1. After completing painting operations in each space or area, reinstall items removed using workers skilled in the trades involved.
- B. Cleaning: Before applying paint or other surface treatments, clean the substrates of substances that could impair the bond of the various coatings. Remove oil and grease before cleaning.
 - 1. Schedule cleaning and painting so dust and other contaminants from the cleaning process will not fall on wet, newly painted surfaces.
- C. Surface Preparation: Clean and prepare surfaces to be painted according to manufacturer's written instructions for each particular substrate condition and as specified.
 - 1. Provide barrier coats over incompatible primers or remove and reprime.
 - 2. Cementitious Materials: Prepare concrete, concrete masonry block, cement plaster, and mineral-fiber-reinforced cement panel surfaces to be painted. Remove efflorescence, chalk, dust, dirt, grease, oils, and release agents. Roughen as required to remove glaze. If hardeners or sealers have been used to improve curing, use mechanical methods of surface preparation.
 - a. Use abrasive blast-cleaning methods if recommended by paint manufacturer.

GLASTONBURY TRACKING NUMBER: GL-2017-26

- b. Determine alkalinity and moisture content of surfaces by performing appropriate tests. If surfaces are sufficiently alkaline to cause the finish paint to blister and burn, correct this condition before application. Do not paint surfaces where moisture content exceeds that permitted in manufacturer's written instructions.
 3. Ferrous Metals: Clean ungalvanized ferrous-metal surfaces that have not been shop coated; remove oil, grease, dirt, loose mill scale, and other foreign substances. Use solvent or mechanical cleaning methods that comply with the Steel Structures Painting Council's (SSPC) recommendations.
 - a. Touch up bare areas and shop-applied prime coats that have been damaged. Wire-brush, clean with solvents recommended by paint manufacturer, and touch up with the same primer as the shop coat.
 4. Galvanized Surfaces: Clean galvanized surfaces with nonpetroleum-based solvents so surface is free of oil and surface contaminants. Remove pretreatment from galvanized sheet metal fabricated from coil stock by mechanical methods.
- D. Materials Preparation: Mix and prepare paint materials according to manufacturer's written instructions.
 1. Maintain containers used in mixing and applying paint in a clean condition, free of foreign materials and residue.
 2. Stir material before application to produce a mixture of uniform density. Stir as required during application. Do not stir surface film into material. If necessary, remove surface film and strain material before using.
 3. Use only thinners approved by paint manufacturer and only within recommended limits.
- E. Tinting: Tint each undercoat a lighter shade to simplify identification of each coat when multiple coats of the same material are applied. Tint undercoats to match the color of the finish coat, but provide sufficient differences in shade of undercoats to distinguish each separate coat.

3.3 APPLICATION:

- A. General: Apply paint according to manufacturer's written instructions. Use applicators and techniques best suited for substrate and type of material being applied.
 1. Paint colors, surface treatments, and finishes are indicated in the schedules.
 2. Do not paint over dirt, rust, scale, grease, moisture, scuffed surfaces, or conditions detrimental to formation of a durable paint film.
 3. Provide finish coats that are compatible with primers used.
 4. The term "exposed surfaces" includes areas visible when permanent or built-in fixtures, convactor covers, covers for finned-tube radiation, grilles, and similar components are in place. Extend coatings in these areas, as required, to maintain the system integrity and provide desired protection.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

5. Paint surfaces behind movable equipment and furniture the same as similar exposed surfaces. Before the final installation of equipment, paint surfaces behind permanently fixed equipment or furniture with prime coat only.
 6. Paint interior surfaces of ducts with a flat, nonspecular black paint where visible through registers or grilles.
 7. Paint back sides of access panels and removable or hinged covers to match exposed surfaces.
 8. Finish exterior doors on tops, bottoms, and side edges the same as exterior faces.
- B. Scheduling Painting: Apply first coat to surfaces that have been cleaned, pretreated, or otherwise prepared for painting as soon as practicable after preparation and before subsequent surface deterioration.
1. The number of coats and the film thickness required are the same regardless of application method. Do not apply succeeding coats until the previous coat has cured as recommended by the manufacturer. If sanding is required to produce a smooth, even surface according to manufacturer's written instructions, sand between applications.
 2. Omit primer on metal surfaces that have been shop primed and touchup painted.
 3. If undercoats, stains, or other conditions show through final coat of paint, apply additional coats until paint film is of uniform finish, color, and appearance. Give special attention to ensure edges, corners, crevices, welds, and exposed fasteners receive a dry film thickness equivalent to that of flat surfaces.
 4. Allow sufficient time between successive coats to permit proper drying. Do not recoat surfaces until paint has dried to where it feels firm, does not deform or feel sticky under moderate thumb pressure, and where application of another coat of paint does not cause the undercoat to lift or lose adhesion.
- C. Application Procedures: Apply paints and coatings by brush, roller, spray, or other applicators according to manufacturer's written instructions.
1. Brushes: Use brushes best suited for the type of material applied. Use brush of appropriate size for the surface or item being painted.
 2. Rollers: Use rollers of carpet, velvet back, or high-pile sheep's wool as recommended by the manufacturer for the material and texture required.
 3. Spray Equipment: Use airless spray equipment with orifice size as recommended by the manufacturer for the material and texture required.
- D. Minimum Coating Thickness: Apply paint materials no thinner than manufacturer's recommended spreading rate. Provide the total dry film thickness of the entire system as recommended by the manufacturer.
- E. Mechanical and Electrical Work: Painting of mechanical and electrical work is limited to items exposed in equipment rooms (electrical, mechanical and data) and in occupied spaces.
- F. Mechanical items to be painted include, but are not limited to, the following:
1. Piping, pipe hangers, and supports.

2. Heat exchangers.
3. Tanks.
4. Ductwork.
5. Insulation.
6. Accessory items.

G. Electrical items to be painted include, but are not limited to, the following:

1. Conduit and fittings.

H. Block Fillers: Apply block fillers to concrete masonry block at a rate to ensure complete coverage with pores filled.

I. Prime Coats: Before applying finish coats, apply a prime coat of material, as recommended by the manufacturer, to material that is required to be painted or finished and that has not been prime coated by others. Recoat primed and sealed surfaces where evidence of suction spots or unsealed areas in first coat appears, to ensure a finish coat with no burn through or other defects due to insufficient sealing.

J. Pigmented (Opaque) Finishes: Completely cover surfaces as necessary to provide a smooth, opaque surface of uniform finish, color, appearance, and coverage. Cloudiness, spotting, holidays, laps, brush marks, runs, sags, ropiness, or other surface imperfections will not be acceptable.

K. Transparent (Clear) Finishes: Use multiple coats to produce a glass-smooth surface film of even luster. Provide a finish free of laps, runs, cloudiness, color irregularity, brush marks, orange peel, nail holes, or other surface imperfections.

1. Provide satin finish for final coats.

L. Completed Work: Match approved samples for color, texture, and coverage. Remove, refinish, or repaint work not complying with requirements.

3.4 CLEANING:

A. Cleanup: At the end of each workday, remove empty cans, rags, rubbish, and other discarded paint materials from the site.

1. After completing painting, clean glass and paint-spattered surfaces. Remove spattered paint by washing and scraping. Be careful not to scratch or damage adjacent finished surfaces.

3.5 PROTECTION:

A. Protect work of other trades, whether being painted or not, against damage by painting. Correct damage by cleaning, repairing or replacing, and repainting, as approved by Architect.

- B. Provide "Wet Paint" signs to protect newly painted finishes. Remove temporary protective wrappings provided by others to protect their work after completing painting operations.
 - 1. At completion of construction activities of other trades, touch up and restore damaged or defaced painted surfaces. Comply with procedures specified in PDCA P1.

3.6 INTERIOR PAINT SCHEDULE:

- A. Concrete Unit Masonry: Provide the following finish system over concrete unit masonry:
 - 1. Semigloss, Epoxy Enamel Finish: Two finish coats over a block filler with a total dry film thickness not less than 3.0 mils, excluding filler coat.
 - a. Block Filler: High-performance, latex block filler applied at spreading rate recommended by the manufacturer to achieve a total dry mill thickness of not less than 14.0 mils.
 - 1) Moore: Corotech Acrylic Block Filler 114.
 - b. First and Second Coats: Interior, semigloss, epoxy enamel.
 - 1) Moore: Corotech V341 Pre Cat Epoxy.
- B. Ferrous Metal: Provide the following finish systems over ferrous metal:
 - 1. Semigloss, Acrylic-Enamel Finish: One finish coat over an enamel undercoater and a primer.
 - a. Primer: Quick-drying, rust-inhibitive, acrylic-metal primer, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.5 mils.
 - 1) Moore: Super Spec HP Acrylic Metal Primer.
 - b. Undercoat: Alkyd, interior enamel undercoat or semigloss, acrylic-latex, interior enamel, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.3 mils.
 - 1) Moore: Ultra Spec 500 Semi Gloss N539.
 - c. Finish Coat: Semigloss, acrylic-latex, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.3 mils.
 - 1) Moore: Ultra Spec 500 Semi Gloss N539.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

C. Zinc-Coated Metal: Provide the following finish systems over zinc-coated metal:

1. Semigloss, Acrylic-Enamel Finish: 2 finish coats over a primer.
 - a. Primer: Galvanized metal primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Moore: P04 Super Spec HP Acrylic Metal Primer.
 - b. Undercoat: Acrylic, interior enamel undercoat or semigloss, interior, acrylic-enamel finish coat, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Moore: Ultra Spec 500 Semi Gloss N539.
 - c. Finish Coat: Odorless, semigloss, acrylic, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.4 mils.
 - 1) Moore: Ultra Spec 500 Semi Gloss N539.

END OF SECTION 099100

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

SECTION 105113 – WELDED METAL LOCKERS (PERSONAL STORAGE LOCKERS WITH BUILT-IN BENCH DRAWER)

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

This Section includes the following:

1. Installation of Personal Storage Lockers with built-in bench drawers, purchased by Owner.
 - a. All lockers include electrical functionality as required.
2. All Personal Storage Lockers, Personal Storage with built-in bench drawers, and Personal Storage Lockers with built-in external access drawers must include environmental ventilation functionality as required.

Related Sections:

Sections in Division 9 – Finishes, relating to finish floor and base materials

1.3 REFERENCES

American National Standards Institute (ANSI) Standards:

Applicable standards for fasteners used for assembly.

American Society for Testing and Materials (ASTM) Standards:

Applicable standards for steel sheet materials used for fabrication

Applicable standards for the testing of electrostatically applied Powder Coat Paint

American Institute Of Steel Construction (AISC) Standards:

Applicable standards for steel materials used for fabrication.

1.4 DESCRIPTION

General: Welded Metal Lockers only with end-user reconfigurable interior. Specialized lances to provide the flexibility of on-site, end-user reconfiguration/addition of internal components anytime, anywhere, now or in the future.

Finishes:

Fabricated Metal Components and Assemblies: All components to be painted with an electrostatically applied Powder Coat paint that can meet or exceed test requirements set out by ASTM standard D3451-06 Standard Guide for Testing Coating Powders and Powder Coatings.

Sizes:

Personal Storage Lockers with built-in bench drawers: height to be [84] inches or [2133.6] millimeters respectively; Built-in bench drawer height is [18] inches or [457.2] millimeters and depth is [36] inches or [914.4] millimeters.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

1.5 PERFORMANCE REQUIREMENTS

Design Requirements:

Limit overall width not to exceed specified nominal width; locker width designed for zero growth.

Seismic Performance: Provide Welded Metal Lockers capable of withstanding the effects of earthquake movement when required by applicable building codes.

ADA Requirements: Personal Storage Lockers with nominal height of [72] inches or [1828.8] millimeters meet ADA requirements.

1.6 SUBMITTALS

Product Data: Submit manufacturer's product literature and installation instructions for each type of welded metal locker required. Include data substantiating that products to be furnished comply with requirements of the contract documents.

Shop Drawings: Show fabrication, assembly, and installation details, including descriptions of procedures and diagrams. Show complete locker installation layout, including quantities, locations and types of accessory units required. Include notations and descriptions of all installation items and components.

Show installation details at non-standard conditions, if any.

Provide layout, dimensions, and identification of each unit, corresponding to sequence of installation procedures.

Provide installation schedule and procedures to ensure proper installation.

Samples: Provide minimum [3] inches or [76] millimeters square example of each color and texture on actual substrate for each component to remain exposed after installation.

Selection Samples: For initial selection of colors and textures, submit manufacturer's color charts, consisting of actual product pieces, showing full range of colors and textures available.

Warranty: Submit draft copy of proposed warranty for review by the Architect.

Maintenance Data: Provide written documentation of the manufacturer's statement, claiming the maintenance free nature of the product.

Reference List: Provide a list of recently installed welded metal lockers to be visited by owner, architect, and contractor. Intent of list is to aid in verifying the suitability of manufacturer's products and comparison with materials and product specified in this section. Include contact name, address, and phone numbers.

1.7 QUALITY ASSURANCE

Manufacturer Qualifications: Engage an experienced manufacturer who is ISO 9001:2008 certified for the design, production, installation and service of welded metal lockers. Furnish certification attesting ISO 9001:2008 quality system registration.

Installer Qualifications: Engage an experienced installer who is the manufacturer's authorized representative for the specified products for installing welded metal lockers.

Minimum Qualifications: 1-year experience installing welded metal lockers of comparable size and complexity to specified project requirements.

1.8 DELIVERY, STORAGE AND HANDLING

Follow manufacturer's instructions and recommendations for delivery, storage and handling requirements.

1.9 PROJECT CONDITIONS

Field Measurements: Verify quantities of welded metal locker units before fabrication. Indicate verified measurements on shop drawings. Coordinate fabrication and delivery to ensure no delay in progress of the work.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

Established Dimensions: Where field measurements cannot be made without delaying the Work, establish dimensions and proceed with fabricating welded metal lockers units without field measurements. Coordinate construction to ensure actual dimensions correspond to established dimensions.

1.10 SEQUENCING AND SCHEDULING

Sequence welded metal lockers [with other work] to minimize possibility of damage and soiling, during remainder of construction period.

Schedule installation of specified welded metal lockers after finishing operations, including painting, have been completed.

Provide components, which must be built in at a time, which causes no delays in the general progress of the work.

Pre-installation Conference: Schedule and conduct conference on project site to review methods and procedures for installing welded Metal Lockers including, but not limited to, the following:

Recommended attendees include:

1. Owner's Representative.
2. Contractor.
3. Architect.
4. Manufacturer's representative.
5. Subcontractors or installers whose work may affect, or be affected by, the work of this section.

1.11 WARRANTY

Provide a written warranty, executed by Contractor, Installer, and Manufacturer, agreeing to repair or replace units, which fail in materials or workmanship within the established warranty period. This warranty shall be in addition to, and not a limitation of, other rights the Owner may have under General Condition's provisions of the Contract Documents.

Limited Lifetime Warranty: Subject to the terms in the written warranty, warrant the original purchaser exclusively that the locker frames manufactured by it will be free from defects in materials and workmanship for the lifetime of the locker.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

General: Free**Style**[™] Personal Storage with built-in bench drawers, based upon welded metal lockers manufactured by Spacesaver Corporation, 1450 Janesville Avenue, Fort Atkinson, Wisconsin 53538-2798. Telephone: 800-492-3434.

2.2 BASIC MATERIALS

General: Provide materials and quality of workmanship, which meets or exceeds established industry standards for products specified. Use furniture grade sheet metal, solid hardwood benches and fasteners for component fabrication unless indicated otherwise. Material thicknesses/gauges are manufacturer's option unless indicated otherwise.

2.3 LOCKER TYPES

Personal Storage Lockers. Provide personal storage lockers with built-in bench drawers by Spacesaver Corporation.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

1. All locker types (except Multi-Tier) to be equipped with environmental ventilation functionality for applications where Mechanical Air Extraction is desired to remove unpleasant odors from the locker.
2. All locker types (except Multi-Tier) to be equipped with the functionality of attaching a modular electrical system as required.
3. All locker types to be equipped with the functionality of attaching a continuous sloped top.

2.4 MANUFACTURED COMPONENTS

Welded Frame:

1. The welded frame must consist of top, bottom, back, and sides constructed of a minimum of 18-gauge or [1.214] millimeters steel. All frame components shall be joined using resistance welding. Riveting of structural members will not be permitted.
2. Horizontal front flanges will be a minimum of [2] inches or [50.8] millimeters. Vertical front flanges will be a minimum of [1] inch or [25.4] millimeters. Horizontal and vertical flanges will overlap and be secured with a minimum two (2) resistance welds per corner.
3. Corner gussets shall be MIG and spot welded in each of the four front corners of the locker for increased stiffness and rigidity.
4. Provide side panel lances evenly spaced on [3] inch or [76.2] millimeter centers. Lances to provide the flexibility of on-site, end-user reconfiguration/addition of internal components anytime, anywhere, now or in the future.
5. Bench Housing for built-in bench drawer
 - a. Welded frame construction shall consist of top, bottom, and side components joined by using resistance welding. Riveting of bench housing structural members will not be permitted.
 - b. Corner gussets shall be welded in the two (2) front bottom corners of the bench housing for increased stiffness and rigidity.
 - c. Horizontal front flanges will be a minimum of [1] inch or [25.4] millimeters
 - d. Vertical front flanges will be a minimum of [1] inch or [25.4] millimeters
 - e. Horizontal and Vertical front flanges will overlap and shall be secured with minimum of one (1) resistance weld per corner.
 - f. Side panels – Lances symmetric and evenly spaced to provide optimum component locations (standard based on [3] inch or [76.2] millimeter on center vertical placement to match mating locker lance design).
 - g. Return flanges on housing to securely fasten housing to welded frame of locker.
 - h. Base of bench housing shall include four (4) 3/8"-16 UNC threaded weld-nuts and corresponding leveling feet.
 - i. Top of bench housing shall include hole pattern for mating bench seat.
 - j. Sides of bench housing shall include mounting holes in the event lockers are ganged together.
6. Lockers with built-in bench drawer and built-in external access drawer shall have intermediate base shelf with interlocking mechanism for securing drawer when locker door is closed.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

7. Provide four (4) [0.875] inch or [22.23] millimeter diameter electrical knock-outs per locker, two (2) located on top of the locker in both right and left rear corners, and two (2) located in the back of locker centered at a distance no greater than [24] inches or [609.6] millimeters from the top and bottom. Knock-outs allow end-user flexibility of adding electrical capability to lockers.
8. Provide a minimum of four (4) duplex receptacle electrical knock-outs per locker; to be used with a UL listed manufactured electrical wiring system as required. This manufactured electrical wiring system is a simple, unique, flexible, and cost effective method of providing electrical capability to the lockers. This electrical system can be added in the future.
 - a. Top of locker shall have electrical duplex receptacle knock-outs located on both right and left side of locker.
 - b. Back panel of locker shall have a minimum of two (2) duplex electrical knock-outs.
 - c. Back of locker shall have electrical duplex receptacle knock-outs located on both right and left side of locker and no farther than [24] inches or [609.6] millimeters from the top of the locker.
9. Provide ventilation holes in top of locker to allow mechanically extracted air to be pulled up through the locker system as required. Ventilation shall be controlled by eight (8) evenly spaced [0.625] inch or [15.875] millimeter diameter holes. Proper ventilation system ensures unpleasant odors are removed from locker system.
10. Lockers shall be prepared with mounting holes for use with the continuous sloped top system.
11. Lockers shall be prepared with mounting holes for attaching necessary trim components
12. Locker shall be prepared with mounting holes for ganging lockers back-to-back or side-by-side
13. Base of lockers shall include four (4) 3/8"-16 UNC threaded weld-nuts and corresponding leveling feet.
14. Base shelf for lockers with built-in external access drawers and bench drawers shall have holes to accommodate double-door lock rod and door stop bracket. (only on [24] inch or [609.6] millimeters wide and larger)
15. End Panels: End Panels with no exposed fasteners shall be provided on the end of each locker run; thus providing a clean and aesthetically pleasing appearance.
16. All locker sizes and types to be specified by architect.
 - a. Width:
 - 1) Personal Storage Locker with built-in bench drawer or external access drawer. [24] inches or [609.6] millimeters
 - b. Height:
 - 1) Personal Storage Locker with built in bench drawer or external access drawer: [84] inches or [2133.6] millimeters
 - c. Depth:

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- 1) All lockers [24] inches or [609.6] millimeters
- 2) Bench drawers: [36] inches or [914.4] millimeters
 - c) Bench seat depth [9.5] inches or [241.3] millimeters
 - c) Leading edge of bench seat to extend [1.125] inches or [28.6] millimeters from front of bench drawer

Ventilation:

17. Provide ventilation holes in top of locker to allow mechanically extracted air to be pulled up through the locker system as required. Ventilation shall be controlled by eight (8) evenly spaced [0.625] inch or [15.875] millimeter diameter holes. Proper ventilation system ensures odors are removed from locker system.
18. Provide an adjustable air baffle for system balancing when mechanical air extraction is used. Upon balancing system, air baffle shall be secured with a fastener to maintain ventilation setting.
19. Provide louvered air vents in bottom of the main locker door/s to allow mechanically extracted air to be pulled up through the locker system.
20. Provide louvered air vents in drawer front when built-in bench drawer or built-in external access drawer models are required.
21. Minimum [0.500] inch or [12.7] millimeter gap between back of shelving components and back of locker to provide uninterrupted air flow up the rear of the locker system.
22. Minimum [2.00] inches or [558.8] millimeter gap between front of shelving and locker door to provide uninterrupted air flow up the front of the locker system.
23. Multi-Tier ventilation is provided thru door panels
24. Upon request manufacturer shall provide HVAC tech data to serve as a guideline for the General Contractor and HVAC Contactor. It is the General Contractor and/or HVAC contractors' responsibility to establish/balance air flow through locker system according to building HVAC constraints.

Electrical

25. Shall provide four (4) electrical knock-outs per locker as described in section 2.4-A item 7. This feature provides the end-user the opportunity for hard wire electrical connection points for each locker. End-user or General Contractor is responsible for final electrical installation.
26. Shall provide a minimum of four (4) duplex receptacle electrical knock-outs per locker as described in section 2.4-A item 8.
27. Shall provide UL Listed manufactured electrical wiring system as required. This manufactured electrical wiring system provides connection for a maximum of 78 receptacles per hardwired power in-feed (Note: total number of receptacles is dependent on load requirements). This manufactured electrical wiring system is a modular, unique, flexible, and cost effective method of providing electrical capability to the lockers. This electrical system can be added in the future.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

Drawers (for bench drawer and external access drawer):

28. Drawer body wrapper shall have welded frame construction. Riveting of structural members will not be permitted.
29. Drawers for locker with built-in bench drawers and built-in external access drawers shall have box-formed drawer front.
30. Provide interlock system for securing drawer when main locker doors are closed and provide access only when main locker door/s is opened.
31. Built-in bench drawer shall have a nominal [36] inches or [914.4] millimeters depth.
32. Provide a flush mounted pull handle.
33. Drawer Slides: Provide [200] lbs or [90.72] kilograms maximum load capacity and pass 50,000 cycle performance testing (Max. load, uniform distribution) (Test data to be provided by manufacturer upon request)
34. Drawer base minimum [21] inches [533.4] millimeter drawer extension
35. Bench drawer minimum [26.5] inches [673.1] millimeter drawer extension
36. Provide louvered air vents in drawer front when built-in bench drawer or built-in external access drawer models are required.
37. Provide capability of attaching glides for Body Armored Drying Rack, as requested.

Bench Seat:

38. Provide [9.5] inches or [241.3] millimeter deep laminated kiln dried maple bench seat; material thickness [1.25] inches or [31.8] millimeters.
39. Front (leading edge) of bench seat to have [.625] inch or [15.88] millimeter radius bull nose.
40. Finish of bench seat shall be sanded smooth and have two (2) coats of catalyzed varnish applied.

Single-Piece Welded Doors (Single and Double Door Models):

41. Shall be formed from two (2) pieces of minimum 18-gauge [1.2] millimeter cold rolled steel box formed and welded together using modern GMAW techniques. Single-piece door with inner and outer door panels shall have a combined steel thickness of no less than [0.096] inches or [2.4] millimeters thick. Welded door design with inner panel optimizes structural integrity of locker door system over and above any single frame door design.
42. Exterior door panel shall be constructed with formed flanges and return flanges to add stiffness.
43. Internal door panel shall be constructed with formed flanges for added stiffness.
44. All inner door panel (except Multi-Tier) heights shall be minimum 70% of external door height.
45. Single-piece welded door frame shall consist of internal door panel nested inside exterior door panel and welded per the following requirements:

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- a. Top / bottom. Exterior and Interior panels to be welded in a minimum of three (3) places with weld spacing not to exceed [6] inches or [152.4] millimeters between adjacent welds and [1] inch or [25.4] millimeters from any corner.
 - b. Sides. Exterior and interior panels to be welded with spacing not to exceed [12] inches or [304.8] millimeters between adjacent welds and [1] inch or [25.4] millimeters from any corner.
46. Inner door panel to have peg board style hole pattern, allowing the attachment of Document Holder and any standard peg board accessory.
47. Inner door panel to have [4] inch or [101.6] millimeter rectangular slot centered towards the top of the locker.
48. External door panel shall have louvers to provide adequate air circulation throughout locker system.
- a. Louvered air vents shall be located at the bottom of the locker door to enhance circulation of mechanically extracted air from the bottom of the locker out of the top.
 - b. Louvered air vents shall be approximately [3] inches or [76.2] millimeters in width and [0.75] inches or [19.05] millimeters in height and spaced on [1] inch or [25.4] millimeter centers.
49. Single door designs available in [12] [18] and [24] inch or [304.8] [457.2] and [609.6] millimeter locker widths
50. Double door designs shall consist of the following:
- a. Design available in [24] [30] and [36] inch or [609.6] [762.0] and [914.4] millimeter locker widths
 - b. Primary door located on the right and the secondary door located on the left-hand side of the locker.
 - c. Secondary door locking mechanism shall consist of the following:
 - 1) Return flange for supporting primary door
 - 2) Catch bracket
 - 3) One lower lock rod
51. All doors shall have neoprene silencers on each door for noise reduction
52. Door torsional deflection shall not exceed [0.1875] inch or [4.76] millimeter with a [20] lb or [9.071] kilogram point load. (Test data to be provided by manufacturer upon request)
53. Hinge:
- a. Provide 16-gauge full length hinge for increased strength and security of locker system.
 - b. Hinges to be welded to door frame with spot welds not to exceed [6] inch or [152.4] millimeter separation.
54. Door assembly to be riveted to door frame on factory pre-established hole pattern.
55. Locking Mechanism.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- a. Provide three locking options (all locking options have protective stainless steel cover plate for durability and scratch resistance):
 - 1) Padlock hasp only.
 - 2) Keyed lock with master and padlock hasp.
 - 3) Combination lock with master and padlock hasp.
- b. Keyed and combination locking mechanisms shall have the capability of locking automatically.
- c. Keyed and Combination locking mechanisms shall have master key override.
- d. Combination locking mechanism shall have user changeable preset combinations.
- e. Single door models: Provide three locking options as listed above.
- f. Double door models: Provide three locking options on the primary door and simple secure lift latch mechanism with [0.3125] inch or [7.94] millimeter lock rod for secondary door.

Interior/Accessory components:

- 56. All interior components must be constructed of minimum 18-gauge or [1.214] millimeter steel (unless otherwise clarified in specification).
- 57. For added security, internal component can be secured utilizing blind rivets, threaded fasteners, or bending specially designed tab.
- 58. All interior components available at time of order and as post-installation upgrades in the future.
- 59. Shelves (available all locker models)
 - a. Shelf with integral hanger bracket
 - 1) Size specified by locker width
 - 2) Hanger bracket designed with perforations on approximately [3] inch or [76.2] millimeter centers to insure clothing separation for optimum ventilation
 - 3) Performance: Uniform load rating [300] lbs or [136.08] kilograms
 - b. Plain
 - 1) Size specified by locker width
 - 2) Performance: Uniform load rating [100] lbs or [45.36] kilograms
 - c. Heavy Duty
 - 1) Size specified by locker width
 - 2) Performance: Uniform load rating [300] lbs or [136.08] kilograms
 - d. Perforated (use as drying rack)
 - 1) Size specified by locker width
 - 2) Tested performance: Uniform load rating [100] lbs or [45.36] kilograms

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- e. Shelf rear return flange stops minimum [0.50] inch or [12.7] millimeters short of locker back panel on order to allow air circulation throughout entire locker assembly
 - f. All performance test data shall be provided by manufacturer upon request.
 - g. Provide modular shelf with slots for connection with file dividers and shelf back stop. File dividers will aid in maintaining a neat and orderly locker system.
60. Provide lockable compartment for small valuables (available in all models except Multi-Tier)
- a. Lockable compartment shall be integral to modular shelf accessory
 - b. Provide a 14-gauge [1.897] millimeter padlock-able compartment door.
 - c. Provide [0.188] inch or [4.77] millimeter diameter zinc plated steel hinge rod.
 - d. Door to be mounted with zinc plated steel hinge rod and two shoulder washers for smooth, quiet operation.
 - e. Provide an 18-gauge or [1.214] millimeter hasp bracket for securing lockable compartment door.
61. Boot Tray
- a. Material – Rubber
 - b. Dimensions:
 - 1) Width – [12.90] inches or [327.7] millimeters
 - 2) Depth – [19.90] inches or [505.5] millimeters
 - 3) Height – [1.25] inches or [34.75] millimeters
 - c. Manufactured from Natural rubber compounds, environmentally friendly, durable, water repellant easily cleaned with soap and water, resistant to alkalis and weak acids, mold, mildew, and dust mites.
62. Body Armor Drying Rack
- a. Shall be available in bench drawer model widths of [18] [24] [30] [36] inch or [457.2] [609.6] [762.0] and [914.4] millimeters
 - b. Size of tray is controlled by locker width
 - c. Bottom of drying tray shall have louvered pattern to provide air circulation throughout
 - d. Shall have the ability to adjust/glide frontward and backward, while mounted in the bench drawer.
63. Hooks
- a. Hook Bracket Hanger Assembly – shall have the ability to attach a three-hook bracket assembly to any lanced location on the side panels of the locker.

Electrical system

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

- 64. UL listed manufactured electrical wiring system with plug-in-play component design
- 65. Receptacles – standard 20 amp duplex receptacles and 20 amp GFCI duplex receptacles
HVAC
- 66. All lockers (except Multi-Tier) shall be equipped with mechanical air extraction capabilities and adjustable air balancing capabilities
- 67. When mechanical air extraction is required, manufacturer shall provide locker system HVAC guidelines and recommendations to aid in overall locker and building system integration. It is the General Contractor and HVAC Contractors' responsibility to establish/balance air flow through locker system according to building HVAC constraints.
Locker Tag Numbers
- 68. Shall provide locker numbers on each locker per customer requirement
ACCESSORIES:
- 69. Trim and Fillers: Provide manufacturer's standard.

2.5 FABRICATION

General: Coordinate fabrication and delivery to ensure no delay in progress of the work.

2.6 FINISHES

Colors: Selected from manufacturer's standard available colors by Architect.

Paint Finish: Textured (Standard) – Provide factory applied electrostatic powder coat paint. Meet or exceed specifications of the American Society for Testing and Materials (ASTM) Standards:

PART 3 - EXECUTION

3.1 EXAMINATION

Examine Lockers scheduled to receive accessories with Installer present for compliance with requirements for installation tolerances and other conditions affecting performance of specified accessory items.

Proceed with accessory installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

General: Follow manufacturer's written instructions for installation of each type of accessory item specified.

3.3 FIELD QUALITY CONTROL

Verify accessory unit alignment and plumb after installation. Correct if required, following manufacturer's instructions.

Remove components that are chipped, scratched, or otherwise damaged and which do not match adjoining work. Replace with new matching units, installed as specified and in manner to eliminate evidence of replacement.

3.4 ADJUSTING

Adjust all accessories to provide smoothly operating, visually acceptable installation.

3.5 CLEANING

Immediately upon completion of installation, clean components and surfaces. Remove surplus materials, rubbish and debris, resulting from installation, upon completion of work and leave areas of installation in neat, clean condition.

**LOCKER ROOM RENOVATIONS
GLASTONBURY POLICE DEPARTMENT
GLASTONBURY, CONNECTICUT**

GLASTONBURY TRACKING NUMBER: GL-2017-26

3.6 DEMONSTRATION/TRAINING

Schedule and conduct demonstration of installed accessory items and features with Owner's personnel.

Schedule and conduct maintenance training with Owner's maintenance personnel. Training session should include lecture and demonstration of all maintenance and repair procedures that end-user personnel would normally perform.

3.7 PROTECTION

Protect system against damage during remainder of construction period. Advise owner of additional protection needed to ensure that system will be without damage or deterioration at time of substantial completion.

END OF SECTION