

# TOWN OF GLASTONBURY

## **BID GL-2010-08 EPOXY COATING FOR BAY – FIRE CO. #1 ADDENDUM #1**

**Dated: 6-16-09**

### **ADDITIONAL INFORMATION FOR THE ABOVE REFERENCED**

Please be advised that the following addenda item has been faxed to all known plan holders:

Section 3.02 (add)

F. Apply 4 inch wide line stripes at each door for trucks to back up with Polythane #2HS and add-a-color#4.

G. Apply final topcoat of ARMOR TOP at 3 mils and allow to cure.

3.03 DETAILS

- A. Saw-cut existing control joints after floor is complete and fill with backer rod; next apply Polyfill UJF, polyurea joint sealant.
- B. Pre-patch non-moving surface deviations with patching compound comprised of 100% solids epoxy and aggregate.
- C. “Key in” all drains, edges and transition points according to manufacturers instructions.
- D. Install a 4” integral cove base at perimeter walls.
- E. After floor is prepared with blastrac machine, use a roofing torch to burn off fiberglass strands from concrete substrate before priming floor.

END OF SECTION

**Please confirm receipt of this addendum via fax by 6-18-09 by 10:00 A.M to: Kathy Hughey @ (860) 652-7590 (fax)**

Company Name: \_\_\_\_\_

Name of Person Responding: \_\_\_\_\_

Authorized Signature: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_